

---

Subject: [RFC][PATCH 13/14] Define CLONE\_NEWPID flag  
Posted by [Sukadev Bhattiprolu](#) on Wed, 21 Mar 2007 03:24:17 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

This was discussed on containers and we thought it would be useful to reserve this flag.

---

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>  
Subject: [RFC][PATCH 13/14] Define CLONE\_NEWPID flag

Define CLONE\_NEWPID flag that will be used to clone pid namespaces.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

---

include/linux/sched.h | 1 +  
1 file changed, 1 insertion(+)

Index: 2.6.21-rc3-mm2/include/linux/sched.h

=====

--- 2.6.21-rc3-mm2.orig/include/linux/sched.h

+++ 2.6.21-rc3-mm2/include/linux/sched.h

@@ -26,6 +26,7 @@

#define CLONE\_STOPPED 0x02000000 /\* Start in stopped state \*/

#define CLONE\_NEWUTS 0x04000000 /\* New utsname group? \*/

#define CLONE\_NEWIPC 0x08000000 /\* New ipc \*/

+#define CLONE\_NEWPID 0x10000000 /\* New pid namespace \*/

/\*

\* Scheduling policies

--

---

Containers mailing list  
[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---