

---

Subject: - remove-the-likelypid-check-in-copy\_process.patch removed from -mm tree

Posted by [akpm](#) on Wed, 21 Mar 2007 18:27:51 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

The patch titled

Remove the likely(pid) check in copy\_process  
has been removed from the -mm tree. Its filename was  
remove-the-likelypid-check-in-copy\_process.patch

This patch was dropped because it had testing failures

---

-----  
Subject: Remove the likely(pid) check in copy\_process  
From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Now that we pass in a struct pid parameter to copy\_process() and even the swapper (pid\_t == 0) has a valid struct pid, we no longer need this check.

Changelog:

Per Eric Biederman's comments, moved this out to a separate patch for easier review.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Cc: Cedric Le Goater <clg@fr.ibm.com>

Cc: Dave Hansen <haveblue@us.ibm.com>

Cc: Serge Hallyn <serue@us.ibm.com>

Cc: <containers@lists.osdl.org>

Acked-by: Eric W. Biederman <ebiederm@xmission.com>

Signed-off-by: Andrew Morton <akpm@linux-foundation.org>

---

kernel/fork.c | 34 ++++++-----

1 file changed, 16 insertions(+), 18 deletions(-)

diff -puN kernel/fork.c~remove-the-likelypid-check-in-copy\_process kernel/fork.c

--- a/kernel/fork.c~remove-the-likelypid-check-in-copy\_process

+++ a/kernel/fork.c

@@ -1237,26 +1237,24 @@ static struct task\_struct \*copy\_process(

}

}

- if (likely(p->pid)) {

- add\_parent(p);

- tracehook\_init\_task(p);

-

- if (thread\_group\_leader(p)) {

```

- pid_t pgid = process_group(current);
- pid_t sid = process_session(current);
-
- p->signal->tty = current->signal->tty;
- p->signal->pgrp = pgid;
- set_signal_session(p->signal, process_session(current));
- attach_pid(p, PIDTYPE_PPID, find_pid(pgid));
- attach_pid(p, PIDTYPE_SID, find_pid(sid));
+ add_parent(p);
+ tracehook_init_task(p);

- list_add_tail_rcu(&p->tasks, &init_task.tasks);
- __get_cpu_var(process_counts)++;
- }
- attach_pid(p, PIDTYPE_PID, pid);
- nr_threads++;
+ if (thread_group_leader(p)) {
+ pid_t pgid = process_group(current);
+ pid_t sid = process_session(current);
+
+ p->signal->tty = current->signal->tty;
+ p->signal->pgrp = pgid;
+ set_signal_session(p->signal, process_session(current));
+ attach_pid(p, PIDTYPE_PPID, find_pid(pgid));
+ attach_pid(p, PIDTYPE_SID, find_pid(sid));
+
+ list_add_tail_rcu(&p->tasks, &init_task.tasks);
+ __get_cpu_var(process_counts)++;
}
+ attach_pid(p, PIDTYPE_PID, pid);
+ nr_threads++;

total_forks++;
spin_unlock(&current->sighand->siglock);
-
```

Patches currently in -mm which might be from sukadev@us.ibm.com are

attach\_pid-with-struct-pid-parameter.patch  
 statically-initialize-struct-pid-for-swapper.patch  
 explicitly-set-pgid-and-sid-of-init-process.patch  
 use-struct-pid-parameter-in-copy\_process.patch  
 use-task\_pgrp-task\_session-in-copy\_process.patch  
 kill-unused-session-and-group-values-in-rocket-driver.patch  
 fix-some-coding-style-errors-in-autofs.patch  
 replace-pid\_t-in-autofs-with-struct-pid-reference.patch

---

Containers mailing list  
Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---