
Subject: [PATCH] Define CLONE_NEWPID flag
Posted by [Sukadev Bhattiprolu](#) on Wed, 21 Mar 2007 19:41:03 GMT
[View Forum Message](#) <> [Reply to Message](#)

This was discussed on containers and we thought it would be useful to reserve this flag.

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [PATCH] Define CLONE_NEWPID flag

Define CLONE_NEWPID flag that will be used to clone pid namespaces.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

include/linux/sched.h | 1 +
1 file changed, 1 insertion(+)

Index: lx26-21-rc3-mm2/include/linux/sched.h

```
=====
--- lx26-21-rc3-mm2.orig/include/linux/sched.h 2007-03-20 20:13:19.000000000 -0700
+++ lx26-21-rc3-mm2/include/linux/sched.h 2007-03-21 11:10:33.000000000 -0700
@@ -26,6 +26,7 @@
#define CLONE_STOPPED 0x02000000 /* Start in stopped state */
#define CLONE_NEWUTS 0x04000000 /* New utsname group? */
#define CLONE_NEWIPC 0x08000000 /* New ipcns */
+#define CLONE_NEWPID 0x10000000 /* New pid namespace */

/*
 * Scheduling policies
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
