Subject: Re: [PATCH] Define CLONE_NEWPID flag Posted by akpm on Wed, 21 Mar 2007 20:39:38 GMT

View Forum Message <> Reply to Message

On Wed, 21 Mar 2007 12:41:03 -0700 sukadev@us.ibm.com wrote:

```
> This was discussed on containers and we thought it would be useful
> to reserve this flag.
> From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> Subject: [PATCH] Define CLONE_NEWPID flag
> Define CLONE_NEWPID flag that will be used to clone pid namespaces.
> Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> include/linux/sched.h |
  1 file changed, 1 insertion(+)
> Index: lx26-21-rc3-mm2/include/linux/sched.h
> --- lx26-21-rc3-mm2.orig/include/linux/sched.h 2007-03-20 20:13:19.000000000 -0700
> +++ lx26-21-rc3-mm2/include/linux/sched.h 2007-03-21 11:10:33.000000000 -0700
> @ @ -26,6 +26,7 @ @
> #define CLONE STOPPED 0x02000000 /* Start in stopped state */
> #define CLONE NEWUTS 0x04000000 /* New utsname group? */
> #define CLONE_NEWIPC 0x08000000 /* New ipcs */
> +#define CLONE NEWPID 0x10000000
                                           /* New pid namespace */
>
```

Do we actually have any need to reserve it at this time? I'd have thought that we could defer adding this until we have some code in-kernel which uses it.

Containers mailing list
Containers@lists.linux-foundation.org

https://lists.linux-foundation.org/mailman/listinfo/containers