
Subject: Re: [RFC][PATCH 13/14] Define CLONE_NEWPID flag
Posted by [Cedric Le Goater](#) on Wed, 21 Mar 2007 12:50:44 GMT
[View Forum Message](#) <> [Reply to Message](#)

sukadev@us.ibm.com wrote:

```
> This was discussed on containers and we thought it would be useful
> to reserve this flag.
> ---
>
> From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> Subject: [RFC][PATCH 13/14] Define CLONE_NEWPID flag
>
> Define CLONE_NEWPID flag that will be used to clone pid namespaces.
>
> Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
> ---
> include/linux/sched.h | 1 +
> 1 file changed, 1 insertion(+)
>
> Index: 2.6.21-rc3-mm2/include/linux/sched.h
> =====
> --- 2.6.21-rc3-mm2.orig/include/linux/sched.h
> +++ 2.6.21-rc3-mm2/include/linux/sched.h
> @@ -26,6 +26,7 @@
> #define CLONE_STOPPED 0x02000000 /* Start in stopped state */
> #define CLONE_NEWUTS 0x04000000 /* New utsname group? */
> #define CLONE_NEWIPC 0x08000000 /* New ipcs */
> +#define CLONE_NEWPID 0x10000000 /* New pid namespace */
>
> /*
>  * Scheduling policies
>
```

I think we can send this one to -mm.

thanks,

C.

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
