
Subject: Re: [PATCH] net: Add etun driver
Posted by [Patrick McHardy](#) on Tue, 10 Apr 2007 10:46:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

Johannes Berg wrote:

> On Tue, 2007-04-10 at 11:52 +0200, Patrick McHardy wrote:
>
>
>> Without having thought much about it yet, roughly like this:
>>
>>- driver receives RTM_NEWLINK message (under rtnl)
>>- driver allocates new device
>>- driver initializes device based on content of RTM_NEWLINK message
>>- driver returns
>
>
> Sounds good to me, but where's the advantage over something that isn't
> generic if RTM_NEWLINK contains totally different things depending on
> the subsystem like wireless where it'd have to contain the hardware
> identifier?

Not totally different, so far I think we should use the same attributes as for RTM_SETLINK messages and include the device-specific stuff in IFLA_PROTINFO, which is symmetric to what the kernel sends in RTM_NETLINK messages (see `br_netlink.c` for an example). The easiest case would be an empty IFLA_PROTINFO attribute, which would simply create a device without any configuration.

The main advantage that we don't get more weird sysfs/proc/ioctl based interfaces and use the same interface that is used for all other network configuration, which f.e. will allow to add support for all software devices to `iproute` without much effort, so you don't need 30 different tools for configuring the different software device types anymore. Additionally we get atomic setup/dumps and extensibility.

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
