

---

Subject: Re: [patch 1/8] add user mounts to the kernel

Posted by [akpm](#) on Sat, 21 Apr 2007 07:55:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

On Fri, 20 Apr 2007 12:25:33 +0200 Miklos Szeredi <[miklos@szeredi.hu](mailto:miklos@szeredi.hu)> wrote:

> From: Miklos Szeredi <[mszeredi@suse.cz](mailto:mszeredi@suse.cz)>

>

> Add ownership information to mounts.

>

> A new mount flag, MS\_SETUSER is used to make a mount owned by a user.

> If this flag is specified, then the owner will be set to the current

> real user id and the mount will be marked with the MNT\_USER flag. On

> remount don't preserve previous owner, and treat MS\_SETUSER as for a

> new mount. The MS\_SETUSER flag is ignored on mount move.

So is a modified mount(8) needed? If so, is there some convenient way in which testers can get hold of it?

> The MNT\_USER flag is not copied on any kind of mount cloning:

> namespace creation, binding or propagation. For bind mounts the

> cloned mount(s) are set to MNT\_USER depending on the MS\_SETUSER mount

> flag. In all the other cases MNT\_USER is always cleared.

>

> For MNT\_USER mounts a "user=UID" option is added to /proc/PID/mounts.

> This is compatible with how mount ownership is stored in /etc/mstab.

>

> Signed-off-by: Miklos Szeredi <[mszeredi@suse.cz](mailto:mszeredi@suse.cz)>

> ---

>

> Index: linux/fs/namespace.c

> =====

> --- linux.orig/fs/namespace.c 2007-04-20 11:55:02.000000000 +0200

> +++ linux/fs/namespace.c 2007-04-20 11:55:05.000000000 +0200

> @@ -227,6 +227,13 @@ static struct vfsmount \*skip\_mnt\_tree(st

> return p;

> }

>

> +static void set\_mnt\_user(struct vfsmount \*mnt)

> +{

> + BUG\_ON(mnt->mnt\_flags & MNT\_USER);

> + mnt->mnt\_uid = current->uid;

> + mnt->mnt\_flags |= MNT\_USER;

> +}

I'm a bit surprised to see this. Using uids in-kernel is all rather old-fashioned and restricted. I'd have expected

```
mnt->user = get_uid(current->user);
```

---

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>

---