

---

Subject: Changed gentoo-add\_ip.sh to work with baselayout-vserver-1.11.14-r3

Posted by [steffen.zieger](#) on Wed, 01 Mar 2006 09:13:24 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello,

I've fixed the gentoo-add\_ip.sh to work again with baselayout-vserver-1.11.14-r3.  
Also I've fixed a hardcoded venet0 where it wasn't necessary.

Here is a diff:

```
--- gentoo-add_ip.sh.orig      2006-03-01 09:46:27.806261592 +0100
+++ gentoo-add_ip.sh   2006-03-01 09:48:43.808586096 +0100
@@ -37,7 +37,7 @@
        rc-update del net.eth0 &>/dev/null
        ln -sf /etc/init.d/net.lo /etc/init.d/net.${VENET_DEV}
        rc-update add net.lo boot &>/dev/null
-       rc-update add net.venet0 default &>/dev/null
+       rc-update add net.${VENET_DEV} default &>/dev/null
         if ! grep -qe "^config_eth" ${IFCFG} 2>/dev/null; then
             return 0
         fi
@@ -54,7 +54,7 @@
     fix_net
     put_param3 ${IFCFG} "config_${VENET_DEV}" ""
     # add fake route
-    put_param3 ${IFCFG} "routes_${VENET_DEV}" "-net ${FAKEGATEWAYNET}/24"
+    put_param3 ${IFCFG} "routes_${VENET_DEV}" "-net ${FAKEGATEWAYNET} netmask
255.255.255.255 dev ${VENET_DEV}"
         add_param3 ${IFCFG} "routes_${VENET_DEV}" "default via ${FAKEGATEWAY}"
     # Set up /etc/hosts
     if [ ! -f ${HOSTFILE} ]; then
```

At the moment, I'm trying to get an gentoo-template for productivity to work.  
I'm in the last steps. There is only one problem left with disk quota.

HAND,  
Steffen

---