
Subject: [patch 41/68] Explicitly set pgid and sid of init process
Posted by [akpm](#) on Fri, 11 May 2007 05:23:01 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Explicitly set pgid and sid of init process to 1.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: Eric Biederman <ebiederm@xmission.com>
Cc: Herbert Poetzl <herbert@13thfloor.at>
Cc: <containers@lists.osdl.org>
Acked-by: Eric W. Biederman <ebiederm@xmission.com>
Signed-off-by: Andrew Morton <akpm@linux-foundation.org>

init/main.c | 1 +
1 file changed, 1 insertion(+)

```
diff -puN init/main.c~explicitly-set-pgid-and-sid-of-init-process init/main.c
--- a/init/main.c~explicitly-set-pgid-and-sid-of-init-process
+++ a/init/main.c
@@ -801,6 +801,7 @@ static int __init kernel_init(void * unu
 */
init_pid_ns.child_reaper = current;

+ __set_special_pids(1, 1);
cad_pid = task_pid(current);

smp_prepare_cpus(max_cpus);
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
