
Subject: [patch 44/68] Kill unused session and group values in rocket driver
Posted by [akpm](#) on Fri, 11 May 2007 05:23:05 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

The process_session() and process_group() values are not really used by the driver.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Cc: Cedric Le Goater <cclg@fr.ibm.com>

Cc: Dave Hansen <haveblue@us.ibm.com>

Cc: Serge Hallyn <serue@us.ibm.com>

Cc: <containers@lists.osdl.org>

Cc: Eric W. Biederman <ebiederm@xmission.com>

Signed-off-by: Andrew Morton <akpm@linux-foundation.org>

drivers/char/rocket.c | 3 ---

drivers/char/rocket_int.h | 2 --

2 files changed, 5 deletions(-)

```
diff -puN drivers/char/rocket.c~kill-unused-session-and-group-values-in-rocket-driver
drivers/char/rocket.c
```

```
--- a/drivers/char/rocket.c~kill-unused-sesssion-and-group-values-in-rocket-driver
```

```
+++ a/drivers/char/rocket.c
```

```
@@ -1014,9 +1014,6 @@ static int rp_open(struct tty_struct *tt
```

```
/*
```

```
 * Info->count is now 1; so it's safe to sleep now.
```

```
*/
```

```
- info->session = process_session(current);
```

```
- info->pgrp = process_group(current);
```

```
-
```

```
if ((info->flags & ROCKET_INITIALIZED) == 0) {
```

```
    cp = &info->channel;
```

```
    sSetRxTrigger(cp, TRIG_1);
```

```
diff -puN drivers/char/rocket_int.h~kill-unused-sesssion-and-group-values-in-rocket-driver
drivers/char/rocket_int.h
```

```
--- a/drivers/char/rocket_int.h~kill-unused-sesssion-and-group-values-in-rocket-driver
```

```
+++ a/drivers/char/rocket_int.h
```

```
@@ -1158,8 +1158,6 @@ struct r_port {
```

```
    int xmit_head;
```

```
    int xmit_tail;
```

```
    int xmit_cnt;
```

```
- int session;
```

```
- int pgrp;
```

```
    int cd_status;
```

```
    int ignore_status_mask;
```

```
int read_status_mask;
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
