
Subject: [patch 44/68] Kill unused sesssion and group values in rocket driver
Posted by [akpm](#) on Fri, 11 May 2007 05:23:05 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

The process_session() and process_group() values are not really used by the driver.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Cc: Cedric Le Goater <clg@fr.ibm.com>
Cc: Dave Hansen <haveblue@us.ibm.com>
Cc: Serge Hallyn <serue@us.ibm.com>
Cc: <containers@lists.osdl.org>
Cc: Eric W. Biederman <ebiederm@xmission.com>
Signed-off-by: Andrew Morton <akpm@linux-foundation.org>

```
drivers/char/rocket.c | 3 ---
drivers/char/rocket_int.h | 2 --
2 files changed, 5 deletions(-)
```

diff -puN drivers/char/rocket.c~kill-unused-sesssion-and-group-values-in-rocket-driver

drivers/char/rocket.c

--- a/drivers/char/rocket.c~kill-unused-sesssion-and-group-values-in-rocket-driver

+++ a/drivers/char/rocket.c

@@ -1014,9 +1014,6 @@ static int rp_open(struct tty_struct *tt

/*

* Info->count is now 1; so it's safe to sleep now.

*/

- info->session = process_session(current);

- info->pgrp = process_group(current);

-

if ((info->flags & ROCKET_INITIALIZED) == 0) {

cp = &info->channel;

sSetRxTrigger(cp, TRIG_1);

diff -puN drivers/char/rocket_int.h~kill-unused-sesssion-and-group-values-in-rocket-driver

drivers/char/rocket_int.h

--- a/drivers/char/rocket_int.h~kill-unused-sesssion-and-group-values-in-rocket-driver

+++ a/drivers/char/rocket_int.h

@@ -1158,8 +1158,6 @@ struct r_port {

int xmit_head;

int xmit_tail;

int xmit_cnt;

- int session;

- int pgrp;

int cd_status;

int ignore_status_mask;

```
int read_status_mask;
```

—

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
