

---

Subject: - explicitly-set-pgid-and-sid-of-init-process.patch removed from -mm tree  
Posted by [akpm](#) on Sat, 12 May 2007 05:34:32 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

The patch titled  
Explicitly set pgid and sid of init process  
has been removed from the -mm tree. Its filename was  
explicitly-set-pgid-and-sid-of-init-process.patch

This patch was dropped because it was merged into mainline or a subsystem tree

-----  
Subject: Explicitly set pgid and sid of init process  
From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Explicitly set pgid and sid of init process to 1.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>  
Cc: Cedric Le Goater <clg@fr.ibm.com>  
Cc: Dave Hansen <haveblue@us.ibm.com>  
Cc: Serge Hallyn <serue@us.ibm.com>  
Cc: Eric Biederman <ebiederm@xmission.com>  
Cc: Herbert Poetzl <herbert@13thfloor.at>  
Cc: <containers@lists.osdl.org>  
Acked-by: Eric W. Biederman <ebiederm@xmission.com>  
Signed-off-by: Andrew Morton <akpm@linux-foundation.org>

---

init/main.c | 1 +  
1 file changed, 1 insertion(+)

diff -puN init/main.c~explicitly-set-pgid-and-sid-of-init-process init/main.c

--- a/init/main.c~explicitly-set-pgid-and-sid-of-init-process

+++ a/init/main.c

@@ -801,6 +801,7 @@ static int \_\_init kernel\_init(void \* unu  
\*/

init\_pid\_ns.child\_reaper = current;

+ \_\_set\_special\_pids(1, 1);  
cad\_pid = task\_pid(current);

smp\_prepare\_cpus(max\_cpus);

—

Patches currently in -mm which might be from sukadev@us.ibm.com are

origin.patch

---

Containers mailing list  
Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---