Subject: [RFC][PATCH 09/16] Use pid ns from pid->upid_list
Posted by Sukadev Bhattiprolu on Thu, 24 May 2007 01:12:36 GMT
View Forum Message <> Reply to Message

Subject: Use pid ns from pid->upid_list

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

We need to decouple pid namespace from nsproxy to allow getting and releasing
pid namespace independently from other namespaces. This is required since a
process's reference to its pid namespace must exist even after its references
to other namespaces are dropped during process exit.

With multiple pid namespaces, a process can have different pid_t values in
different pid namespaces and 'struct upid' and the pid->upid_list list
provide this association of pid_t value with pid namespace for a process.

Use pid->upid_list list to find the active pid namespace of a process and
remove nsproxy->pid_namespace.

(Review note: My description of active pid namespace is probably long-winded.
Appreciate any comments in explaining it better :-)

TODO:
- Include pid_namespace in pid_hash() so processes with same pid_t
in different namespaces are on different hash lists.

Changelog:

2.6.21-mm2-pidns3:
- 'struct upid' used to be called 'struct pid_nr' and a list of these
were hanging off of 'struct pid'. So, we renamed 'struct pid_nr'
and now hold them in a statically sized array in 'struct pid' since
the number of 'struct upid's for a process is known at process-
creation time.

[2.6.21-rc3-mm2]
- Drop support for unshare() of pid namespace which simplifies cloning
of pid namespace and reorganize several functions.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>
---
include/linux/init_task.h | 1 -
include/linux/nsproxy.h | 2 --
include/linux/pid_namespace.h | 4 ++--
kernel/nsproxy.c | 10 ----------
kernel/pid.c | 23 ++++++++++++++++++++-------

```
 5 files changed, 18 insertions(+), 22 deletions(-)

Index: lx26-21-mm2/include/linux/init_task.h
===================================================================
--- lx26-21-mm2.orig/include/linux/init_task.h 2007-05-22 16:59:49.000000000 -0700
+++ lx26-21-mm2/include/linux/init_task.h 2007-05-22 16:59:50.000000000 -0700
@@ -72,7 +72,6 @@

 extern struct nsproxy init_nsproxy;
 #define INIT_NSPROXY(nsproxy) {      \
- .pid_ns  = &init_pid_ns,     \
  .count  = ATOMIC_INIT(1),    \
  .nslock  = __SPIN_LOCK_UNLOCKED(nsproxy.nslock),  \
  .uts_ns  = &init_uts_ns,     \
Index: lx26-21-mm2/include/linux/nsproxy.h
===================================================================
--- lx26-21-mm2.orig/include/linux/nsproxy.h 2007-05-22 16:58:37.000000000 -0700
+++ lx26-21-mm2/include/linux/nsproxy.h 2007-05-22 16:59:50.000000000 -0700
@@ -7,7 +7,6 @@
 struct mnt_namespace;
 struct uts_namespace;
 struct ipc_namespace;
-struct pid_namespace;

 /*
  * A structure to contain pointers to all per-process
@@ -27,7 +26,6 @@ struct nsproxy {
  struct uts_namespace *uts_ns;
  struct ipc_namespace *ipc_ns;
  struct mnt_namespace *mnt_ns;
- struct pid_namespace *pid_ns;
 };
 extern struct nsproxy init_nsproxy;

Index: lx26-21-mm2/include/linux/pid_namespace.h
===================================================================
--- lx26-21-mm2.orig/include/linux/pid_namespace.h 2007-05-22 16:59:49.000000000 -0700
+++ lx26-21-mm2/include/linux/pid_namespace.h 2007-05-22 16:59:50.000000000 -0700
@@ -41,8 +41,8 @@ static inline void get_pid_ns(struct pid
  kref_get(&ns->kref);
 }

-extern struct pid_namespace *copy_pid_ns(int flags, struct pid_namespace *ns);
 extern void free_pid_ns(struct kref *kref);
+extern struct pid_namespace *pid_active_pid_ns(struct pid *pid);

 static inline void put_pid_ns(struct pid_namespace *ns)
 {
```

```
@@ -51,7 +51,7 @@ static inline void put_pid_ns(struct pid

 static inline struct pid_namespace *task_active_pid_ns(struct task_struct *tsk)
 {
- return tsk->nsproxy->pid_ns;
+ return pid_active_pid_ns(task_pid(tsk));
 }

 static inline struct task_struct *task_child_reaper(struct task_struct *tsk)
Index: lx26-21-mm2/kernel/nsproxy.c
===================================================================
--- lx26-21-mm2.orig/kernel/nsproxy.c 2007-05-22 16:58:37.000000000 -0700
+++ lx26-21-mm2/kernel/nsproxy.c 2007-05-22 16:59:50.000000000 -0700
@@ -19,7 +19,6 @@
 #include <linux/init_task.h>
 #include <linux/mnt_namespace.h>
 #include <linux/utsname.h>
-#include <linux/pid_namespace.h>

 struct nsproxy init_nsproxy = INIT_NSPROXY(init_nsproxy);

@@ -75,15 +74,8 @@ static struct nsproxy *create_new_namesp
  if (IS_ERR(new_nsp->ipc_ns))
   goto out_ipc;

- new_nsp->pid_ns = copy_pid_ns(flags, tsk->nsproxy->pid_ns);
- if (IS_ERR(new_nsp->pid_ns))
-  goto out_pid;
-
  return new_nsp;

-out_pid:
- if (new_nsp->ipc_ns)
-  put_ipc_ns(new_nsp->ipc_ns);
 out_ipc:
  if (new_nsp->uts_ns)
   put_uts_ns(new_nsp->uts_ns);
@@ -138,8 +130,6 @@ void free_nsproxy(struct nsproxy *ns)
   put_uts_ns(ns->uts_ns);
  if (ns->ipc_ns)
   put_ipc_ns(ns->ipc_ns);
- if (ns->pid_ns)
-  put_pid_ns(ns->pid_ns);
  kfree(ns);
 }

Index: lx26-21-mm2/kernel/pid.c
===================================================================
```

```
--- lx26-21-mm2.orig/kernel/pid.c 2007-05-22 16:59:49.000000000 -0700
+++ lx26-21-mm2/kernel/pid.c 2007-05-22 16:59:50.000000000 -0700
@@ -242,6 +242,22 @@ static int init_upid(struct upid *upid,
  return 0;
 }

+static struct upid *pid_active_upid(struct pid *pid)
+{
+ return &pid->upid_list[0];
+}
+
+/*
+ * Return the active pid namespace of the process @pid.
+ *
+ * Note: At present, there is only one pid namespace (init_pid_ns).
+ */
+struct pid_namespace *pid_active_pid_ns(struct pid *pid)
+{
+ return pid_active_upid(pid)->pid_ns;
+}
+EXPORT_SYMBOL_GPL(pid_active_pid_ns);
+
 /*
  * Return the pid_t by which the process @pid is known in the pid
  * namespace @ns.
@@ -515,13 +531,6 @@ struct pid *find_ge_pid(int nr)
 }
 EXPORT_SYMBOL_GPL(find_get_pid);

-struct pid_namespace *copy_pid_ns(int flags, struct pid_namespace *old_ns)
-{
- BUG_ON(!old_ns);
- get_pid_ns(old_ns);
- return old_ns;
-}
-
 void free_pid_ns(struct kref *kref)
 {
  struct pid_namespace *ns;
```

_____
Containers mailing list
Containers@lists.linux-foundation.org
https://lists.linux-foundation.org/mailman/listinfo/containers