
Subject: [RFC][PATCH 10/16] Define CLONE_NEWPID flag
Posted by [Sukadev Bhattiprolu](#) on Thu, 24 May 2007 01:13:03 GMT
[View Forum Message](#) <> [Reply to Message](#)

Subject: Define CLONE_NEWPID flag

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

This was discussed on containers and we thought it would be useful to reserve this flag.

TODO: Merge this with the next patch ?

Define CLONE_NEWPID flag that will be used to clone pid namespaces.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

include/linux/sched.h | 1 +
1 file changed, 1 insertion(+)

Index: lx26-21-mm2/include/linux/sched.h

=====

--- lx26-21-mm2.orig/include/linux/sched.h 2007-05-22 16:59:46.000000000 -0700

+++ lx26-21-mm2/include/linux/sched.h 2007-05-22 16:59:51.000000000 -0700

@@ -26,6 +26,7 @@

#define CLONE_STOPPED 0x02000000 /* Start in stopped state */

#define CLONE_NEWUTS 0x04000000 /* New utsname group? */

#define CLONE_NEWIPC 0x08000000 /* New ipcs */

+#define CLONE_NEWPID 0x10000000 /* New pid namespace */

/*

* Scheduling policies

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
