

---

Subject: [RFC][PATCH 10/16] Define CLONE\_NEWPID flag  
Posted by [Sukadev Bhattiprolu](#) on Thu, 24 May 2007 01:13:03 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Subject: Define CLONE\_NEWPID flag

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

This was discussed on containers and we thought it would be useful to reserve this flag.

TODO: Merge this with the next patch ?

Define CLONE\_NEWPID flag that will be used to clone pid namespaces.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

---

include/linux/sched.h | 1 +  
1 file changed, 1 insertion(+)

Index: lx26-21-mm2/include/linux/sched.h

```
=====
--- lx26-21-mm2.orig/include/linux/sched.h 2007-05-22 16:59:46.000000000 -0700
+++ lx26-21-mm2/include/linux/sched.h 2007-05-22 16:59:51.000000000 -0700
@@ -26,6 +26,7 @@
#define CLONE_STOPPED 0x02000000 /* Start in stopped state */
#define CLONE_NEWUTS 0x04000000 /* New utsname group? */
#define CLONE_NEWIPC 0x08000000 /* New ipcs */
+#define CLONE_NEWPID 0x10000000 /* New pid namespace */

/*
 * Scheduling policies
```

---

Containers mailing list  
[Containers@lists.linux-foundation.org](mailto:Containers@lists.linux-foundation.org)  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---