
Subject: [patch 07/22] ext4: remove extra IS_RDONLY() check
Posted by [Cedric Le Goater](#) on Thu, 07 Jun 2007 15:25:34 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Dave Hansen <hansendc@us.ibm.com>

ext4_change_inode_journal_flag() is only called from one location: ext4_ioctl(EXT3_IOC_SETFLAGS). That ioctl case already has a IS_RDONLY() call in it so this one is superfluous.

Signed-off-by: Dave Hansen <hansendc@us.ibm.com>

fs/ext4/inode.c | 2 +-
1 file changed, 1 insertion(+), 1 deletion(-)

Index: 2.6.22-rc4-mm2-robindmount/fs/ext4/inode.c

=====

--- 2.6.22-rc4-mm2-robindmount.orig/fs/ext4/inode.c

+++ 2.6.22-rc4-mm2-robindmount/fs/ext4/inode.c

@@ -3359,7 +3359,7 @@ int ext4_change_inode_journal_flag(struc
*/

journal = EXT4_JOURNAL(inode);
- if (is_journal_aborted(journal) || IS_RDONLY(inode))
+ if (is_journal_aborted(journal))
return -EROFS;

jbd2_journal_lock_updates(journal);

--

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
