

---

Subject: [patch 17/22] elevate write count over calls to vfs\_rename()

Posted by [Cedric Le Goater](#) on Thu, 07 Jun 2007 15:25:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

From: Dave Hansen <[hansendc@us.ibm.com](mailto:hansendc@us.ibm.com)>

This also creates a little helper in the NFS code to  
make an if() a little bit less ugly.

Signed-off-by: Dave Hansen <[hansendc@us.ibm.com](mailto:hansendc@us.ibm.com)>

---

---

```
fs/namei.c |  4 +++
fs/nfsd/vfs.c | 23 ++++++=====
2 files changed, 23 insertions(+), 4 deletions(-)
```

Index: 2.6.22-rc4-mm2-robindmount/fs/namei.c

=====

```
--- 2.6.22-rc4-mm2-robindmount.orig/fs/namei.c
+++ 2.6.22-rc4-mm2-robindmount/fs/namei.c
@@ -2627,8 +2627,12 @@ static int do_rename(int oldfd, const c
    if (new_dentry == trap)
        goto exit5;
```

```
+ error = mnt_want_write(oldnd.mnt);
+ if (error)
+     goto exit5;
    error = vfs_rename(old_dir->d_inode, old_dentry,
                       new_dir->d_inode, new_dentry);
+ mnt_drop_write(oldnd.mnt);
exit5:
    dput(new_dentry);
exit4:
```

Index: 2.6.22-rc4-mm2-robindmount/fs/nfsd/vfs.c

=====

```
--- 2.6.22-rc4-mm2-robindmount.orig/fs/nfsd/vfs.c
+++ 2.6.22-rc4-mm2-robindmount/fs/nfsd/vfs.c
@@ -1554,6 +1554,14 @@ out_nfserr:
    goto out_unlock;
}

+static inline int svc_msnfs(struct svc_fh *ffhp)
+{
+#ifdef MSNFS
+    return (ffhp->fh_export->ex_flags & NFSEXP_MSNFS);
+#else
+    return 0;
}
```

```

+#endif
+}
/*
 * Rename a file
 * N.B. After this call _both_ ffhp and tfhp need an fh_put
@@ -1615,13 +1623,20 @@ nfsd_rename(struct svc_rqst *rqstp, stru
if (ndentry == trap)
    goto out_dput_new;

#ifndef MSNFS
- if ((ffhp->fh_export->ex_flags & NFSEXP_MSNFS) &&
+ if (svc_msnfs(ffhp) &&
    ((atomic_read(&odentry->d_count) > 1)
     || (atomic_read(&ndentry->d_count) > 1))) {
    host_err = -EPERM;
- } else
-#endif
+    goto out_dput_new;
+ }
+
+ host_err = -EXDEV;
+ if (ffhp->fh_export->ex_mnt != tfhp->fh_export->ex_mnt)
+    goto out_dput_new;
+ host_err = mnt_want_write(ffhp->fh_export->ex_mnt);
+ if (host_err)
+    goto out_dput_new;
+
host_err = vfs_rename(fdir, odentry, tdir, ndentry);
if (!host_err && EX_ISSYNC(tfhp->fh_export)) {
    host_err = nfsd_sync_dir(ndentry);

--
```

---

Containers mailing list  
 Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---