
Subject: Re: [0/1] [patch -mm] Add containerstats (v3)

Posted by [akpm](#) on Sat, 09 Jun 2007 08:17:40 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Sat, 9 Jun 2007 01:07:53 -0700 "Paul Menage" <menage@google.com> wrote:

> On 6/9/07, Andrew Morton <akpm@linux-foundation.org> wrote:

> >

> > - CONTAINER_DEBUG should depend on CONTAINERS

>

> CONTAINER_DEBUG is actually a container subsystem whose sole purpose

> is to provide debugging information about any hierarchy that it's

> mounted as a part of. So in some senses it's in the same boat as

> something like cpusets or the RSS controller. CONFIG_CONTAINER_DEBUG

> doesn't affect any of the container framework code.

Oh, that's right.

But it still should depend on CONTAINERS

> >

> > - the CPUSETS && SMP is weird and should be deleted, unless I'm missing

> > something

>

> Cpusets depends on SMP in the vanilla tree, so that's not anything new

> that I added.

Oh, OK, so CPUSETS is not a client of CONTAINERS: so it depends on CONTAINERS

> >

> > - CONTAINERS should depend on CPUSETS

>

> You mean the other way around?

yup

> >

> > - That leaves CONTAINER_CPUACCT.

>

> Really, CONTAINER_CPUACCT should have the same relationship to

> CONTAINERS as CPUSETS does.

>

Would it not be simplest to have CONTAINERS as the top-level user-configurable item and to then have everything else depend on it?

select is a nasty thing - we repeatedly have problems when using it.

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
