
Subject: Re: PATCH -mm] fix create_new_namespaces() return value
Posted by [Badari Pulavarty](#) on Mon, 11 Jun 2007 16:22:52 GMT
[View Forum Message](#) <> [Reply to Message](#)

Cedric Le Goater wrote:

>The following patch modifies create_new_namespaces() to also use the
>errors returned by the copy_*_ns routines and not to systematically
>return ENOMEM.
>

In my initial version, I did same. It doesn't work :(

copy_*_ns() routines doesn't return any errors. All they return is NULL
in case of a
failure + with the exception of copy_mnt_ns, there are no other failure
cases.

So, there is no way to find out why the copy_*_ns() routines failed from
create_new_namespaces().

If you really really want to do this, change all copy_*_ns() routines to
returns meaningful
errors instead of NULL.

>
>

>Signed-off-by: Cedric Le Goater <clg@fr.ibm.com>
>Cc: Serge E. Hallyn <serue@us.ibm.com>
>Cc: Badari Pulavarty <pbadari@us.ibm.com>
>Cc: Pavel Emelianov <xemul@openvz.org>
>Cc: Herbert Poetzl <herbert@13thfloor.at>
>Cc: Eric W. Biederman <ebiederm@xmission.com>

>---

> kernel/nsproxy.c | 23 ++++++++-----

> 1 file changed, 17 insertions(+), 6 deletions(-)

>

>Index: 2.6.22-rc4-mm2/kernel/nsproxy.c

>=====

>--- 2.6.22-rc4-mm2.orig/kernel/nsproxy.c

>+++ 2.6.22-rc4-mm2/kernel/nsproxy.c

>@@ -58,30 +58,41 @@ static struct nsproxy *create_new_namesp

> struct fs_struct *new_fs)

> {

> struct nsproxy *new_nsp;

>+ int err;

>

> new_nsp = clone_nsproxy(tsk->nsproxy);

> if (!new_nsp)

> return ERR_PTR(-ENOMEM);

```

>
> new_nsp->mnt_ns = copy_mnt_ns(flags, tsk->nsproxy->mnt_ns, new_fs);
>- if (IS_ERR(new_nsp->mnt_ns))
>+ if (IS_ERR(new_nsp->mnt_ns)) {
>+ err = PTR_ERR(new_nsp->mnt_ns);
> goto out_ns;
>+ }
>
> new_nsp->uts_ns = copy_utsname(flags, tsk->nsproxy->uts_ns);
>- if (IS_ERR(new_nsp->uts_ns))
>+ if (IS_ERR(new_nsp->uts_ns)) {
>+ err = PTR_ERR(new_nsp->uts_ns);
> goto out_uts;
>+ }
>
> new_nsp->ipc_ns = copy_ipcs(flags, tsk->nsproxy->ipc_ns);
>- if (IS_ERR(new_nsp->ipc_ns))
>+ if (IS_ERR(new_nsp->ipc_ns)) {
>+ err = PTR_ERR(new_nsp->ipc_ns);
> goto out_ipc;
>+ }
>
> new_nsp->pid_ns = copy_pid_ns(flags, tsk->nsproxy->pid_ns);
>- if (IS_ERR(new_nsp->pid_ns))
>+ if (IS_ERR(new_nsp->pid_ns)) {
>+ err = PTR_ERR(new_nsp->pid_ns);
> goto out_pid;
>+ }
>
> new_nsp->user_ns = copy_user_ns(flags, tsk->nsproxy->user_ns);
>- if (IS_ERR(new_nsp->user_ns))
>+ if (IS_ERR(new_nsp->user_ns)) {
>+ err = PTR_ERR(new_nsp->user_ns);
>
Hmm.. copy_user_ns() ? I don't see this in rc4-mm2.

```

Thanks,
Badari

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
