
Subject: [PATCH 3/6] Rename child_reaper function.
Posted by [Sukadev Bhattiprolu](#) on Fri, 06 Jul 2007 05:54:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

Subject: [PATCH 3/6] Rename child_reaper function.

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Rename the child_reaper() function to task_child_reaper() to be similar to other task_* functions and to distinguish the function from 'struct pid_namespace.child_reaper'.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

```
fs/exec.c          | 2 +-
include/linux/pid_namespace.h | 2 +-
kernel/exit.c      | 4 +++-
kernel/signal.c    | 2 +-
4 files changed, 5 insertions(+), 5 deletions(-)
```

Index: lx26-22-rc6-mm1/include/linux/pid_namespace.h

```
=====
--- lx26-22-rc6-mm1.orig/include/linux/pid_namespace.h 2007-07-05 18:53:48.000000000 -0700
+++ lx26-22-rc6-mm1/include/linux/pid_namespace.h 2007-07-05 18:56:53.000000000 -0700
@@ -42,7 +42,7 @@ static inline struct pid_namespace *task
    return tsk->nsproxy->pid_ns;
}
```

```
-static inline struct task_struct *child_reaper(struct task_struct *tsk)
+static inline struct task_struct *task_child_reaper(struct task_struct *tsk)
{
    return init_pid_ns.child_reaper;
}
```

Index: lx26-22-rc6-mm1/fs/exec.c

```
=====
--- lx26-22-rc6-mm1.orig/fs/exec.c 2007-07-05 18:53:48.000000000 -0700
+++ lx26-22-rc6-mm1/fs/exec.c 2007-07-05 18:56:53.000000000 -0700
@@ -826,7 +826,7 @@ static int de_thread(struct task_struct
    * Reparenting needs write_lock on tasklist_lock,
    * so it is safe to do it under read_lock.
    */
- if (unlikely(tsk->group_leader == child_reaper(tsk)))
+ if (unlikely(tsk->group_leader == task_child_reaper(tsk)))
    task_active_pid_ns(tsk)->child_reaper = tsk;
```

```
    zap_other_threads(tsk);
```

Index: lx26-22-rc6-mm1/kernel/exit.c

```

=====
--- lx26-22-rc6-mm1.orig/kernel/exit.c 2007-07-05 18:53:48.000000000 -0700
+++ lx26-22-rc6-mm1/kernel/exit.c 2007-07-05 18:56:53.000000000 -0700
@@ -695,7 +695,7 @@ forget_original_parent(struct task_struct
do {
    reaper = next_thread(reaper);
    if (reaper == father) {
-   reaper = child_reaper(father);
+   reaper = task_child_reaper(father);
    break;
}
} while (reaper->exit_state);
@@ -908,7 +908,7 @@ fastcall NORET_TYPE void do_exit(long co
panic("Aiee, killing interrupt handler!");
if (unlikely(!tsk->pid))
panic("Attempted to kill the idle task!");
- if (unlikely(tsk == child_reaper(tsk))) {
+ if (unlikely(tsk == task_child_reaper(tsk))) {
    if (task_active_pid_ns(tsk) != &init_pid_ns)
        task_active_pid_ns(tsk)->child_reaper =
            init_pid_ns.child_reaper;
Index: lx26-22-rc6-mm1/kernel/signal.c
=====
--- lx26-22-rc6-mm1.orig/kernel/signal.c 2007-07-05 18:53:42.000000000 -0700
+++ lx26-22-rc6-mm1/kernel/signal.c 2007-07-05 18:56:53.000000000 -0700
@@ -1853,7 +1853,7 @@ relock:
    * within that pid space. It can of course get signals from
    * its parent pid space.
    */
- if (current == child_reaper(current))
+ if (current == task_child_reaper(current))
    continue;

    if (sig_kernel_stop(signr)) {

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
