

---

Subject: [PATCH 4/6] Use pid\_to\_nr() in process info functions  
Posted by [Sukadev Bhattiprolu](#) on Fri, 06 Jul 2007 05:55:12 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Subject: [PATCH 4/6] Use pid\_to\_nr() in process info functions

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>

Use pid\_to\_nr() function in getppid(), getpgid() and getsid() functions  
so they return the correct pid\_t for processes in multiple pid namespaces.

Note: We don't need pid\_to\_nr() in getpid() because the process always  
"sees itself" as being in its active pid namespace. Using pid\_to\_nr()  
in getpid() would unnecessarily hurt its performance.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

---  
include/linux/sched.h | 24 +++++  
kernel/sys.c | 10 +++++  
kernel/timer.c | 2 +-  
3 files changed, 30 insertions(+), 6 deletions(-)

Index: lx26-22-rc6-mm1/include/linux/sched.h

```
=====
--- lx26-22-rc6-mm1.orig/include/linux/sched.h 2007-07-05 18:53:42.000000000 -0700
+++ lx26-22-rc6-mm1/include/linux/sched.h 2007-07-05 18:57:34.000000000 -0700
@@ -1200,6 +1200,30 @@ static inline struct pid *task_tgid(stru
     return task->group_leader->pids[PIDTYPE_PID].pid;
 }

+/* NOTE: Caller must hold rcu_readlock() */
+static inline struct pid *task_parent_tgid(struct task_struct *task)
+{
+    return task_tgid(rcu_dereference(task->real_parent));
+}
+
+/* NOTE: Caller must hold rcu_readlock() */
+static inline struct pid *task_parent_pid(struct task_struct *task)
+{
+    return task_pid(rcu_dereference(task->real_parent));
+}
+
+/* NOTE: Caller must hold rcu_readlock() */
+static inline struct pid *task_tracer_tgid(struct task_struct *task)
+{
+    return task_tgid(rcu_dereference(task->parent));
+}
+
```

```

+/* NOTE: Caller must hold rcu_readlock() */
+static inline struct pid *task_tracer_pid(struct task_struct *task)
+{
+ return task_pid(rcu_dereference(task->parent));
+}
+

```

```

static inline struct pid *task_pgrp(struct task_struct *task)
{
    return task->group_leader->pids[PIDTYPE_PGID].pid;
}

```

Index: lx26-22-rc6-mm1/kernel/timer.c

=====

--- lx26-22-rc6-mm1.orig/kernel/timer.c 2007-07-05 18:53:42.000000000 -0700

+++ lx26-22-rc6-mm1/kernel/timer.c 2007-07-05 18:57:34.000000000 -0700

@@ -971,7 +971,7 @@ asmlinkage long sys\_getppid(void)

```

    int pid;

    rcu_read_lock();
- pid = rcu_dereference(current->real_parent)->tgid;
+ pid = pid_to_nr(task_parent_tgid(current));
    rcu_read_unlock();

```

```

    return pid;

```

Index: lx26-22-rc6-mm1/kernel/sys.c

=====

--- lx26-22-rc6-mm1.orig/kernel/sys.c 2007-07-05 18:53:42.000000000 -0700

+++ lx26-22-rc6-mm1/kernel/sys.c 2007-07-05 18:57:34.000000000 -0700

@@ -1503,7 +1503,7 @@ out:

asmlinkage long sys\_getpgid(pid\_t pid)

```

{
    if (!pid)
- return process_group(current);
+ return pid_to_nr(task_pgrp(current));
    else {
        int retval;
        struct task_struct *p;
@@ -1515,7 +1515,7 @@ asmlinkage long sys_getpgid(pid_t pid)
        if (p) {
            retval = security_task_getpgid(p);
            if (!retval)
- retval = process_group(p);
+ retval = pid_to_nr(task_pgrp(p));
        }
        read_unlock(&tasklist_lock);
        return retval;
@@ -1527,7 +1527,7 @@ asmlinkage long sys_getpgid(pid_t pid)
asmlinkage long sys_getpgrp(void)
{

```

```

/* SMP - assuming writes are word atomic this is fine */

```

```

- return process_group(current);
+ return pid_to_nr(task_pgrp(current));
}

#endif
@@ -1535,7 +1535,7 @@ asmlinkage long sys_getpgrp(void)
asmlinkage long sys_getsid(pid_t pid)
{
    if (!pid)
- return process_session(current);
+ return pid_to_nr(task_session(current));
    else {
        int retval;
        struct task_struct *p;
@@ -1547,7 +1547,7 @@ asmlinkage long sys_getsid(pid_t pid)
        if (p) {
            retval = security_task_getsid(p);
            if (!retval)
-         retval = process_session(p);
+         retval = pid_to_nr(task_session(p));
        }
        read_unlock(&tasklist_lock);
        return retval;

```

---

Containers mailing list  
Containers@lists.linux-foundation.org  
<https://lists.linux-foundation.org/mailman/listinfo/containers>

---