
Subject: [PATCH 1/3] Round up the API

Posted by [Pavel Emelianov](#) on Tue, 10 Jul 2007 14:21:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

The set of functions process_session, task_session, process_group and task_pgrp is confusing, as the names can be mixed with each other when looking at the code for a long time.

The proposals are to

- * equip the functions that return the integer with _nr suffix to represent that fact,
- * and to make all functions work with task (not process) by making the common prefix of the same name.

For monotony the routines signal_session() and set_signal_session() are replaced with task_session_nr() and set_task_session(), especially since they are only used with the explicit task->signal dereference.

Signed-off-by: Pavel Emelianov <xemul@openvz.org>

Acked-by: Serge E. Hallyn <serue@us.ibm.com>

```
diff --git a/arch/mips/kernel/irixelf.c b/arch/mips/kernel/irixelf.c
index 403d96f..10ba0a5 100644
--- a/arch/mips/kernel/irixelf.c
+++ b/arch/mips/kernel/irixelf.c
@@ -1170,8 +1170,8 @@ static int irix_core_dump(long signr, st
    prstatus.pr_sighold = current->blocked.sig[0];
    psinfo.pr_pid = prstatus.pr_pid = current->pid;
    psinfo.pr_ppid = prstatus.pr_ppid = current->parent->pid;
-   psinfo.pr_pgrp = prstatus.pr_pgrp = process_group(current);
-   psinfo.pr_sid = prstatus.pr_sid = process_session(current);
+   psinfo.pr_pgrp = prstatus.pr_pgrp = task_pgrp_nr(current);
+   psinfo.pr_sid = prstatus.pr_sid = task_session_nr(current);
    if (current->pid == current->tgid) {
        /*
         * This is the record for the group leader. Add in the

```

```
diff --git a/arch/mips/kernel/irixsig.c b/arch/mips/kernel/irixsig.c
index 6980deb..210503e 100644
--- a/arch/mips/kernel/irixsig.c
+++ b/arch/mips/kernel/irixsig.c
@@ -609,7 +609,7 @@ repeat:
```

```
    p = list_entry(_p,struct task_struct,sibling);
    if ((type == IRIX_P_PID) && p->pid != pid)
        continue;
-   if ((type == IRIX_P_PGID) && process_group(p) != pid)
+   if ((type == IRIX_P_PGID) && task_pgrp_nr(p) != pid)
```

```

continue;
if ((p->exit_signal != SIGCHLD))
    continue;
diff --git a/arch/mips/kernel/sysirix.c b/arch/mips/kernel/sysirix.c
index 93a1484..23c3e82 100644
--- a/arch/mips/kernel/sysirix.c
+++ b/arch/mips/kernel/sysirix.c
@@ -763,11 +763,11 @@ asmlinkage int irix_setpgrp(int flags)
    printk("[%s:%d] setpgrp(%d) ", current->comm, current->pid, flags);
#endif
    if(!flags)
-    error = process_group(current);
+    error = task_pgrp_nr(current);
    else
        error = sys_setsid();
#ifndef DEBUG_PROCGRPS
-    printk("returning %d\n", process_group(current));
+    printk("returning %d\n", task_pgrp_nr(current));
#endif

    return error;
diff --git a/arch/sparc64/solaris/misc.c b/arch/sparc64/solaris/misc.c
index 3b67de7..c86cb30 100644
--- a/arch/sparc64/solaris/misc.c
+++ b/arch/sparc64/solaris/misc.c
@@ -415,7 +415,7 @@ asmlinkage int solaris_procids(int cmd,
switch (cmd) {
case 0: /* getpgrp */
-    return process_group(current);
+    return task_pgrp_nr(current);
case 1: /* setpgrp */
{
    int (*sys_setpgid)(pid_t,pid_t) =
@@ -426,7 +426,7 @@ asmlinkage int solaris_procids(int cmd,
    ret = sys_setpgid(0, 0);
    if (ret) return ret;
    proc_clear_tty(current);
-    return process_group(current);
+    return task_pgrp_nr(current);
}
case 2: /* getsid */
{
diff --git a/drivers/char/tty_io.c b/drivers/char/tty_io.c
index de37ebc..a58ea84 100644
--- a/drivers/char/tty_io.c
+++ b/drivers/char/tty_io.c
@@ -3501,7 +3501,7 @@ void __do_SAK(struct tty_struct *tty)

```

```

/* Kill the entire session */
do_each_pid_task(session, PIDTYPE_SID, p) {
    printk(KERN_NOTICE "SAK: killed process %d"
-   " (%s): process_session(p)==tty->session\n",
+   " (%s): task_session_nr(p)==tty->session\n",
        p->pid, p->comm);
    send_sig(SIGKILL, p, 1);
} while_each_pid_task(session, PIDTYPE_SID, p);
@@ -3511,7 +3511,7 @@ void __do_SAK(struct tty_struct *tty)
do_each_thread(g, p) {
    if (p->signal->tty == tty) {
        printk(KERN_NOTICE "SAK: killed process %d"
-       " (%s): process_session(p)==tty->session\n",
+       " (%s): task_session_nr(p)==tty->session\n",
            p->pid, p->comm);
        send_sig(SIGKILL, p, 1);
        continue;
diff --git a/fs/autofs/inode.c b/fs/autofs/inode.c
index e7204d7..45f5992 100644
--- a/fs/autofs/inode.c
+++ b/fs/autofs/inode.c
@@ -80,7 +80,7 @@ static int parse_options(char *options,
    *uid = current->uid;
    *gid = current->gid;
- *pgrp = process_group(current);
+ *pgrp = task_pgrp_nr(current);

    *minproto = *maxproto = AUTOFS_PROTO_VERSION;

diff --git a/fs/autofs/root.c b/fs/autofs/root.c
index c148953..592f640 100644
--- a/fs/autofs/root.c
+++ b/fs/autofs/root.c
@@ -215,7 +215,7 @@ static struct dentry *autofs_root_lookup
    oz_mode = autofs_oz_mode(sbi);
    DPRINK(("autofs_lookup: pid = %u, pgrp = %u, catatonic = %d, "
        "oz_mode = %d\n", pid_nr(task_pid(current)),
-       process_group(current), sbi->catatonic,
+       task_pgrp_nr(current), sbi->catatonic,
        oz_mode));

/*
@@ -536,7 +536,7 @@ static int autofs_root_ioctl(struct inode
    struct autofs_sb_info *sbi = autofs_sbi(inode->i_sb);
    void __user *argp = (void __user *)arg;

- DPRINK(("autofs_ioctl: cmd = 0x%08x, arg = 0x%08lx, sbi = %p, pgrp =

```

```
%u\n",cmd,arg,sbi,process_group(current)));
+ DPRINK(("autofs_ioctl: cmd = 0x%08x, arg = 0x%08lx, sbi = %p, pgrp =
%u\n",cmd,arg,sbi,task_pgrp_nr(current)));

if (_IOC_TYPE(cmd) != _IOC_TYPE(AUTOFS_IOC_FIRST) ||
    _IOC_NR(cmd) - _IOC_NR(AUTOFS_IOC_FIRST) >= AUTOFS_IOC_COUNT)
diff --git a/fs/autofs4/autofs_i.h b/fs/autofs4/autofs_i.h
index d85f42f..2d4ae40 100644
--- a/fs/autofs4/autofs_i.h
+++ b/fs/autofs4/autofs_i.h
@@ -131,7 +131,7 @@ static inline struct autofs_info *autofs
    filesystem without "magic".) */

static inline int autofs4_oz_mode(struct autofs_sb_info *sbi) {
- return sbi->catatonic || process_group(current) == sbi->oz_pgrp;
+ return sbi->catatonic || task_pgrp_nr(current) == sbi->oz_pgrp;
}

/* Does a dentry have some pending activity? */
diff --git a/fs/autofs4/inode.c b/fs/autofs4/inode.c
index 692364e..32a39b0 100644
--- a/fs/autofs4/inode.c
+++ b/fs/autofs4/inode.c
@@ -226,7 +226,7 @@ static int parse_options(char *options,
*uid = current->uid;
*gid = current->gid;
- *pgrp = process_group(current);
+ *pgrp = task_pgrp_nr(current);

*minproto = AUTOFS_MIN_PROTO_VERSION;
*maxproto = AUTOFS_MAX_PROTO_VERSION;
@@ -325,7 +325,7 @@ int autofs4_fill_super(struct super_block
    sbi->pipe = NULL;
    sbi->catatonic = 1;
    sbi->exp_timeout = 0;
-    sbi->oz_pgrp = process_group(current);
+    sbi->oz_pgrp = task_pgrp_nr(current);
    sbi->sb = s;
    sbi->version = 0;
    sbi->sub_version = 0;
diff --git a/fs/autofs4/root.c b/fs/autofs4/root.c
index 2d4c8a3..c766ff8 100644
--- a/fs/autofs4/root.c
+++ b/fs/autofs4/root.c
@@ -582,7 +582,7 @@ static struct dentry *autofs4_lookup(str
    oz_mode = autofs4_oz_mode(sbi);
```

```

DPRINTK("pid = %u, pgrp = %u, catatonic = %d, oz_mode = %d",
- current->pid, process_group(current), sbi->catatonic, oz_mode);
+ current->pid, task_pgrp_nr(current), sbi->catatonic, oz_mode);

unhashed = autofs4_lookup_unhashed(sbi, dentry->d_parent, &dentry->d_name);
if (!unhashed) {
@@ -973,7 +973,7 @@ static int autofs4_root_ioctl(struct ino
void __user *p = (void __user *)arg;

DPRINTK("cmd = 0x%08x, arg = 0x%08lx, sbi = %p, pgrp = %u",
- cmd,arg,sbi,process_group(current));
+ cmd,arg,sbi,task_pgrp_nr(current));

if (_IOC_TYPE(cmd) != _IOC_TYPE(AUTOFS_IOC_FIRST) ||
    _IOC_NR(cmd) - _IOC_NR(AUTOFS_IOC_FIRST) >= AUTOFS_IOC_COUNT)
diff --git a/fs/binfmt_elf.c b/fs/binfmt_elf.c
index da270d1..0777ee1 100644
--- a/fs/binfmt_elf.c
+++ b/fs/binfmt_elf.c
@@ -1404,8 +1404,8 @@ static void fill_prstatus(struct elf_prs
prstatus->pr_sighold = p->blocked.sig[0];
prstatus->pr_pid = p->pid;
prstatus->pr_ppid = p->parent->pid;
- prstatus->pr_pgrp = process_group(p);
- prstatus->pr_sid = process_session(p);
+ prstatus->pr_pgrp = task_pgrp_nr(p);
+ prstatus->pr_sid = task_session_nr(p);
if (thread_group_leader(p)) {
/*
 * This is the record for the group leader. Add in the
@@ -1450,8 +1450,8 @@ static int fill_psinfo(struct elf_prpsin

psinfo->pr_pid = p->pid;
psinfo->pr_ppid = p->parent->pid;
- psinfo->pr_pgrp = process_group(p);
- psinfo->pr_sid = process_session(p);
+ psinfo->pr_pgrp = task_pgrp_nr(p);
+ psinfo->pr_sid = task_session_nr(p);

i = p->state ? ffz(~p->state) + 1 : 0;
psinfo->pr_state = i;
diff --git a/fs/binfmt_elf_fdpic.c b/fs/binfmt_elf_fdpic.c
index 2f5d8db..46c1d03 100644
--- a/fs/binfmt_elf_fdpic.c
+++ b/fs/binfmt_elf_fdpic.c
@@ -1344,8 +1344,8 @@ static void fill_prstatus(struct elf_prs
prstatus->pr_sighold = p->blocked.sig[0];
prstatus->pr_pid = p->pid;

```

```

prstatus->pr_ppid = p->parent->pid;
- prstatus->pr_pgrp = process_group(p);
- prstatus->pr_sid = process_session(p);
+ prstatus->pr_pgrp = task_pgrp_nr(p);
+ prstatus->pr_sid = task_session_nr(p);
if (thread_group_leader(p)) {
/*
 * This is the record for the group leader. Add in the
@@ -1393,8 +1393,8 @@ static int fill_psinfo(struct elf_prpsin

psinfo->pr_pid = p->pid;
psinfo->pr_ppid = p->parent->pid;
- psinfo->pr_pgrp = process_group(p);
- psinfo->pr_sid = process_session(p);
+ psinfo->pr_pgrp = task_pgrp_nr(p);
+ psinfo->pr_sid = task_session_nr(p);

i = p->state ? ffz(~p->state) + 1 : 0;
psinfo->pr_state = i;
diff --git a/fs/coda/upcall.c b/fs/coda/upcall.c
index 5faacdb..89b3073 100644
--- a/fs/coda/upcall.c
+++ b/fs/coda/upcall.c
@@ -53,7 +53,7 @@ static void *alloc_upcall(int opcode, in

    inp->ih.opcode = opcode;
    inp->ih.pid = current->pid;
- inp->ih.pgid = process_group(current);
+ inp->ih.pgid = task_pgrp_nr(current);
#ifndef CONFIG_CODA_FS_OLD_API
    memset(&inp->ih.cred, 0, sizeof(struct coda_cred));
    inp->ih.cred.cr_fsuid = current->fsuid;
diff --git a/fs/proc/array.c b/fs/proc/array.c
index b4c8965..d9c0766 100644
--- a/fs/proc/array.c
+++ b/fs/proc/array.c
@@ -428,8 +428,8 @@ static int do_task_stat(struct task_struct
    stime += cputime_to_clock_t(sig->stime);
}

- sid = signal_session(sig);
- pgid = process_group(task);
+ sid = task_session_nr(task);
+ pgid = task_pgrp_nr(task);
ppid = rcu_dereference(task->real_parent)->tgid;

unlock_task_sighand(task, &flags);
diff --git a/include/linux/sched.h b/include/linux/sched.h

```

```

index e953c55..69e9b3a 100644
--- a/include/linux/sched.h
+++ b/include/linux/sched.h
@@ -1170,24 +1170,19 @@ struct task_struct {
#endif
};

-static inline pid_t process_group(struct task_struct *tsk)
+static inline pid_t task_pgrp_nr(struct task_struct *tsk)
{
    return tsk->signal->pgrp;
}

-static inline pid_t signal_session(struct signal_struct *sig)
+static inline pid_t task_session_nr(struct task_struct *tsk)
{
    - return sig->__session;
+ return tsk->signal->__session;
}

-static inline pid_t process_session(struct task_struct *tsk)
+static inline void set_task_session(struct task_struct *tsk, pid_t session)
{
    - return signal_session(tsk->signal);
}
-
-static inline void set_signal_session(struct signal_struct *sig, pid_t session)
-{
-    sig->__session = session;
+ tsk->signal->__session = session;
}

static inline struct pid *task_pid(struct task_struct *task)
diff --git a/kernel/exit.c b/kernel/exit.c
index af031a7..4dc4122 100644
--- a/kernel/exit.c
+++ b/kernel/exit.c
@@ -309,12 +309,12 @@ void __set_special_pids(pid_t session, p
{
    struct task_struct *curr = current->group_leader;

- if (process_session(curr) != session) {
+ if (task_session_nr(curr) != session) {
    detach_pid(curr, PIDTYPE_SID);
-    set_signal_session(curr->signal, session);
+    set_task_session(curr, session);
    attach_pid(curr, PIDTYPE_SID, find_pid(session));
}

```

```

- if (process_group(curr) != pgrp) {
+ if (task_pgrp_nr(curr) != pgrp) {
    detach_pid(curr, PIDTYPE_PPID);
    curr->signal->pgrp = pgrp;
    attach_pid(curr, PIDTYPE_PPID, find_pid(pgrp));
@@ -1108,10 +1108,10 @@ static int eligible_child(pid_t pid, int
    if (p->pid != pid)
        return 0;
} else if (!pid) {
- if (process_group(p) != process_group(current))
+ if (task_pgrp_nr(p) != task_pgrp_nr(current))
    return 0;
} else if (pid != -1) {
- if (process_group(p) != -pid)
+ if (task_pgrp_nr(p) != -pid)
    return 0;
}

```

```

diff --git a/kernel/fork.c b/kernel/fork.c
index 43744ba..e7e2d0c 100644
--- a/kernel/fork.c
+++ b/kernel/fork.c
@@ -1262,8 +1262,8 @@ static struct task_struct *copy_process(

```

```

if (thread_group_leader(p)) {
    p->signal->tty = current->signal->tty;
- p->signal->pgrp = process_group(current);
- set_signal_session(p->signal, process_session(current));
+ p->signal->pgrp = task_pgrp_nr(current);
+ set_task_session(p, task_session_nr(current));
    attach_pid(p, PIDTYPE_PPID, task_pgrp(current));
    attach_pid(p, PIDTYPE_SID, task_session(current));

```

```

diff --git a/kernel/signal.c b/kernel/signal.c
index ef8156a..dae013d 100644
--- a/kernel/signal.c
+++ b/kernel/signal.c
@@ -540,7 +540,7 @@ static int check_kill_permission(int sig
    error = -EPERM;
    if ((info == SEND_SIG_NOINFO || (!is_si_special(info) && SI_FROMUSER(info)))
        && ((sig != SIGCONT) ||
- (process_session(current) != process_session(t)))
+ (task_session_nr(current) != task_session_nr(t)))
        && (current->euid ^ t->suid) && (current->euid ^ t->uid)
        && (current->uid ^ t->suid) && (current->uid ^ t->uid)
        && !capable(CAP_KILL))
diff --git a/kernel/sys.c b/kernel/sys.c
index 01d6dac..c5ef39d 100644

```

```

--- a/kernel/sys.c
+++ b/kernel/sys.c
@@ -1487,7 +1487,7 @@ asmlinkage long sys_setpgid(pid_t pid, p
if (err)
    goto out;

- if (process_group(p) != pgid) {
+ if (task_pgrp_nr(p) != pgid) {
    detach_pid(p, PIDTYPE_PPID);
    p->signal->pgrp = pgid;
    attach_pid(p, PIDTYPE_PPID, find_pid(pgid));
@@ -1503,7 +1503,7 @@ out:
asmlinkage long sys_getpgid(pid_t pid)
{
if (!pid)
- return process_group(current);
+ return task_pgrp_nr(current);
else {
    int retval;
    struct task_struct *p;
@@ -1515,7 +1515,7 @@ asmlinkage long sys_getpgid(pid_t pid)
if (p) {
    retval = security_task_getpgid(p);
    if (!retval)
-    retval = process_group(p);
+    retval = task_pgrp_nr(p);
}
read_unlock(&tasklist_lock);
return retval;
@@ -1527,7 +1527,7 @@ asmlinkage long sys_getpgrp(void)
asmlinkage long sys_getpgrp(void)
{
/* SMP - assuming writes are word atomic this is fine */
- return process_group(current);
+ return task_pgrp_nr(current);
}

#endif
@@ -1535,7 +1535,7 @@ asmlinkage long sys_getpgrp(void)
asmlinkage long sys_getsid(pid_t pid)
{
if (!pid)
- return process_session(current);
+ return task_session_nr(current);
else {
    int retval;
    struct task_struct *p;
@@ -1547,7 +1547,7 @@ asmlinkage long sys_getsid(pid_t pid)

```

```
if (p) {
    retval = security_task_getsid(p);
    if (!retval)
-    retval = process_session(p);
+    retval = task_session_nr(p);
}
read_unlock(&tasklist_lock);
return retval;
@@ -1584,7 +1584,7 @@ asmlinkage long sys_setsid(void)
group_leader->signal->tty = NULL;
spin_unlock(&group_leader->sighand->siglock);

- err = process_group(group_leader);
+ err = task_pgrp_nr(group_leader);
out:
write_unlock_irq(&tasklist_lock);
return err;
```

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
