
Subject: [PATCH 2/3] Make get_pid_ns() return the namespace itself

Posted by [Pavel Emelianov](#) on Tue, 10 Jul 2007 14:23:29 GMT

[View Forum Message](#) <> [Reply to Message](#)

Make get_pid_ns() return the namespace itself to look like the other getters and make the code using it look nicer.

Signed-off-by: Pavel Emelianov <xemul@openvz.org>

Acked-by: Cedric Le Goater <clg@fr.ibm.com>

```
diff --git a/include/linux/pid_namespace.h b/include/linux/pid_namespace.h
```

```
index b9a17e0..ddb9a4c 100644
```

```
--- a/include/linux/pid_namespace.h
```

```
+++ b/include/linux/pid_namespace.h
```

```
@@ -24,9 +24,10 @@ struct pid_namespace {
```

```
extern struct pid_namespace init_pid_ns;
```

```
-static inline void get_pid_ns(struct pid_namespace *ns)
```

```
+static inline struct pid_namespace *get_pid_ns(struct pid_namespace *ns)
```

```
{  
    kref_get(&ns->kref);
```

```
+ return ns;
```

```
}
```

```
extern struct pid_namespace *copy_pid_ns(unsigned long flags, struct pid_namespace *ns);
```

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
