
Subject: [PATCH 23/25] sysfs: Implement sysfs tagged directory support.
Posted by [ebiederm](#) on Tue, 07 Aug 2007 21:35:31 GMT

[View Forum Message](#) <> [Reply to Message](#)

The problem. When implementing a network namespace I need to be able to have multiple network devices with the same name. Currently this is a problem for `/sys/class/net/*`, `/sys/devices/virtual/net/*`, and potentially a few other directories of the form `/sys/ ... /net/*`.

What this patch does is to add an additional tag field to the sysfs dirent structure. For directories that should show different contents depending on the context such as `/sys/class/net/`, and `/sys/devices/virtual/net/` this tag field is used to specify the context in which those directories should be visible. Effectively this is the same as creating multiple distinct directories with the same name the internally to sysfs the result is nicer.

I am calling the concept of a single directory that looks like multiple directories all at the same path in the filesystem tagged directories.

For the networking namespace the set of directories whose contents I need to filter with tags can depend on the presence or absence of hutplug hardware or which modules are currently loaded. Which means I need a simple race free way to setup those directories as taged.

To achieve a race free design all tagged directories are created and managed by sysfs itself. The upper level code that knows what tagged directories we need provides just two methods that enable this:

- `sb_tag()` - that returns a "void *" tag that identifies the context of the process that mounted sysfs.

- `kobject_tag(kobj)` - that returns a "void *" tag that identifies the context a kobject should be in.

Everything else is left up to sysfs.

For the network namespace `sb_tag` and `kobject_tag` are essentially one line functions, and look to remain that.

The work needed in sysfs is more extensive. At each directory or symlink creating I need to check if the directory it is being created in is a tagged directory and if so generate the appropriate tag to place on the `sysfs_dirent`. Likewise at each symlink or directory removal I need to check if the sysfs directory it is being removed from is a tagged directory and if so figure out which tag goes along with the name I am deleting.

Currently only directories which hold kobjects, and symlinks are supported. There is not enough information

in the current file attribute interfaces to give us anything to discriminate on which makes it useless, and there are no potential users which makes it an uninteresting problem to solve.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

```
---
fs/sysfs/bin.c      |  2 +-
fs/sysfs/dir.c     | 180 ++++++-----
fs/sysfs/file.c    |  8 +-
fs/sysfs/group.c   | 12 +++-
fs/sysfs/inode.c   |  6 +-
fs/sysfs/mount.c   | 44 ++++++---
fs/sysfs/symlink.c |  2 +-
fs/sysfs/sysfs.h   | 15 ++++-
include/linux/sysfs.h | 17 +++++
9 files changed, 253 insertions(+), 33 deletions(-)
```

```
diff --git a/fs/sysfs/bin.c b/fs/sysfs/bin.c
index 135353f..1ef0a07 100644
```

```
--- a/fs/sysfs/bin.c
+++ b/fs/sysfs/bin.c
@@ -248,7 +248,7 @@ int sysfs_create_bin_file(struct kobject * kobj, struct bin_attribute * attr)

void sysfs_remove_bin_file(struct kobject * kobj, struct bin_attribute * attr)
{
- if (sysfs_hash_and_remove(kobj->sd, attr->attr.name) < 0) {
+ if (sysfs_hash_and_remove(kobj, kobj->sd, attr->attr.name) < 0) {
    printk(KERN_ERR "%s: "
           "bad dentry or inode or no such file: \"%s\"\n",
           __FUNCTION__, attr->attr.name);
```

```
diff --git a/fs/sysfs/dir.c b/fs/sysfs/dir.c
index 34eabf4..bc30a8a 100644
```

```
--- a/fs/sysfs/dir.c
+++ b/fs/sysfs/dir.c
@@ -387,10 +387,16 @@ void sysfs_addrm_start(struct sysfs_addrm_cxt *acxt,
 */
int sysfs_add_one(struct sysfs_addrm_cxt *acxt, struct sysfs_dirent *sd)
{
- if (sysfs_find_dirent(acxt->parent_sd, sd->s_name))
+ const void *tag = NULL;
+
+ tag = sysfs_creation_tag(acxt->parent_sd, sd);
+
+ if (sysfs_find_dirent(acxt->parent_sd, tag, sd->s_name))
    return -EEXIST;

    sd->s_parent = sysfs_get(acxt->parent_sd);
```

```

+ if (sd->s_parent->s_flags & SYSFS_FLAG_TAGGED)
+ sd->s_tag.tag = tag;

    if (sysfs_type(sd) == SYSFS_DIR && acxt->parent_inode)
        inc_nlink(acxt->parent_inode);
@@ -540,13 +546,18 @@ void sysfs_addrm_finish(struct sysfs_addrm_cxt *acxt)
 * Pointer to sysfs_dirent if found, NULL if not.
 */
struct sysfs_dirent *sysfs_find_dirent(struct sysfs_dirent *parent_sd,
+     const void *tag,
+     const unsigned char *name)
{
    struct sysfs_dirent *sd;

- for (sd = parent_sd->s_children; sd; sd = sd->s_sibling)
+ for (sd = parent_sd->s_children; sd; sd = sd->s_sibling) {
+ if ((parent_sd->s_flags & SYSFS_FLAG_TAGGED) &&
+     (sd->s_tag.tag != tag))
+     continue;
    if (!strcmp(sd->s_name, name))
        return sd;
+ }
    return NULL;
}

@@ -570,7 +581,7 @@ struct sysfs_dirent *sysfs_get_dirent(struct sysfs_dirent *parent_sd,
    struct sysfs_dirent *sd;

    mutex_lock(&sysfs_mutex);
- sd = sysfs_find_dirent(parent_sd, name);
+ sd = sysfs_find_dirent(parent_sd, NULL, name);
    sysfs_get(sd);
    mutex_unlock(&sysfs_mutex);

@@ -636,13 +647,16 @@ static struct dentry * sysfs_lookup(struct inode *dir, struct dentry
*dentry,
    struct nameidata *nd)
{
    struct dentry *ret = NULL;
- struct sysfs_dirent *parent_sd = dentry->d_parent->d_fsdata;
+ struct dentry *parent = dentry->d_parent;
+ struct sysfs_dirent *parent_sd = parent->d_fsdata;
    struct sysfs_dirent *sd;
    struct inode *inode;
+ const void *tag;

    mutex_lock(&sysfs_mutex);

```

```

- sd = sysfs_find_dirent(parent_sd, dentry->d_name.name);
+ tag = sysfs_lookup_tag(parent_sd, parent->d_sb);
+ sd = sysfs_find_dirent(parent_sd, tag, dentry->d_name.name);

/* no such entry */
if (!sd)
@@ -825,6 +839,14 @@ struct dentry *sysfs_get_dentry(struct super_block *sb, struct
sysfs_dirent *sd)
    struct sysfs_dirent *cur;
    struct dentry *parent_dentry, *dentry;

+ /* Bail if this sd won't show up in this superblock */
+ if (sd->s_parent && sd->s_parent->s_flags & SYSFS_FLAG_TAGGED) {
+     const void *tag;
+     tag = sysfs_lookup_tag(sd->s_parent, sb);
+     if (sd->s_tag.tag != tag)
+         return NULL;
+ }
+
/* Find the first parent which has valid dentry.
*/
dentry = NULL;
@@ -926,7 +948,6 @@ err_out:
    return error;
}

-
int sysfs_rename_dir(struct kobject * kobj, const char *new_name)
{
    struct sysfs_dirent *sd = kobj->sd;
@@ -934,19 +955,24 @@ int sysfs_rename_dir(struct kobject * kobj, const char *new_name)
    struct sysfs_rename_struct *srs;
    struct inode *parent_inode = NULL;
    const char *dup_name = NULL;
+ const void *old_tag, *tag;
    int error;

    INIT_LIST_HEAD(&todo);
    mutex_lock(&sysfs_rename_mutex);
+ old_tag = sysfs_dirent_tag(sd);
+ tag = sysfs_creation_tag(sd->s_parent, sd);

    error = 0;
- if (strcmp(sd->s_name, new_name) == 0)
+ if ((old_tag == tag) && (strcmp(sd->s_name, new_name) == 0))
    goto out; /* nothing to rename */

    sysfs_grab_supers());

```

```

- error = prep_rename(&todo, sd, sd->s_parent, new_name);
- if (error)
- goto out_release;
+ if (old_tag == tag) {
+ error = prep_rename(&todo, sd, sd->s_parent, new_name);
+ if (error)
+ goto out_release;
+ }

error = -ENOMEM;
mutex_lock(&sysfs_mutex);
@@ -959,7 +985,7 @@ int sysfs_rename_dir(struct kobject * kobj, const char *new_name)
mutex_lock(&sysfs_mutex);

error = -EEXIST;
- if (sysfs_find_dirent(sd->s_parent, new_name))
+ if (sysfs_find_dirent(sd->s_parent, tag, new_name))
goto out_unlock;

/* rename kobject and sysfs_dirent */
@@ -974,6 +1000,8 @@ int sysfs_rename_dir(struct kobject * kobj, const char *new_name)

dup_name = sd->s_name;
sd->s_name = new_name;
+ if (sd->s_parent->s_flags & SYSFS_FLAG_TAGGED)
+ sd->s_tag.tag = tag;

/* rename */
list_for_each_entry(srs, &todo, list) {
@@ -981,6 +1009,20 @@ int sysfs_rename_dir(struct kobject * kobj, const char *new_name)
d_move(srs->old_dentry, srs->new_dentry);
}

+ /* If we are moving across superblocks drop the dcache entries */
+ if (old_tag != tag) {
+ struct super_block *sb;
+ struct dentry *dentry;
+ list_for_each_entry(sb, &sysfs_fs_type.fs_supers, s_instances) {
+ dentry = __sysfs_get_dentry(sb, sd);
+ if (!dentry)
+ continue;
+ shrink_dcache_parent(dentry);
+ d_drop(dentry);
+ dput(dentry);
+ }
+ }
+
error = 0;

```

```

out_unlock:
    mutex_unlock(&sysfs_mutex);
@@ -1003,11 +1045,13 @@ int sysfs_move_dir(struct kobject *kobj, struct kobject
*new_parent_kobj)
    struct sysfs_rename_struct *srs;
    struct inode *old_parent_inode = NULL, *new_parent_inode = NULL;
    int error;
+ const void *tag;

    INIT_LIST_HEAD(&todo);
    mutex_lock(&sysfs_rename_mutex);
    BUG_ON(!sd->s_parent);
    new_parent_sd = new_parent_kobj->sd ? new_parent_kobj->sd : &sysfs_root;
+ tag = sysfs_dirent_tag(sd);

    error = 0;
    if (sd->s_parent == new_parent_sd)
@@ -1041,7 +1085,7 @@ again:
    mutex_lock(&sysfs_mutex);

    error = -EEXIST;
- if (sysfs_find_dirent(new_parent_sd, sd->s_name))
+ if (sysfs_find_dirent(new_parent_sd, tag, sd->s_name))
    goto out_unlock;

    error = 0;
@@ -1080,10 +1124,11 @@ static inline unsigned char dt_type(struct sysfs_dirent *sd)

static int sysfs_readdir(struct file * filp, void * dirent, filldir_t filldir)
{
- struct dentry *dentry = filp->f_path.dentry;
- struct sysfs_dirent * parent_sd = dentry->d_fsdata;
+ struct dentry *parent = filp->f_path.dentry;
+ struct sysfs_dirent * parent_sd = parent->d_fsdata;
    struct sysfs_dirent *pos;
    ino_t ino;
+ const void *tag;

    if (filp->f_pos == 0) {
        ino = parent_sd->s_ino;
@@ -1101,6 +1146,8 @@ static int sysfs_readdir(struct file * filp, void * dirent, filldir_t filldir)
    if ((filp->f_pos > 1) && (filp->f_pos < UINT_MAX)) {
        mutex_lock(&sysfs_mutex);

+ tag = sysfs_lookup_tag(parent_sd, parent->d_sb);
+
    /* Skip the dentries we have already reported */
    pos = parent_sd->s_children;

```

```

while (pos && (filp->f_pos > pos->s_ino))
@@ -1110,6 +1157,10 @@ static int sysfs_readdir(struct file * filp, void * dirent, filldir_t filldir)
    const char * name;
    int len;

+ if ((parent_sd->s_flags & SYSFS_FLAG_TAGGED) &&
+     (pos->s_tag.tag != tag))
+ continue;
+
    name = pos->s_name;
    len = strlen(name);
    filp->f_pos = ino = pos->s_ino;
@@ -1130,3 +1181,104 @@ const struct file_operations sysfs_dir_operations = {
    .read = generic_read_dir,
    .readdir = sysfs_readdir,
};
+
+const void *sysfs_creation_tag(struct sysfs_dirent *parent_sd, struct sysfs_dirent *sd)
+{
+ const void *tag = NULL;
+
+ if (parent_sd->s_flags & SYSFS_FLAG_TAGGED) {
+ struct kobject *kobj;
+ switch (sysfs_type(sd)) {
+ case SYSFS_DIR:
+ kobj = sd->s_elem.dir.kobj;
+ break;
+ case SYSFS_KOBJ_LINK:
+ kobj = sd->s_elem.symlink.target_sd->s_elem.dir.kobj;
+ break;
+ default:
+ BUG();
+ }
+ tag = parent_sd->s_tag.ops->kobject_tag(kobj);
+ }
+ return tag;
+}
+
+const void *sysfs_removal_tag(struct kobject *kobj, struct sysfs_dirent *dir_sd)
+{
+ const void *tag = NULL;
+
+ if (dir_sd->s_flags & SYSFS_FLAG_TAGGED)
+ tag = kobj->sd->s_tag.tag;
+
+ return tag;
+}
+

```

```

+const void *sysfs_lookup_tag(struct sysfs_dirent *dir_sd, struct super_block *sb)
+{
+ const void *tag = NULL;
+
+ if (dir_sd->s_flags & SYSFS_FLAG_TAGGED)
+ tag = dir_sd->s_tag.ops->sb_tag(&sysfs_info(sb)->tag);
+
+ return tag;
+}
+
+const void *sysfs_dirent_tag(struct sysfs_dirent *sd)
+{
+ const void *tag = NULL;
+
+ if (sd->s_parent && (sd->s_parent->s_flags & SYSFS_FLAG_TAGGED))
+ tag = sd->s_tag.tag;
+
+ return tag;
+}
+
+/**
+ * sysfs_enable_tagging - Automatically tag all of the children in a directory.
+ * @kobj: object whose children should be filtered by tags
+ *
+ * Once tagging has been enabled on a directory the contents
+ * of the directory become dependent upon context captured when
+ * sysfs was mounted.
+ *
+ * tag_ops->sb_tag() returns the context for a given superblock.
+ *
+ * tag_ops->kobject_tag() returns the context that a given kobj
+ * resides in.
+ *
+ * Using those methods the sysfs code on tagged directories
+ * carefully stores the files so that when we lookup files
+ * we get the proper answer for our context.
+ *
+ * If the context of a kobject is changed it is expected that
+ * the kobject will be renamed so the appropriate sysfs data structures
+ * can be updated.
+ */
+int sysfs_enable_tagging(struct kobject *kobj,
+ const struct sysfs_tagged_dir_operations *tag_ops)
+{
+ struct sysfs_dirent *sd;
+ int err;
+
+ err = -ENOENT;

```

```

+ sd = kobj->sd;
+
+ mutex_lock(&sysfs_mutex);
+ err = -EINVAL;
+ /* We can only enable tagging on empty directories
+ * where tagging is not already enabled, and
+ * who are not subdirectories of directories where tagging is
+ * enabled.
+ */
+ if (!sd->s_children && (sysfs_type(sd) == SYSFS_DIR) &&
+     !(sd->s_flags & SYSFS_FLAG_REMOVED) &&
+     !(sd->s_flags & SYSFS_FLAG_TAGGED) &&
+     sd->s_parent &&
+     !(sd->s_parent->s_flags & SYSFS_FLAG_TAGGED)) {
+ err = 0;
+ sd->s_flags |= SYSFS_FLAG_TAGGED;
+ sd->s_tag.ops = tag_ops;
+ }
+ mutex_unlock(&sysfs_mutex);
+ return err;
+}
diff --git a/fs/sysfs/file.c b/fs/sysfs/file.c
index 1e6f9df..11a385c 100644
--- a/fs/sysfs/file.c
+++ b/fs/sysfs/file.c
@@ -369,9 +369,9 @@ void sysfs_notify(struct kobject *k, char *dir, char *attr)
     mutex_lock(&sysfs_mutex);

     if (sd && dir)
- sd = sysfs_find_dirent(sd, dir);
+ sd = sysfs_find_dirent(sd, NULL, dir);
     if (sd && attr)
- sd = sysfs_find_dirent(sd, attr);
+ sd = sysfs_find_dirent(sd, NULL, attr);
     if (sd) {
         atomic_inc(&sd->s_event);
         wake_up_interruptible(&k->poll);
@@ -560,7 +560,7 @@ EXPORT_SYMBOL_GPL(sysfs_chmod_file);

void sysfs_remove_file(struct kobject * kobj, const struct attribute * attr)
{
- sysfs_hash_and_remove(kobj->sd, attr->name);
+ sysfs_hash_and_remove(kobj, kobj->sd, attr->name);
}

@@ -577,7 +577,7 @@ void sysfs_remove_file_from_group(struct kobject *kobj,

```

```

dir_sd = sysfs_get_dirent(kobj->sd, group);
if (dir_sd) {
- sysfs_hash_and_remove(dir_sd, attr->name);
+ sysfs_hash_and_remove(kobj, dir_sd, attr->name);
  sysfs_put(dir_sd);
}
}
diff --git a/fs/sysfs/group.c b/fs/sysfs/group.c
index 4606f7c..9e928fd 100644
--- a/fs/sysfs/group.c
+++ b/fs/sysfs/group.c
@@ -17,16 +17,16 @@
#include "sysfs.h"

-static void remove_files(struct sysfs_dirent *dir_sd,
+static void remove_files(struct kobject *kobj, struct sysfs_dirent *dir_sd,
  const struct attribute_group *grp)
{
  struct attribute *const* attr;

  for (attr = grp->attrs; *attr; attr++)
- sysfs_hash_and_remove(dir_sd, (*attr)->name);
+ sysfs_hash_and_remove(kobj, dir_sd, (*attr)->name);
}

-static int create_files(struct sysfs_dirent *dir_sd,
+static int create_files(struct kobject *kobj, struct sysfs_dirent *dir_sd,
  const struct attribute_group *grp)
{
  struct attribute *const* attr;
@@ -35,7 +35,7 @@
  static int create_files(struct sysfs_dirent *dir_sd,
  for (attr = grp->attrs; *attr && !error; attr++)
    error = sysfs_add_file(dir_sd, *attr, SYSFS_KOBJ_ATTR);
  if (error)
- remove_files(dir_sd, grp);
+ remove_files(kobj, dir_sd, grp);
  return error;
}

@@ -55,7 +55,7 @@
  int sysfs_create_group(struct kobject * kobj,
  } else
    sd = kobj->sd;
  sysfs_get(sd);
- error = create_files(sd, grp);
+ error = create_files(kobj, sd, grp);
  if (error) {
    if (grp->name)

```

```

    sysfs_remove_subdir(sd);
@@ -76,7 +76,7 @@ void sysfs_remove_group(struct kobject * kobj,
} else
sd = sysfs_get(dir_sd);

- remove_files(sd, grp);
+ remove_files(kobj, sd, grp);
  if (grp->name)
    sysfs_remove_subdir(sd);

diff --git a/fs/sysfs/inode.c b/fs/sysfs/inode.c
index 70a2420..d870efd 100644
--- a/fs/sysfs/inode.c
+++ b/fs/sysfs/inode.c
@@ -212,17 +212,19 @@ struct inode * sysfs_get_inode(struct sysfs_dirent *sd)
  return inode;
}

-int sysfs_hash_and_remove(struct sysfs_dirent *dir_sd, const char *name)
+int sysfs_hash_and_remove(struct kobject *kobj, struct sysfs_dirent *dir_sd, const char *name)
{
  struct sysfs_addrm_cxt acxt;
  struct sysfs_dirent *sd;
+ const void *tag;

  if (!dir_sd)
    return -ENOENT;

  sysfs_addrm_start(&acxt, dir_sd);
+ tag = sysfs_removal_tag(kobj, dir_sd);

- sd = sysfs_find_dirent(dir_sd, name);
+ sd = sysfs_find_dirent(dir_sd, tag, name);
  if (sd)
    sysfs_remove_one(&acxt, sd);

diff --git a/fs/sysfs/mount.c b/fs/sysfs/mount.c
index b2bfa45..7668e66 100644
--- a/fs/sysfs/mount.c
+++ b/fs/sysfs/mount.c
@@ -67,6 +67,7 @@ static int sysfs_fill_super(struct super_block *sb, void *data, int silent)
  goto out_err;
}
root->d_fsdata = &sysfs_root;
+ root->d_sb = sb;
sb->s_root = root;
sb->s_fs_info = info;
return 0;

```

```

@@ -80,20 +81,55 @@ out_err:
    return error;
}

+static int sysfs_test_super(struct super_block *sb, void *ptr)
+{
+ struct task_struct *task = ptr;
+ struct sysfs_super_info *info = sysfs_info(sb);
+ int found = 1;
+
+ return found;
+}
+
static int sysfs_get_sb(struct file_system_type *fs_type,
    int flags, const char *dev_name, void *data, struct vfsmount *mnt)
{
- int rc;
+ struct super_block *sb;
+ int error;
    mutex_lock(&sysfs_rename_mutex);
- rc = get_sb_single(fs_type, flags, data, sysfs_fill_super, mnt);
+ sb = sget(fs_type, sysfs_test_super, set_anon_super, current);
+ if (IS_ERR(sb)) {
+ error = PTR_ERR(sb);
+ goto out;
+ }
+ if (!sb->s_root) {
+ sb->s_flags = flags;
+ error = sysfs_fill_super(sb, data, flags & MS_SILENT ? 1 : 0);
+ if (error) {
+ up_write(&sb->s_umount);
+ deactivate_super(sb);
+ goto out;
+ }
+ sb->s_flags |= MS_ACTIVE;
+ }
+ do_remount_sb(sb, flags, data, 0);
+ error = simple_set_mnt(mnt, sb);
+out:
    mutex_unlock(&sysfs_rename_mutex);
- return rc;
+ return error;
+}
+
+static void sysfs_kill_sb(struct super_block *sb)
+{
+ struct sysfs_super_info *info = sysfs_info(sb);
+

```

```
+ kill_anon_super(sb);
+ kfree(info);
}
```

```
struct file_system_type sysfs_fs_type = {
    .name = "sysfs",
    .get_sb = sysfs_get_sb,
- .kill_sb = kill_anon_super,
+ .kill_sb = sysfs_kill_sb,
};
```

```
void sysfs_grab_supers(void)
diff --git a/fs/sysfs/symlink.c b/fs/sysfs/symlink.c
index 46f8fd4..99aaf6f 100644
```

```
--- a/fs/sysfs/symlink.c
```

```
+++ b/fs/sysfs/symlink.c
```

```
@@ -113,7 +113,7 @@ int sysfs_create_link(struct kobject * kobj, struct kobject * target, const
char
```

```
void sysfs_remove_link(struct kobject * kobj, const char * name)
{
- sysfs_hash_and_remove(kobj->sd, name);
+ sysfs_hash_and_remove(kobj, kobj->sd, name);
}
```

```
static int sysfs_get_target_path(struct sysfs_dirent * parent_sd,
diff --git a/fs/sysfs/sysfs.h b/fs/sysfs/sysfs.h
index 6de7e2b..832d675 100644
```

```
--- a/fs/sysfs/sysfs.h
```

```
+++ b/fs/sysfs/sysfs.h
```

```
@@ -28,6 +28,10 @@ struct sysfs_dirent {
    const char * s_name;
```

```
    union {
+ const struct sysfs_tagged_dir_operations *ops;
+ const void *tag;
+ } s_tag;
+ union {
    struct sysfs_elem_dir dir;
    struct sysfs_elem_symlink symlink;
    struct sysfs_elem_attr attr;
@@ -52,6 +56,7 @@ struct sysfs_addrm_cxt {
```

```
struct sysfs_super_info {
    int grabbed;
+ struct sysfs_tag_info tag;
};
```

```

#define sysfs_info(SB) ((struct sysfs_super_info *) (SB)->s_fs_info)
@@ -63,6 +68,13 @@ extern struct file_system_type sysfs_fs_type;
void sysfs_grab_supers(void);
void sysfs_release_supers(void);

+extern const void *sysfs_creation_tag(struct sysfs_dirent *parent_sd,
+ struct sysfs_dirent *sd);
+extern const void *sysfs_removal_tag(struct kobject *kobj,
+ struct sysfs_dirent *dir_sd);
+extern const void *sysfs_lookup_tag(struct sysfs_dirent *dir_sd,
+ struct super_block *sb);
+extern const void *sysfs_dirent_tag(struct sysfs_dirent *sd);
extern struct dentry *sysfs_get_dentry(struct super_block *sb, struct sysfs_dirent *sd);
extern struct sysfs_dirent *sysfs_get_active(struct sysfs_dirent *sd);
extern void sysfs_put_active(struct sysfs_dirent *sd);
@@ -80,6 +92,7 @@ extern struct inode * sysfs_get_inode(struct sysfs_dirent *sd);

extern void release_sysfs_dirent(struct sysfs_dirent * sd);
extern struct sysfs_dirent *sysfs_find_dirent(struct sysfs_dirent *parent_sd,
+ const void *tag,
+ const unsigned char *name);
extern struct sysfs_dirent *sysfs_get_dirent(struct sysfs_dirent *parent_sd,
+ const unsigned char *name);
@@ -88,7 +101,7 @@ extern struct sysfs_dirent *sysfs_new_dirent(const char *name, umode_t
mode,

extern int sysfs_add_file(struct sysfs_dirent *dir_sd,
+ const struct attribute *attr, int type);
-extern int sysfs_hash_and_remove(struct sysfs_dirent *dir_sd, const char *name);
+extern int sysfs_hash_and_remove(struct kobject *kobj, struct sysfs_dirent *dir_sd, const char
*name);
extern struct sysfs_dirent *sysfs_find(struct sysfs_dirent *dir, const char * name);

extern int sysfs_create_subdir(struct kobject *kobj, const char *name,
diff --git a/include/linux/sysfs.h b/include/linux/sysfs.h
index c16e4c5..28c497e 100644
--- a/include/linux/sysfs.h
+++ b/include/linux/sysfs.h
@@ -74,6 +74,14 @@ struct sysfs_ops {
+ ssize_t (*store)(struct kobject *, struct attribute *, const char *, size_t);
};

+struct sysfs_tag_info {
+};
+
+struct sysfs_tagged_dir_operations {
+ const void *(*sb_tag)(struct sysfs_tag_info *info);
+ const void *(*kobject_tag)(struct kobject *kobj);

```

```

+};
+
#define SYSFS_TYPE_MASK 0x00ff
#define SYSFS_ROOT 0x0001
#define SYSFS_DIR 0x0002
@@ -84,6 +92,7 @@ struct sysfs_ops {

#define SYSFS_FLAG_MASK ~SYSFS_TYPE_MASK
#define SYSFS_FLAG_REMOVED 0x0100
+#define SYSFS_FLAG_TAGGED 0x0200

#ifdef CONFIG_SYSFS

@@ -134,6 +143,8 @@ void sysfs_remove_file_from_group(struct kobject *kobj,

void sysfs_notify(struct kobject * k, char *dir, char *attr);

+int sysfs_enable_tagging(struct kobject *, const struct sysfs_tagged_dir_operations *);
+
extern int __must_check sysfs_init(void);

#else /* CONFIG_SYSFS */
@@ -229,6 +240,12 @@ static inline void sysfs_notify(struct kobject * k, char *dir, char *attr)
{
}

+static inline int sysfs_enable_tagging(struct kobject *kobj,
+ const struct sysfs_tagged_dir_operations *tag_ops)
+{
+ return 0;
+}
+
static inline int __must_check sysfs_init(void)
{
return 0;
}
--
1.5.1.1.181.g2de0

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
