
Subject: [PATCH] Allow signalling container-init
Posted by [Sukadev Bhattiprolu](#) on Wed, 08 Aug 2007 23:47:37 GMT
[View Forum Message](#) <> [Reply to Message](#)

Pavel,

Should we include this in the patchset ?

Sukadev

From: Sukadev Bhattiprolu <sukadev@us.ibm.com>
Subject: [PATCH] Allow signalling container-init

Only the global-init process must be special - any other container-init process must be killable to prevent run-away processes in the system.

TODO: Ideally we should allow killing the container-init only from ancestor containers and prevent it being killed from that or descendant containers. But that is a more complex change and will be addressed by a follow-on patch. For now allow the container-init to be terminated by any process with sufficient privileges.

Signed-off-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

kernel/signal.c | 6 +-----
1 file changed, 2 insertions(+), 4 deletions(-)

Index: lx26-23-rc1-mm1/kernel/signal.c

=====

--- lx26-23-rc1-mm1.orig/kernel/signal.c 2007-08-07 13:52:12.000000000 -0700

+++ lx26-23-rc1-mm1/kernel/signal.c 2007-08-08 15:09:27.000000000 -0700

@ @ -1861,11 +1861,9 @ @ relock:

continue;

/*

- * Init of a pid space gets no signals it doesn't want from
- * within that pid space. It can of course get signals from
- * its parent pid space.

+ * Global init gets no signals it doesn't want.

*/

- if (current == task_child_reaper(current))

+ if (is_global_init(current->group_leader))

continue;

if (sig_kernel_stop(signr)) {

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
