
Subject: [RFC][PATCH] Make access to tasks's nsproxy later
Posted by [Pavel Emelianov](#) on Wed, 08 Aug 2007 15:37:05 GMT
[View Forum Message](#) <> [Reply to Message](#)

When someone wants to deal with some other tasks's namespaces it has to lock the task and then to get the desired namespace if the one exists. This is slow on read-only paths and may be impossible in some cases.

E.g. Oleg recently noticed a race between unshare() and the (just sent for review) pid namespaces - when the task notifies the parent it has to know the parent's namespace, but taking the task_lock() is impossible there - the code is under write locked tasklist lock.

On the other hand switching the namespace on task (daemonize) and releasing the namespace (after the last task exit) is rather rare operation and we can sacrifice its speed to solve the issues above.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
fs/proc/base.c      | 27 ++++++-----  
include/linux/nsproxy.h | 19 +++++-----  
kernel/exit.c       |  4 +---  
kernel/fork.c       | 11 +++++-----  
kernel/nsproxy.c    | 38 ++++++-----  
5 files changed, 60 insertions(+), 39 deletions(-)
```

```
diff --git a/fs/proc/base.c b/fs/proc/base.c  
index ed2b224..614851a 100644  
--- a/fs/proc/base.c  
+++ b/fs/proc/base.c  
@@ -371,18 +371,21 @@ struct proc_mounts {  
 static int mounts_open(struct inode *inode, struct file *file)  
{  
     struct task_struct *task = get_proc_task(inode);  
+    struct nsproxy *nsp;  
     struct mnt_namespace *ns = NULL;  
     struct proc_mounts *p;  
     int ret = -EINVAL;  
  
     if (task) {  
-        task_lock(task);  
-        if (task->nsproxy) {  
-            ns = task->nsproxy->mnt_ns;
```

```

+ rcu_read_lock();
+ nsp = task_nsproxy(task);
+ if (nsp) {
+ ns = nsp->mnt_ns;
  if (ns)
    get_mnt_ns(ns);
}
- task_unlock(task);
+ rcu_read_unlock();
+
  put_task_struct(task);
}

```

@@ -445,16 +448,20 @@ static int mountstats_open(struct inode

```

if (!ret) {
  struct seq_file *m = file->private_data;
+ struct nsproxy *nsp;
  struct mnt_namespace *mnt_ns = NULL;
  struct task_struct *task = get_proc_task(inode);

  if (task) {
- task_lock(task);
- if (task->nsproxy)
-   mnt_ns = task->nsproxy->mnt_ns;
- if (mnt_ns)
-   get_mnt_ns(mnt_ns);
- task_unlock(task);
+ rcu_read_lock();
+ nsp = task_nsproxy(task);
+ if (nsp) {
+   mnt_ns = nsp->mnt_ns;
+   if (mnt_ns)
+     get_mnt_ns(mnt_ns);
+ }
+ rcu_read_unlock();
+
  put_task_struct(task);
}

```

diff --git a/include/linux/nsproxy.h b/include/linux/nsproxy.h

index 525d8fc..74f21fe 100644

```

--- a/include/linux/nsproxy.h
+++ b/include/linux/nsproxy.h
@@ -32,8 +32,14 @@ struct nsproxy {
};
extern struct nsproxy init_nsproxy;
```

```

+static inline struct nsproxy *task_nsproxy(struct task_struct *tsk)
+{
+    return rcu_dereference(tsk->nsproxy);
+}
+
int copy_namespaces(unsigned long flags, struct task_struct *tsk);
void get_task_namespaces(struct task_struct *tsk);
void exit_task_namespaces(struct task_struct *tsk);
void switch_task_namespaces(struct task_struct *tsk, struct nsproxy *new);
void free_nsproxy(struct nsproxy *ns);
int unshare_nsproxy_namespaces(unsigned long, struct nsproxy **,
    struct fs_struct *);
@@ -45,17 +51,6 @@ static inline void put_nsproxy(struct ns
}
}

-static inline void exit_task_namespaces(struct task_struct *p)
-{
-    struct nsproxy *ns = p->nsproxy;
-    if (ns) {
-        task_lock(p);
-        p->nsproxy = NULL;
-        task_unlock(p);
-        put_nsproxy(ns);
-    }
-}
-
#endif CONFIG_CONTAINER_NS
int ns_container_clone(struct task_struct *tsk);
#else
diff --git a/kernel/exit.c b/kernel/exit.c
index 2f4f35e..a2aef1f 100644
--- a/kernel/exit.c
+++ b/kernel/exit.c
@@ -409,9 +409,7 @@ void daemonize(const char *name, ...)
    current->fs = fs;
    atomic_inc(&fs->count);

-    exit_task_namespaces(current);
-    current->nsproxy = init_task.nsproxy;
-    get_task_namespaces(current);
+    switch_task_namespaces(current, init_task.nsproxy);

    exit_files(current);
    current->files = init_task.files;
diff --git a/kernel/fork.c b/kernel/fork.c
index bc48e0f..0c6dd67 100644
--- a/kernel/fork.c

```

```

+++ b/kernel/fork.c
@@ -1618,7 +1618,7 @@ asmlinkage long sys_unshare(unsigned lon
    struct mm_struct *mm, *new_mm = NULL, *active_mm = NULL;
    struct files_struct *fd, *new_fd = NULL;
    struct sem_undo_list *new_ulist = NULL;
-   struct nsproxy *new_nsproxy = NULL, *old_nsproxy = NULL;
+   struct nsproxy *new_nsproxy = NULL;

    check_unshare_flags(&unshare_flags);

@@ -1647,14 +1647,13 @@ asmlinkage long sys_unshare(unsigned lon
    if (new_fs || new_mm || new_fd || new_ulist || new_nsproxy) {

-   task_lock(current);
-
-   if (new_nsproxy) {
-       old_nsproxy = current->nsproxy;
-       current->nsproxy = new_nsproxy;
-       new_nsproxy = old_nsproxy;
+   switch_task_namespaces(current, new_nsproxy);
+   new_nsproxy = NULL;
    }

+   task_lock(current);
+
+   if (new_fs) {
+       fs = current->fs;
+       current->fs = new_fs;
diff --git a/kernel/nsproxy.c b/kernel/nsproxy.c
index 58843ae..91dca27 100644
--- a/kernel/nsproxy.c
+++ b/kernel/nsproxy.c
@@ -30,14 +30,6 @@ static inline void get_nsproxy(struct ns
    atomic_inc(&ns->count);
}

-void get_task_namespaces(struct task_struct *tsk)
-{
-   struct nsproxy *ns = tsk->nsproxy;
-   if (ns) {
-       get_nsproxy(ns);
-   }
-}
-
/*
 * creates a copy of "orig" with refcount 1.
 */

```

```

@@ -205,6 +197,36 @@ out:
    return err;
}

+void switch_task_namespaces(struct task_struct *p, struct nsproxy *new)
+{
+ struct nsproxy *ns;
+
+ might_sleep();
+
+ ns = p->nsproxy;
+ if (ns == new)
+ return;
+
+ if (new)
+ get_nsproxy(new);
+ rcu_assign_pointer(p->nsproxy, new);
+
+ if (ns && atomic_dec_and_test(&ns->count)) {
+ /*
+ * wait for others to get what they want from this
+ * nsproxy. cannot release this nsproxy via the
+ * call_rcu() since put_mnt_ns will want to sleep
+ */
+ synchronize_rcu();
+ free_nsproxy(ns);
+ }
+}
+
+void exit_task_namespaces(struct task_struct *p)
+{
+ switch_task_namespaces(p, NULL);
+}
+
static int __init nsproxy_cache_init(void)
{
    nsproxy_cachep = kmem_cache_create("nsproxy", sizeof(struct nsproxy),

```

Containers mailing list
 Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>