
Subject: [PATCH] Containers: Avoid lockdep warning
Posted by [menage](#) on Wed, 22 Aug 2007 23:17:10 GMT
[View Forum Message](#) <> [Reply to Message](#)

I think this is the right way to handle the lockdep false-positive in the current containers patches, but I'm not that familiar with lockdep so any suggestions for a better approach are welcomed.

In order to avoid a false-positive lockdep warning, we lock the root inode of a new filesystem mount prior to taking container_mutex, to preserve the invariant that container_mutex nests inside inode->i_mutex. In order to prevent a lockdep false positive when locking i_mutex on a newly-created container directory inode we use mutex_lock_nested(), with a nesting level of I_MUTEX_CHILD since the new inode will ultimately be a child directory of the parent whose i_mutex is nested outside of container_mutex.

Signed-off-by: Paul Menage <menage@google.com>

kernel/container.c | 17 ++++++-----
1 file changed, 7 insertions(+), 10 deletions(-)

Index: container-2.6.23-rc3-mm1/kernel/container.c

```
=====
--- container-2.6.23-rc3-mm1.orig/kernel/container.c
+++ container-2.6.23-rc3-mm1/kernel/container.c
@@ -966,13 +966,16 @@ static int container_get_sb(struct file_
 } else {
     /* New superblock */
     struct container *cont = &root->top_container;
+ struct inode *inode;

     BUG_ON(sb->s_root != NULL);

     ret = container_get_rootdir(sb);
     if (ret)
         goto drop_new_super;
+ inode = sb->s_root->d_inode;

+ mutex_lock(&inode->i_mutex);
     mutex_lock(&container_mutex);

     /*
@@ -985,12 +988,14 @@ static int container_get_sb(struct file_
     ret = allocate_cg_links(css_group_count, &tmp_cg_links);
     if (ret) {
```

```

    mutex_unlock(&container_mutex);
+ mutex_unlock(&inode->i_mutex);
    goto drop_new_super;
}

ret = rebind_subsystems(root, root->subsys_bits);
if (ret == -EBUSY) {
    mutex_unlock(&container_mutex);
+ mutex_unlock(&inode->i_mutex);
    goto drop_new_super;
}

@@ -1030,16 +1035,8 @@ static int container_get_sb(struct file_
    BUG_ON(!list_empty(&cont->children));
    BUG_ON(root->number_of_containers != 1);

- /*
-  * I believe that it's safe to nest i_mutex inside
-  * container_mutex in this case, since no-one else can
-  * be accessing this directory yet. But we still need
-  * to teach lockdep that this is the case - currently
-  * a containerfs remount triggers a lockdep warning
-  */
- mutex_lock(&cont->dentry->d_inode->i_mutex);
    container_populate_dir(cont);
- mutex_unlock(&cont->dentry->d_inode->i_mutex);
+ mutex_unlock(&inode->i_mutex);
    mutex_unlock(&container_mutex);
}

@@ -1529,7 +1526,7 @@ static int container_create_file(struct

    /* start with the directory inode held, so that we can
     * populate it without racing with another mkdir */
- mutex_lock(&inode->i_mutex);
+ mutex_lock_nested(&inode->i_mutex, I_MUTEX_CHILD);
} else if (S_ISREG(mode)) {
    inode->i_size = 0;
    inode->i_fop = &container_file_operations;

```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
