
Subject: [-mm PATCH 1/10] Memory controller resource counters (v7)

Posted by [Balbir Singh](#) on Fri, 24 Aug 2007 15:19:58 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Pavel Emelianov <xemul@openvz.org>

Introduce generic structures and routines for resource accounting.

Each resource accounting container is supposed to aggregate it,
container_subsystem_state and its resource-specific members within.

Signed-off-by: Pavel Emelianov <xemul@openvz.org>

Signed-off-by: Balbir Singh <balbir@linux.vnet.ibm.com>

```
include/linux/res_counter.h | 102 ++++++
init/Kconfig                |   7 ++
kernel/Makefile             |   1
kernel/res_counter.c        | 120 ++++++
4 files changed, 230 insertions(+)
```

```
diff -puN /dev/null include/linux/res_counter.h
```

```
--- /dev/null 2007-06-01 20:42:04.000000000 +0530
```

```
+++ linux-2.6.23-rc2-mm2-balbir/include/linux/res_counter.h 2007-08-24 20:46:06.000000000
+0530
```

```
@@ -0,0 +1,102 @@
```

```
+#ifndef __RES_COUNTER_H__
```

```
+#define __RES_COUNTER_H__
```

```
+
```

```
+/*
```

```
+ * Resource Counters
```

```
+ * Contain common data types and routines for resource accounting
```

```
+ *
```

```
+ * Copyright 2007 OpenVZ SWsoft Inc
```

```
+ *
```

```
+ * Author: Pavel Emelianov <xemul@openvz.org>
```

```
+ *
```

```
+ */
```

```
+
```

```
+#include <linux/container.h>
```

```
+
```

```
+/*
```

```
+ * The core object. the container that wishes to account for some
```

```
+ * resource may include this counter into its structures and use
```

```
+ * the helpers described beyond
```

```
+ */
```

```
+
```

```
+struct res_counter {
```

```

+ /*
+  * the current resource consumption level
+ */
+ unsigned long usage;
+ /*
+  * the limit that usage cannot exceed
+ */
+ unsigned long limit;
+ /*
+  * the number of unsuccessful attempts to consume the resource
+ */
+ unsigned long failcnt;
+ /*
+  * the lock to protect all of the above.
+  * the routines below consider this to be IRQ-safe
+ */
+ spinlock_t lock;
+};
+
+/*
+ * Helpers to interact with userspace
+ * res_counter_read/_write - put/get the specified fields from the
+ * res_counter struct to/from the user
+ *
+ * @counter:   the counter in question
+ * @member:   the field to work with (see RES_xxx below)
+ * @buf:      the buffer to operate on,...
+ * @nbytes:   its size...
+ * @pos:      and the offset.
+ */
+
+ssize_t res_counter_read(struct res_counter *counter, int member,
+ const char __user *buf, size_t nbytes, loff_t *pos);
+ssize_t res_counter_write(struct res_counter *counter, int member,
+ const char __user *buf, size_t nbytes, loff_t *pos);
+
+/*
+ * the field descriptors. one for each member of res_counter
+ */
+
+enum {
+ RES_USAGE,
+ RES_LIMIT,
+ RES_FAILCNT,
+};
+
+/*
+ * helpers for accounting

```

```

+ */
+
+void res_counter_init(struct res_counter *counter);
+
+/*
+ * charge - try to consume more resource.
+ *
+ * @counter: the counter
+ * @val: the amount of the resource. each controller defines its own
+ *       units, e.g. numbers, bytes, Kbytes, etc
+ *
+ * returns 0 on success and <0 if the counter->usage will exceed the
+ * counter->limit _locked call expects the counter->lock to be taken
+ */
+
+int res_counter_charge_locked(struct res_counter *counter, unsigned long val);
+int res_counter_charge(struct res_counter *counter, unsigned long val);
+
+/*
+ * uncharge - tell that some portion of the resource is released
+ *
+ * @counter: the counter
+ * @val: the amount of the resource
+ *
+ * these calls check for usage underflow and show a warning on the console
+ * _locked call expects the counter->lock to be taken
+ */
+
+void res_counter_uncharge_locked(struct res_counter *counter, unsigned long val);
+void res_counter_uncharge(struct res_counter *counter, unsigned long val);
+
+#endif
diff -puN init/Kconfig~mem-control-res-counters-infrastructure init/Kconfig
--- linux-2.6.23-rc2-mm2/init/Kconfig~mem-control-res-counters-infrastructure 2007-08-24
20:46:06.000000000 +0530
+++ linux-2.6.23-rc2-mm2-balbir/init/Kconfig 2007-08-24 20:46:06.000000000 +0530
@@ -337,6 +337,13 @@ config CPUSETS

```

Say N if unsure.

```

+config RESOURCE_COUNTERS
+ bool "Resource counters"
+ help
+   This option enables controller independent resource accounting
+   infrastructure that works with containers
+ depends on CONTAINERS
+
+config SYSFS_DEPRECATED

```

```

bool "Create deprecated sysfs files"
default y
diff -puN kernel/Makefile~mem-control-res-counters-infrastructure kernel/Makefile
--- linux-2.6.23-rc2-mm2/kernel/Makefile~mem-control-res-counters-infrastructure 2007-08-24
20:46:06.000000000 +0530
+++ linux-2.6.23-rc2-mm2-balbir/kernel/Makefile 2007-08-24 20:46:06.000000000 +0530
@@ -59,6 +59,7 @@ obj-$(CONFIG_RELAY) += relay.o
obj-$(CONFIG_SYSCTL) += utsname_sysctl.o
obj-$(CONFIG_TASK_DELAY_ACCT) += delayacct.o
obj-$(CONFIG_TASKSTATS) += taskstats.o tsacct.o
+obj-$(CONFIG_RESOURCE_COUNTERS) += res_counter.o

ifneq ($(CONFIG_SCHED_NO_NO_OMIT_FRAME_POINTER),y)
# According to Alan Modra <alan@linuxcare.com.au>, the -fno-omit-frame-pointer is
diff -puN /dev/null kernel/res_counter.c
--- /dev/null 2007-06-01 20:42:04.000000000 +0530
+++ linux-2.6.23-rc2-mm2-balbir/kernel/res_counter.c 2007-08-24 20:46:06.000000000 +0530
@@ -0,0 +1,120 @@
+/*
+ * resource containers
+ *
+ * Copyright 2007 OpenVZ SWsoft Inc
+ *
+ * Author: Pavel Emelianov <xemul@openvz.org>
+ *
+ */
+
+#include <linux/types.h>
+#include <linux/parser.h>
+#include <linux/fs.h>
+#include <linux/res_counter.h>
+#include <linux/uaccess.h>
+
+void res_counter_init(struct res_counter *counter)
+{
+ spin_lock_init(&counter->lock);
+ counter->limit = (unsigned long)LONG_MAX;
+}
+
+int res_counter_charge_locked(struct res_counter *counter, unsigned long val)
+{
+ if (counter->usage > (counter->limit - val)) {
+ counter->failcnt++;
+ return -ENOMEM;
+ }
+
+ counter->usage += val;
+ return 0;

```

```

+}
+
+int res_counter_charge(struct res_counter *counter, unsigned long val)
+{
+ int ret;
+ unsigned long flags;
+
+ spin_lock_irqsave(&counter->lock, flags);
+ ret = res_counter_charge_locked(counter, val);
+ spin_unlock_irqrestore(&counter->lock, flags);
+ return ret;
+}
+
+void res_counter_uncharge_locked(struct res_counter *counter, unsigned long val)
+{
+ if (WARN_ON(counter->usage < val))
+ val = counter->usage;
+
+ counter->usage -= val;
+}
+
+void res_counter_uncharge(struct res_counter *counter, unsigned long val)
+{
+ unsigned long flags;
+
+ spin_lock_irqsave(&counter->lock, flags);
+ res_counter_uncharge_locked(counter, val);
+ spin_unlock_irqrestore(&counter->lock, flags);
+}
+
+
+static inline unsigned long *res_counter_member(struct res_counter *counter,
+ int member)
+{
+ switch (member) {
+ case RES_USAGE:
+ return &counter->usage;
+ case RES_LIMIT:
+ return &counter->limit;
+ case RES_FAILCNT:
+ return &counter->failcnt;
+ };
+
+ BUG();
+ return NULL;
+}
+
+ssize_t res_counter_read(struct res_counter *counter, int member,

```

```

+ const char __user *userbuf, size_t nbytes, loff_t *pos)
+{
+ unsigned long *val;
+ char buf[64], *s;
+
+ s = buf;
+ val = res_counter_member(counter, member);
+ s += sprintf(s, "%lu\n", *val);
+ return simple_read_from_buffer((void __user *)userbuf, nbytes,
+ pos, buf, s - buf);
+}
+
+ssize_t res_counter_write(struct res_counter *counter, int member,
+ const char __user *userbuf, size_t nbytes, loff_t *pos)
+{
+ int ret;
+ char *buf, *end;
+ unsigned long tmp, *val;
+
+ buf = kmalloc(nbytes + 1, GFP_KERNEL);
+ ret = -ENOMEM;
+ if (buf == NULL)
+ goto out;
+
+ buf[nbytes] = '\0';
+ ret = -EFAULT;
+ if (copy_from_user(buf, userbuf, nbytes))
+ goto out_free;
+
+ ret = -EINVAL;
+ tmp = simple_strtoul(buf, &end, 10);
+ if (*end != '\0')
+ goto out_free;
+
+ val = res_counter_member(counter, member);
+ *val = tmp;
+ ret = nbytes;
+out_free:
+ kfree(buf);
+out:
+ return ret;
+}

```

—

--

Warm Regards,
Balbir Singh
Linux Technology Center

IBM, ISTL

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
