
Subject: Re: [PATCH] Use helpers to obtain task pid in printks (arch code)

Posted by [Joe Perches](#) on Mon, 27 Aug 2007 18:01:48 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Mon, 2007-08-27 at 11:30 +0400, Pavel Emelyanov wrote:

> From: Alexey Dobriyan <adobriyan@openvz.org>

>

> One of the easiest things to isolate is the pid printed in kernel

> log. There was a patch, that made this for arch-independent code,

> this one makes so for arch/xxx files.

Perhaps it would be worthwhile to standardize the printk
task information content? Maybe a format knob?

Maybe TASK_FMT/TASK_ARG(task)

```
#define TASK_FMT "%s"
```

```
#define TASK_ARG(tsk) ({char __buf[MAX_TASK_INFO]; print_task(tsk, buf, sizeof(__buf));  
__buf})
```

```
char* print_task(const struct task_struct* tsk, char* buf, size_t size)
```

```
{  
    char* p = buf;  
    int task_knob = get_task_knob();  
    *p++ = '[';  
    if (task_knob & feature)  
        p += snprintf(p, size - (p - buf), fmt, feature);  
    [...]  
    *p++ = ']';  
    return buf;  
}
```

```
EXPORT_SYMBOL(print_task)
```

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
