
Subject: Re: [PATCH] Use task_pid_nr() in ip_vs_sync.c
Posted by [Sukadev Bhattiprolu](#) on Wed, 29 Aug 2007 21:50:55 GMT
[View Forum Message](#) <> [Reply to Message](#)

Pavel Emelianov [xemul@openvz.org] wrote:
| The sync_master_pid and sync_backup_pid are set in set_sync_pid()
| and are used later for set/not-set checks and in printk. So it
| is safe to use the global pid value in this case.
|
| Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

Acked-by: Sukadev Bhattiprolu <sukadev@us.ibm.com>

|
| ---
|
| diff --git a/net/ipv4/ipvs/ip_vs_sync.c b/net/ipv4/ipvs/ip_vs_sync.c
| index 959c08d..d0798a5 100644
| --- a/net/ipv4/ipvs/ip_vs_sync.c
| +++ b/net/ipv4/ipvs/ip_vs_sync.c
| @@ -794,7 +794,7 @@ static int sync_thread(void *startup)
|
| add_wait_queue(&sync_wait, &wait);
|
| - set_sync_pid(state, current->pid);
| + set_sync_pid(state, task_pid_nr(current));
| complete(tinfo->startup);
|
| /*

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
