
Subject: [PATCH 01/16] appletalk: In notifier handlers convert the void pointer to a netdevice

Posted by [ebiederm](#) on Sat, 08 Sep 2007 21:09:36 GMT

[View Forum Message](#) <> [Reply to Message](#)

This slightly improves code safety and clarity.

Later network namespace patches touch this code so this is a preliminary cleanup.

Signed-off-by: Eric W. Biederman <ebiederm@xmission.com>

net/appletalk/aarp.c | 7 +++++--

net/appletalk/ddp.c | 4 +++-

2 files changed, 7 insertions(+), 4 deletions(-)

diff --git a/net/appletalk/aarp.c b/net/appletalk/aarp.c

index 3d1655f..80b5414 100644

--- a/net/appletalk/aarp.c

+++ b/net/appletalk/aarp.c

@@ -330,15 +330,16 @@ static void aarp_expire_timeout(unsigned long unused)

static int aarp_device_event(struct notifier_block *this, unsigned long event,
void *ptr)

{

+ struct net_device *dev = ptr;
int ct;

if (event == NETDEV_DOWN) {
write_lock_bh(&aarp_lock);

for (ct = 0; ct < AARP_HASH_SIZE; ct++) {

- __aarp_expire_device(&resolved[ct], ptr);

- __aarp_expire_device(&unresolved[ct], ptr);

- __aarp_expire_device(&proxies[ct], ptr);

+ __aarp_expire_device(&resolved[ct], dev);

+ __aarp_expire_device(&unresolved[ct], dev);

+ __aarp_expire_device(&proxies[ct], dev);

}

write_unlock_bh(&aarp_lock);

diff --git a/net/appletalk/ddp.c b/net/appletalk/ddp.c

index fbdfb12..594b597 100644

--- a/net/appletalk/ddp.c

+++ b/net/appletalk/ddp.c

@@ -647,9 +647,11 @@ static inline void atalk_dev_down(struct net_device *dev)

static int ddp_device_event(struct notifier_block *this, unsigned long event,
void *ptr)

{

```
+ struct net_device *dev = ptr;
+
+ if (event == NETDEV_DOWN)
+   /* Discard any use of this */
- atalk_dev_down(ptr);
+ atalk_dev_down(dev);

return NOTIFY_DONE;
}
--
1.5.3.rc6.17.g1911
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
