
Subject: Re: [PATCH] Hookup group-scheduler with task container infrastructure
Posted by [Srivatsa Vaddagiri](#) on Mon, 10 Sep 2007 17:46:49 GMT

[View Forum Message](#) <> [Reply to Message](#)

On Mon, Sep 10, 2007 at 10:22:59AM -0700, Andrew Morton wrote:
> objection ;) "cpuctlr" isn't memorable. Kernel code is write-rarely,
> read-often. "cpu_controller", please. The extra typing is worth it ;)

Ok! Here's the modified patch (against 2.6.23-rc4-mm1).

Signed-off-by : Srivatsa Vaddagiri <vatsa@linux.vnet.ibm.com>
Signed-off-by : Dhaval Giani <dhaval@linux.vnet.ibm.com>

```
---  
include/linux/container_subsys.h |  5  
init/Kconfig                   |  9 +  
kernel/sched.c                | 311 ++++++-----  
kernel/sched_fair.c           |   3  
4 files changed, 313 insertions(+), 15 deletions(-)  
  
Index: current/include/linux/container_subsys.h  
=====--- current.orig/include/linux/container_subsys.h  
+++ current/include/linux/container_subsys.h  
@@ -36,3 +36,8 @@ SUBSYS(mem_container)  
#endif  
  
/* */  
+#ifdef CONFIG_FAIR_GROUP_SCHED  
+SUBSYS(cpu_controller)  
+#endif  
+  
+/* */  
Index: current/init/Kconfig  
=====--- current.orig/init/Kconfig  
+++ current/init/Kconfig  
@@ -326,6 +326,15 @@ config RESOURCE_COUNTERS  
    infrastructure that works with containers  
    depends on CONTAINERS  
  
+config FAIR_GROUP_SCHED  
+ bool "Fair group scheduler"  
+ depends on EXPERIMENTAL && CONTAINERS  
+ help  
+  This option enables you to group tasks and control CPU resource  
+  allocation to such groups.  
+
```

```

+ Say N if unsure.
+
config SYSFS_DEPRECATED
    bool "Create deprecated sysfs files"
    default y
Index: current/kernel/sched.c
=====
--- current.orig/kernel/sched.c
+++ current/kernel/sched.c
@@ -179,6 +179,58 @@ struct load_stat {
    unsigned long delta_fair, delta_exec, delta_stat;
};

+#ifdef CONFIG_FAIR_GROUP_SCHED
+
+#include <linux/container.h>
+
+struct cfs_rq;
+
+/* task group related information */
+struct task_grp {
+    struct container_subsys_state css;
+    /* schedulable entities of this group on each cpu */
+    struct sched_entity **se;
+    /* runqueue "owned" by this group on each cpu */
+    struct cfs_rq **cfs_rq;
+    unsigned long shares;
+};
+
+/* Default task group's sched entity on each cpu */
+static DEFINE_PER_CPU(struct sched_entity, init_sched_entity);
+/* Default task group's cfs_rq on each cpu */
+static DEFINE_PER_CPU(struct cfs_rq, init_cfs_rq) ____ cacheline_aligned_in_smp;
+
+static struct sched_entity *init_sched_entity_p[CONFIG_NR_CPUS];
+static struct cfs_rq *init_cfs_rq_p[CONFIG_NR_CPUS];
+
+/* Default task group.
+ * Every task in system belong to this group at bootup.
+ */
+static struct task_grp init_task_grp = {
+    .se    = init_sched_entity_p,
+    .cfs_rq = init_cfs_rq_p,
+};
+
+/* return group to which a task belongs */
+static inline struct task_grp *task_grp(struct task_struct *p)
+{

```

```

+ return container_of(task_subsys_state(p, cpu_controller_subsys_id),
+ struct task_grp, css);
+}
+
+/* Change a task's cfs_rq and parent entity if it moves across CPUs/groups */
+static inline void set_task_cfs_rq(struct task_struct *p)
+{
+ p->se.cfs_rq = task_grp(p)->cfs_rq[task_cpu(p)];
+ p->se.parent = task_grp(p)->se[task_cpu(p)];
+}
+
+#
+#else
+
+static inline void set_task_cfs_rq(struct task_struct *p) { }
+
+#
#endif /* CONFIG_FAIR_GROUP_SCHED */
+
/* CFS-related fields in a runqueue */
struct cfs_rq {
    struct load_weight load;
@@ -208,6 +260,7 @@ struct cfs_rq {
    * list is used during load balance.
    */
    struct list_head leaf_cfs_rq_list; /* Better name : task_cfs_rq_list? */
+ struct task_grp *tg; /* group that "owns" this runqueue */
#endif
};

@@ -405,18 +458,6 @@ unsigned long long cpu_clock(int cpu)

```

EXPORT_SYMBOL_GPL(cpu_clock);

```

#ifndef CONFIG_FAIR_GROUP_SCHED
/* Change a task's ->cfs_rq if it moves across CPUs */
static inline void set_task_cfs_rq(struct task_struct *p)
-{
- p->se.cfs_rq = &task_rq(p)->cfs;
-}
#else
static inline void set_task_cfs_rq(struct task_struct *p)
-{
-}
#endif
-
#ifndef prepare_arch_switch
#define prepare_arch_switch(next) do { } while (0)
#endif
@@ -6567,7 +6608,25 @@ void __init sched_init(void)

```

```

init_cfs_rq(&rq->cfs, rq);
#ifndef CONFIG_FAIR_GROUP_SCHED
INIT_LIST_HEAD(&rq->leaf_cfs_rq_list);
- list_add(&rq->cfs.leaf_cfs_rq_list, &rq->leaf_cfs_rq_list);
+
+ {
+   struct cfs_rq *cfs_rq = &per_cpu(init_cfs_rq, i);
+   struct sched_entity *se =
+     &per_cpu(init_sched_entity, i);
+
+   init_cfs_rq_p[i] = cfs_rq;
+   init_cfs_rq(cfs_rq, rq);
+   cfs_rq->tg = &init_task_grp;
+   list_add(&cfs_rq->leaf_cfs_rq_list,
+           &rq->leaf_cfs_rq_list);
+
+   init_sched_entity_p[i] = se;
+   se->cfs_rq = &rq->cfs;
+   se->my_q = cfs_rq;
+   se->load.weight = NICE_0_LOAD;
+   se->load.inv_weight = div64_64(1ULL<<32, NICE_0_LOAD);
+   se->parent = NULL;
+ }
+ init_task_grp.shares = NICE_0_LOAD;
#endif
rq->ls.load_update_last = now;
rq->ls.load_update_start = now;
@@ -6764,3 +6823,229 @@ void set_curr_task(int cpu, struct task_
}

#endif
+
+/* return corresponding task_grp object of a container */
+static inline struct task_grp *container_tg(struct container *cont)
+{
+ return container_of(container_subsys_state(cont,
+   cpu_controller_subsys_id), struct task_grp, css);
+}
+
+/* allocate runqueue etc for a new task group */
+static struct container_subsys_state *
+sched_create_group(struct container_subsys *ss, struct container *cont)
+{
+ struct task_grp *tg;
+ struct cfs_rq *cfs_rq;
+ struct sched_entity *se;
+ int i;

```

```

+
+ if (!cont->parent) {
+ /* This is early initialization for the top container */
+ init_task_grp.css.container = cont;
+ return &init_task_grp.css;
+ }
+
+ /* we support only 1-level deep hierarchical scheduler atm */
+ if (cont->parent->parent)
+ return ERR_PTR(-EINVAL);
+
+ tg = kzalloc(sizeof(*tg), GFP_KERNEL);
+ if (!tg)
+ return ERR_PTR(-ENOMEM);
+
+ tg->cfs_rq = kzalloc(sizeof(cfs_rq) * num_possible_cpus(), GFP_KERNEL);
+ if (!tg->cfs_rq)
+ goto err;
+ tg->se = kzalloc(sizeof(se) * num_possible_cpus(), GFP_KERNEL);
+ if (!tg->se)
+ goto err;
+
+ for_each_possible_cpu(i) {
+ struct rq *rq = cpu_rq(i);
+
+ cfs_rq = kmalloc_node(sizeof(struct cfs_rq), GFP_KERNEL,
+ cpu_to_node(i));
+ if (!cfs_rq)
+ goto err;
+
+ se = kmalloc_node(sizeof(struct sched_entity), GFP_KERNEL,
+ cpu_to_node(i));
+ if (!se)
+ goto err;
+
+ memset(cfs_rq, 0, sizeof(struct cfs_rq));
+ memset(se, 0, sizeof(struct sched_entity));
+
+ tg->cfs_rq[i] = cfs_rq;
+ init_cfs_rq(cfs_rq, rq);
+ cfs_rq->tg = tg;
+ list_add_rcu(&cfs_rq->leaf_cfs_rq_list, &rq->leaf_cfs_rq_list);
+
+ tg->se[i] = se;
+ se->cfs_rq = &rq->cfs_rq;
+ se->my_q = cfs_rq;
+ se->load.weight = NICE_0_LOAD;
+ se->load.inv_weight = div64_64(1ULL<<32, NICE_0_LOAD);

```

```

+ se->parent = NULL;
+ }
+
+ tg->shares = NICE_0_LOAD;
+
+ /* Bind the container to task_grp object we just created */
+ tg->css.container = cont;
+
+ return &tg->css;
+
+err:
+ for_each_possible_cpu(i) {
+ if (tg->cfs_rq && tg->cfs_rq[i])
+ kfree(tg->cfs_rq[i]);
+ if (tg->se && tg->se[i])
+ kfree(tg->se[i]);
+ }
+ if (tg->cfs_rq)
+ kfree(tg->cfs_rq);
+ if (tg->se)
+ kfree(tg->se);
+ if (tg)
+ kfree(tg);
+
+ return ERR_PTR(-ENOMEM);
+}
+
+/*
+ * destroy runqueue etc associated with a task group */
+static void sched_destroy_group(struct container_subsys *ss,
+ struct container *cont)
+{
+ struct task_grp *tg = container_tg(cont);
+ struct cfs_rq *cfs_rq;
+ struct sched_entity *se;
+ int i;
+
+ for_each_possible_cpu(i) {
+ cfs_rq = tg->cfs_rq[i];
+ list_del_rcu(&cfs_rq->leaf_cfs_rq_list);
+ }
+
+ /* wait for possible concurrent references to cfs_rqs complete */
+ synchronize_sched();
+
+ /* now it should be safe to free those cfs_rqs */
+ for_each_possible_cpu(i) {
+ cfs_rq = tg->cfs_rq[i];

```

```

+ kfree(cfs_rq);
+
+ se = tg->se[i];
+ kfree(se);
+
+ }
+
+ kfree(tg);
+}
+
+/* change task's runqueue when it moves between groups */
+static void sched_move_task(struct container_subsys *ss, struct container *cont,
+    struct container *old_cont, struct task_struct *tsk)
+{
+ int on_rq;
+ unsigned long flags;
+ struct rq *rq;
+
+ rq = task_rq_lock	tsk, &flags);
+
+ on_rq = tsk->se.on_rq;
+ if (on_rq)
+ deactivate_task(rq, tsk, 0);
+
+ if (unlikely(rq->curr == tsk) && tsk->sched_class == &fair_sched_class)
+ tsk->sched_class->put_prev_task(rq, tsk);
+
+ set_task_cfs_rq(tsk);
+
+ if (on_rq)
+ activate_task(rq, tsk, 0);
+
+ if (unlikely(rq->curr == tsk) && tsk->sched_class == &fair_sched_class)
+ tsk->sched_class->set_curr_task(rq);
+
+ task_rq_unlock(rq, &flags);
+}

+static void set_se_shares(struct sched_entity *se, unsigned long shares)
+{
+ struct cfs_rq *cfs_rq = se->cfs_rq;
+ struct rq *rq = cfs_rq->rq;
+ int on_rq;
+
+ spin_lock_irq(&rq->lock);
+
+ on_rq = se->on_rq;
+ if (on_rq)
+ __dequeue_entity(cfs_rq, se);

```

```

+
+ se->load.weight = shares;
+ se->load.inv_weight = div64_64((1ULL<<32), shares);
+
+ if (on_rq)
+ __enqueue_entity(cfs_rq, se);
+
+ spin_unlock_irq(&rq->lock);
+}
+
+static ssize_t cpu_shares_write(struct container *cont, struct cftype *cftype,
+ struct file *file, const char __user *userbuf,
+ size_t nbytes, loff_t *ppos)
+{
+ int i;
+ unsigned long shareval;
+ struct task_grp *tg = container_tg(cont);
+ char buffer[2*sizeof(unsigned long)];
+
+ if (nbytes > 2*sizeof(unsigned long)) /* safety check */
+ return -E2BIG;
+
+ if (copy_from_user(buffer, userbuf, nbytes))
+ return -EFAULT;
+
+ buffer[nbytes] = 0; /* nul-terminate */
+ shareval = simple_strtoul(buffer, NULL, 10);
+
+ tg->shares = shareval;
+ for_each_possible_cpu(i)
+ set_se_shares(tg->se[i], shareval);
+
+ return nbytes;
+}
+
+static u64 cpu_shares_read_uint(struct container *cont, struct cftype *cft)
+{
+ struct task_grp *tg = container_tg(cont);
+
+ return (u64) tg->shares;
+}
+
+struct cftype cpuctl_share = {
+ .name = "shares",
+ .read_uint = cpu_shares_read_uint,
+ .write = cpu_shares_write,
+};
+

```

```

+static int sched_populate(struct container_subsys *ss, struct container *cont)
+{
+    return container_add_file(cont, ss, &cpuctl_share);
+}
+
+struct container_subsys cpu_controller_subsys = {
+    .name = "cpu",
+    .create = sched_create_group,
+    .destroy = sched_destroy_group,
+    .attach = sched_move_task,
+    .populate = sched_populate,
+    .subsys_id = cpu_controller_subsys_id,
+    .early_init = 1,
+};
+
+#endif /* CONFIG_FAIR_GROUP_SCHED */
Index: current/kernel/sched_fair.c
=====
```

```

--- current.orig/kernel/sched_fair.c
+++ current/kernel/sched_fair.c
@@ -798,8 +798,7 @@ static inline struct cfs_rq *group_cfs_r
 */
static inline struct cfs_rq *cpu_cfs_rq(struct cfs_rq *cfs_rq, int this_cpu)
{
- /* A later patch will take group into account */
- return &cpu_rq(this_cpu)->cfs;
+ return cfs_rq->tg->cfs_rq[this_cpu];
}

/* Iterate thr' all leaf cfs_rq's on a runqueue */
```

--
Regards,
vatsa

Containers mailing list
 Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
