
Subject: [PATCH 05/29] task containersv11 add container_clone interface

Posted by [Paul Menage](#) on Tue, 11 Sep 2007 19:52:44 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Paul Menage <menage@google.com>

Add support for cgroup_clone(), a way to create new cgroups intended to be used for systems such as namespace unsharing. A new subsystem callback, post_clone(), is added to allow subsystems to automatically configure cloned cgroups.

Signed-off-by: Paul Menage <menage@google.com>

Cc: Serge E. Hallyn <serue@us.ibm.com>

Cc: "Eric W. Biederman" <ebiederm@xmission.com>

Cc: Dave Hansen <haveblue@us.ibm.com>

Cc: Balbir Singh <balbir@in.ibm.com>

Cc: Paul Jackson <pj@sgi.com>

Cc: Kirill Korotaev <dev@openvz.org>

Cc: Herbert Poetzl <herbert@13thfloor.at>

Cc: Srivatsa Vaddagiri <vatsa@in.ibm.com>

Cc: Cedric Le Goater <cclg@fr.ibm.com>

Signed-off-by: Andrew Morton <akpm@linux-foundation.org>

Documentation/cgroups.txt | 7 +

include/linux/cgroup.h | 3

kernel/cgroup.c | 135 ++++++-----+-----+-----+-----+

3 files changed, 145 insertions(+)

diff -puN Documentation/cgroups.txt~task-cgroupsv11-add-cgroup_clone-interface

Documentation/cgroups.txt

--- a/Documentation/cgroups.txt~task-cgroupsv11-add-cgroup_clone-interface

+++ a/Documentation/cgroups.txt

@@ -504,6 +504,13 @@ include/linux/cgroup.h for details).

method can return an error code, the error code is currently not always handled well.

+void post_clone(struct cgroup_subsys *ss, struct cgroup *cont)

+

+Called at the end of cgroup_clone() to do any parameter

+initialization which might be required before a task could attach. For

+example in cpusets, no task may attach before 'cpus' and 'mems' are set

+up.

+

void bind(struct cgroup_subsys *ss, struct cgroup *root)

LL=callback_mutex

diff -puN include/linux/cgroup.h~task-cgroupsv11-add-cgroup_clone-interface

```

include/linux/cgroup.h
--- a/include/linux/cgroup.h~task-cgroups11-add-cgroup_clone-interface
+++ a/include/linux/cgroup.h
@@ -174,6 +174,7 @@ struct cgroup_subsys {
    void (*exit)(struct cgroup_subsys *ss, struct task_struct *task);
    int (*populate)(struct cgroup_subsys *ss,
                   struct cgroup *cont);
+   void (*post_clone)(struct cgroup_subsys *ss, struct cgroup *cont);
    void (*bind)(struct cgroup_subsys *ss, struct cgroup *root);
    int subsys_id;
    int active;
@@ -213,6 +214,8 @@ static inline struct cgroup* task_con

int cgroup_path(const struct cgroup *cont, char *buf, int buflen);

+int cgroup_clone(struct task_struct *tsk, struct cgroup_subsys *ss);
+
#endif /* !CONFIG_CGROUPS */

static inline int cgroup_init_early(void) { return 0; }
diff -puN kernel/cgroup.c~task-cgroups11-add-cgroup_clone-interface kernel/cgroup.c
--- a/kernel/cgroup.c~task-cgroups11-add-cgroup_clone-interface
+++ a/kernel/cgroup.c
@@ -1684,3 +1684,138 @@ void cgroup_exit(struct task_struct *
    tsk->cgroups = init_task.cgroups;
    task_unlock(tsk);
}
+
+/**
+ * cgroup_clone - duplicate the current cgroup in the hierarchy
+ * that the given subsystem is attached to, and move this task into
+ * the new child
+ */
+int cgroup_clone(struct task_struct *tsk, struct cgroup_subsys *subsys)
+{
+   struct dentry *dentry;
+   int ret = 0;
+   char nodename[MAX_CGROUP_TYPE_NAMELEN];
+   struct cgroup *parent, *child;
+   struct inode *inode;
+   struct css_set *cg;
+   struct cgroupfs_root *root;
+   struct cgroup_subsys *ss;
+
+   /**
+    * We shouldn't be called by an unregistered subsystem */
+   BUG_ON(!subsys->active);
+
+   /**
+    * First figure out what hierarchy and cgroup we're dealing

```

```

+ * with, and pin them so we can drop cgroup_mutex */
+ mutex_lock(&cgroup_mutex);
+ again:
+ root = subsys->root;
+ if (root == &rootnode) {
+ printk(KERN_INFO
+ "Not cloning cgroup for unused subsystem %s\n",
+ subsys->name);
+ mutex_unlock(&cgroup_mutex);
+ return 0;
+ }
+ cg = &tsk->cgroups;
+ parent = task_cgroup(tsk, subsys->subsys_id);
+
+ snprintf(nodename, MAX_CGROUP_TYPE_NAMELEN, "node_%d", tsk->pid);
+
+ /* Pin the hierarchy */
+ atomic_inc(&parent->root->sb->s_active);
+
+ mutex_unlock(&cgroup_mutex);
+
+ /* Now do the VFS work to create a cgroup */
+ inode = parent->dentry->d_inode;
+
+ /* Hold the parent directory mutex across this operation to
+ * stop anyone else deleting the new cgroup */
+ mutex_lock(&inode->i_mutex);
+ dentry = cgroup_get_dentry(parent->dentry, nodename);
+ if (IS_ERR(dentry)) {
+ printk(KERN_INFO
+ "Couldn't allocate dentry for %s: %ld\n", nodename,
+ PTR_ERR(dentry));
+ ret = PTR_ERR(dentry);
+ goto out_release;
+ }
+
+ /* Create the cgroup directory, which also creates the cgroup */
+ ret = vfs_mkdir(inode, dentry, S_IFDIR | 0755);
+ child = __d_cont(dentry);
+ dput(dentry);
+ if (ret) {
+ printk(KERN_INFO
+ "Failed to create cgroup %s: %d\n", nodename,
+ ret);
+ goto out_release;
+ }
+
+ if (!child) {

```

```

+ printk(KERN_INFO
+       "Couldn't find new cgroup %s\n", nodename);
+ ret = -ENOMEM;
+ goto out_release;
+ }
+
+ /* The cgroup now exists. Retake cgroup_mutex and check
+ * that we're still in the same state that we thought we
+ * were. */
+ mutex_lock(&cgroup_mutex);
+ if ((root != subsys->root) ||
+     (parent != task_cgroup(tsk, subsys->subsys_id))) {
+ /* Aargh, we raced ... */
+ mutex_unlock(&inode->i_mutex);
+
+ deactivate_super(parent->root->sb);
+ /* The cgroup is still accessible in the VFS, but
+ * we're not going to try to rmdir() it at this
+ * point. */
+ printk(KERN_INFO
+       "Race in cgroup_clone() - leaking cgroup %s\n",
+       nodename);
+ goto again;
+ }
+
+ /* do any required auto-setup */
+ for_each_subsys(root, ss) {
+ if (ss->post_clone)
+ ss->post_clone(ss, child);
+ }
+
+ /* All seems fine. Finish by moving the task into the new cgroup */
+ ret = attach_task(child, tsk);
+ mutex_unlock(&cgroup_mutex);
+
+ out_release:
+ mutex_unlock(&inode->i_mutex);
+ deactivate_super(parent->root->sb);
+ return ret;
+ }
+
+/*
+ * See if "cont" is a descendant of the current task's cgroup in
+ * the appropriate hierarchy
+ *
+ * If we are sending in dummytop, then presumably we are creating
+ * the top cgroup in the subsystem.
+ */

```

```
+ * Called only by the ns (nsproxy) cgroup.  
+ */  
+int cgroup_is_descendant(const struct cgroup *cont)  
+{  
+ int ret;  
+ struct cgroup *target;  
+ int subsys_id;  
+  
+ if (cont == dummytop)  
+ return 1;  
+  
+ get_first_subsys(cont, NULL, &subsys_id);  
+ target = task_cgroup(current, subsys_id);  
+ while (cont != target && cont!= cont->top_cgroup)  
+ cont = cont->parent;  
+ ret = (cont == target);  
+ return ret;  
+}  
-  
--
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
