
Subject: [net-2.6.24][NETNS][patch 2/3] fix loopback network namespace initialization

Posted by [Daniel Lezcano](#) on Wed, 12 Sep 2007 12:38:13 GMT

[View Forum Message](#) <> [Reply to Message](#)

From: Daniel Lezcano <dlezcano@fr.ibm.com>

The core patchset of the network namespace sent by Eric Biederman does not do dynamic loopback creation. So there is no call to `alloc_netdev_mq` which fills the network namespace field of the netdevice.

This patch assign the loopback to the init network namespace.

Signed-off-by: Daniel Lezcano <dlezcano@fr.ibm.com>

drivers/net/loopback.c | 1 +
1 file changed, 1 insertion(+)

Index: net-2.6.24/drivers/net/loopback.c

=====

--- net-2.6.24.orig/drivers/net/loopback.c

+++ net-2.6.24/drivers/net/loopback.c

@@ -225,6 +225,7 @@

| NETIF_F_LLTX

| NETIF_F_NETNS_LOCAL,

.ethtool_ops = &loopback_ethtool_ops,

+ .nd_net = &init_net,

};

/* Setup and register the loopback device. */

--

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
