

---

Subject: Re: [PATCH 1/2] Convert uid hash to hlist  
Posted by [serue](#) on Fri, 14 Sep 2007 18:25:12 GMT  
[View Forum Message](#) <> [Reply to Message](#)

---

Quoting Pavel Emelyanov (xemul@openvz.org):  
> Surprisingly, but (spotted by Alexey Dobriyan) the uid hash  
> still uses list\_heads, thus occupying twice as much place as  
> it could. Convert it to hlist\_heads.  
>  
> Signed-off-by: Pavel Emelyanov <xemul@openvz.org>  
> Signed-off-by: Alexey Dobriyan <adobriyan@openvz.org>  
> Cc: Serge Hallyn <serue@us.ibm.com>

Looks good.

Signed-off-by: Serge Hallyn <serue@us.ibm.com>

thanks,  
-serge

```
>  
> ---  
>  
> include/linux/sched.h      | 2 +-  
> include/linux/user_namespace.h | 2 +-  
> kernel/user.c              | 15 ++++++-----  
> kernel/user_namespace.c    | 2 +-  
> 4 files changed, 11 insertions(+), 10 deletions(-)  
>  
> diff --git a/include/linux/sched.h b/include/linux/sched.h  
> index f6cf87e..a2afa88 100644  
> --- a/include/linux/sched.h  
> +++ b/include/linux/sched.h  
> @@ -535,7 +535,7 @@ struct user_struct {  
> #endif  
>  
> /* Hash table maintenance information */  
> - struct list_head uidhash_list;  
> + struct hlist_node uidhash_node;  
> uid_t uid;  
> };  
>  
> diff --git a/include/linux/user_namespace.h b/include/linux/user_namespace.h  
> index 1101b0c..b5f41d4 100644  
> --- a/include/linux/user_namespace.h  
> +++ b/include/linux/user_namespace.h  
> @@ -11,7 +11,7 @@  
>
```

```

> struct user_namespace {
> struct kref kref;
> - struct list_head uidhash_table[UIDHASH_SZ];
> + struct hlist_head uidhash_table[UIDHASH_SZ];
> struct user_struct *root_user;
> };
>
> diff --git a/kernel/user.c b/kernel/user.c
> index e080ba8..add57c7 100644
> --- a/kernel/user.c
> +++ b/kernel/user.c
> @@ -55,21 +55,22 @@ struct user_struct root_user = {
> /*
> * These routines must be called with the uidhash spinlock held!
> */
> -static inline void uid_hash_insert(struct user_struct *up, struct list_head *hashent)
> +static inline void uid_hash_insert(struct user_struct *up, struct hlist_head *hashent)
> {
> - list_add(&up->uidhash_list, hashent);
> + hlist_add_head(&up->uidhash_node, hashent);
> }
>
> static inline void uid_hash_remove(struct user_struct *up)
> {
> - list_del(&up->uidhash_list);
> + hlist_del(&up->uidhash_node);
> }
>
> -static inline struct user_struct *uid_hash_find(uid_t uid, struct list_head *hashent)
> +static inline struct user_struct *uid_hash_find(uid_t uid, struct hlist_head *hashent)
> {
> struct user_struct *user;
> + struct hlist_node *h;
>
> - list_for_each_entry(user, hashent, uidhash_list) {
> + hlist_for_each_entry(user, h, hashent, uidhash_node) {
> if(user->uid == uid) {
> atomic_inc(&user->__count);
> return user;
> @@ -118,7 +119,7 @@ void free_uid(struct user_struct *up)
>
> struct user_struct * alloc_uid(struct user_namespace *ns, uid_t uid)
> {
> - struct list_head *hashent = uidhashentry(ns, uid);
> + struct hlist_head *hashent = uidhashentry(ns, uid);
> struct user_struct *up;
>
> spin_lock_irq(&uidhash_lock);

```

```
> @@ -207,7 +208,7 @@ static int __init uid_cache_init(void)
>   0, SLAB_HWCACHE_ALIGN|SLAB_PANIC, NULL);
>
>   for(n = 0; n < UIDHASH_SZ; ++n)
> -   INIT_LIST_HEAD(init_user_ns.uidhash_table + n);
> +   INIT_HLIST_HEAD(init_user_ns.uidhash_table + n);
>
>   /* Insert the root user immediately (init already runs as root) */
>   spin_lock_irq(&uidhash_lock);
> diff --git a/kernel/user_namespace.c b/kernel/user_namespace.c
> index df1d2cf..7af90fc 100644
> --- a/kernel/user_namespace.c
> +++ b/kernel/user_namespace.c
> @@ -39,7 +39,7 @@ static struct user_namespace *clone_user
>   kref_init(&ns->kref);
>
>   for (n = 0; n < UIDHASH_SZ; ++n)
> -   INIT_LIST_HEAD(ns->uidhash_table + n);
> +   INIT_HLIST_HEAD(ns->uidhash_table + n);
>
>   /* Insert new root user. */
>   ns->root_user = alloc_uid(ns, 0);
```

---