
Subject: [PATCH] change inotifyfs magic as the same magic is used for futexfs (v2)
Posted by [Andrey Mirkin](#) on Mon, 24 Sep 2007 08:46:06 GMT
[View Forum Message](#) <> [Reply to Message](#)

From: Andrey Mirkin <major@openvz.org>

Right now futexfs and inotifyfs have one magic 0xBAD1DEA, that looks a little bit confusing.
Use 0xBAD1DEA as magic for futexfs and 0x2BAD1DEA as magic for inotifyfs.

Signed-off-by: Andrey Mirkin <major@openvz.org>

```
fs/inotify_user.c    | 4 +++-
include/linux/magic.h | 3 +++
kernel/futex.c      | 3 ++-
3 files changed, 8 insertions(+), 2 deletions(-)
```

```
diff --git a/fs/inotify_user.c b/fs/inotify_user.c
index 9bf2f6c..5e00933 100644
```

```
--- a/fs/inotify_user.c
+++ b/fs/inotify_user.c
@@ -31,6 +31,7 @@ #include <linux/init.h>
#include <linux/list.h>
#include <linux/inotify.h>
#include <linux/syscalls.h>
+#include <linux/magic.h>
```

```
#include <asm/ioctls.h>
```

```
@@ -684,7 +685,8 @@ static int
inotify_get_sb(struct file_system_type *fs_type, int flags,
               const char *dev_name, void *data, struct vfsmount *mnt)
{
- return get_sb_pseudo(fs_type, "inotify", NULL, 0xBAD1DEA, mnt);
+ return get_sb_pseudo(fs_type, "inotify", NULL,
+ INOTIFYFS_SUPER_MAGIC, mnt);
}
```

```
static struct file_system_type inotify_fs_type = {
diff --git a/include/linux/futex.h b/include/linux/futex.h
diff --git a/include/linux/inotify.h b/include/linux/inotify.h
diff --git a/include/linux/magic.h b/include/linux/magic.h
index 36cc20d..722d475 100644
```

```
--- a/include/linux/magic.h
+++ b/include/linux/magic.h
@@ -38,4 +38,7 @@ #define REISER2FS_JR_SUPER_MAGIC_STRING
```

