
Subject: Kernel text size with the pid namespaces fixes
Posted by [Pavel Emelianov](#) on Tue, 25 Sep 2007 11:00:49 GMT
[View Forum Message](#) <> [Reply to Message](#)

Hi, Suka

I have posted tree patches with un-inlining of some macros and static inline calls that are expanded into another call.

At my i386 notebook this saved about half-a-kilo from the vmlinux. Could you please check these patches at your boxes/configs to see how much progress we have here.

Here's the combined patch for 2.6.24-rc8-mm1

Thanks,
Pavel

```
diff --git a/fs/ioprio.c b/fs/ioprio.c
index 0a615f8..d6ff77e 100644
--- a/fs/ioprio.c
+++ b/fs/ioprio.c
@@ -94,8 +94,7 @@ asmlinkage long sys_ioprio_set(int which
     if (!who)
         p = current;
     else
-    p = find_task_by_pid_ns(who,
-        current->nsproxy->pid_ns);
+    p = find_task_by_vpid(who);
     if (p)
         ret = set_task_ioprio(p, ioprio);
     break;
@@ -182,8 +181,7 @@ asmlinkage long sys_ioprio_get(int which
     if (!who)
         p = current;
     else
-    p = find_task_by_pid_ns(who,
-        current->nsproxy->pid_ns);
+    p = find_task_by_vpid(who);
     if (p)
         ret = get_task_ioprio(p);
     break;
diff --git a/include/linux/pid.h b/include/linux/pid.h
index 4817c66..e29a900 100644
--- a/include/linux/pid.h
+++ b/include/linux/pid.h
```

```

@@ -110,9 +110,8 @@ extern struct pid_namespace init_pid_ns;
 * see also find_task_by_pid() set in include/linux/sched.h
 */
extern struct pid *FASTCALL(find_pid_ns(int nr, struct pid_namespace *ns));
-
-#define find_vpid(pid) find_pid_ns(pid, current->nsproxy->pid_ns)
-#define find_pid(pid) find_pid_ns(pid, &init_pid_ns)
+extern struct pid *find_vpid(int nr);
+extern struct pid *find_pid(int nr);

/*
 * Lookup a PID in the hash table, and return with it's count elevated.
diff --git a/include/linux/sched.h b/include/linux/sched.h
index fe238fb..61d65c6 100644
--- a/include/linux/sched.h
+++ b/include/linux/sched.h
@@ -1228,11 +1228,7 @@ static inline pid_t task_pid_nr(struct t
     return tsk->pid;
 }

-static inline pid_t task_pid_nr_ns(struct task_struct *tsk,
- struct pid_namespace *ns)
-{
- return pid_nr_ns(task_pid(tsk), ns);
-}
+pid_t task_pid_nr_ns(struct task_struct *tsk, struct pid_namespace *ns);

static inline pid_t task_pid_vnr(struct task_struct *tsk)
{
@@ -1245,11 +1241,7 @@ static inline pid_t task_tgid_nr(struct
     return tsk->tgid;
 }

-static inline pid_t task_tgid_nr_ns(struct task_struct *tsk,
- struct pid_namespace *ns)
-{
- return pid_nr_ns(task_tgid(tsk), ns);
-}
+pid_t task_tgid_nr_ns(struct task_struct *tsk, struct pid_namespace *ns);

static inline pid_t task_tgid_vnr(struct task_struct *tsk)
{
@@ -1262,11 +1254,7 @@ static inline pid_t task_pgrp_nr(struct
     return tsk->signal->__pgrp;
 }

-static inline pid_t task_pgrp_nr_ns(struct task_struct *tsk,
- struct pid_namespace *ns)

```

```

- {
- return pid_nr_ns(task_pgrp(tsk), ns);
- }
+ pid_t task_pgrp_nr_ns(struct task_struct *tsk, struct pid_namespace *ns);

static inline pid_t task_pgrp_vnr(struct task_struct *tsk)
{
@@ -1279,11 +1267,7 @@ static inline pid_t task_session_nr(stru
    return tsk->signal->__session;
}

-static inline pid_t task_session_nr_ns(struct task_struct *tsk,
- struct pid_namespace *ns)
- {
- return pid_nr_ns(task_session(tsk), ns);
- }
+ pid_t task_session_nr_ns(struct task_struct *tsk, struct pid_namespace *ns);

static inline pid_t task_session_vnr(struct task_struct *tsk)
{
@@ -1505,9 +1489,8 @@ extern struct pid_namespace init_pid_ns;
*   type and namespace specified
* find_task_by_pid_ns():
*   finds a task by its pid in the specified namespace
- * find_task_by_pid_type():
- *   finds a task by its global id with the specified type, e.g.
- *   by global session id
+ * find_task_by_vpid():
+ *   finds a task by its virtual pid
* find_task_by_pid():
*   finds a task by its global pid
*
@@ -1517,12 +1500,10 @@ extern struct pid_namespace init_pid_ns;
extern struct task_struct *find_task_by_pid_type_ns(int type, int pid,
struct pid_namespace *ns);

#define find_task_by_pid_ns(nr, ns) \
- find_task_by_pid_type_ns(PIDTYPE_PID, nr, ns)
#define find_task_by_pid_type(type, nr) \
- find_task_by_pid_type_ns(type, nr, &init_pid_ns)
#define find_task_by_pid(nr) \
- find_task_by_pid_type(PIDTYPE_PID, nr)
+ extern struct task_struct *find_task_by_pid(pid_t nr);
+ extern struct task_struct *find_task_by_vpid(pid_t nr);
+ extern struct task_struct *find_task_by_pid_ns(pid_t nr,
+ struct pid_namespace *ns);

extern void __set_special_pids(pid_t session, pid_t pgrp);

```

```

diff --git a/kernel/capability.c b/kernel/capability.c
index 0440d6d..4a881b8 100644
--- a/kernel/capability.c
+++ b/kernel/capability.c
@@ -63,8 +63,7 @@ asmlinkage long sys_capget(cap_user_head
    read_lock(&tasklist_lock);

    if (pid && pid != task_pid_vnr(current)) {
- target = find_task_by_pid_ns(pid,
-   current->nsproxy->pid_ns);
+ target = find_task_by_vpid(pid);
    if (!target) {
        ret = -ESRCH;
        goto out;
@@ -97,7 +96,7 @@ static inline int cap_set_pg(int pgrp_nr
    int found = 0;
    struct pid *pgrp;

- pgrp = find_pid_ns(pgrp_nr, current->nsproxy->pid_ns);
+ pgrp = find_vpid(pgrp_nr);
    do_each_pid_task(pgrp, PIDTYPE_PGID, g) {
        target = g;
        while_each_thread(g, target) {
@@ -198,8 +197,7 @@ asmlinkage long sys_capset(cap_user_head
    read_lock(&tasklist_lock);

    if (pid > 0 && pid != task_pid_vnr(current)) {
- target = find_task_by_pid_ns(pid,
-   current->nsproxy->pid_ns);
+ target = find_task_by_vpid(pid);
    if (!target) {
        ret = -ESRCH;
        goto out;
diff --git a/kernel/futex.c b/kernel/futex.c
index 0c1b777..0d51412 100644
--- a/kernel/futex.c
+++ b/kernel/futex.c
@@ -444,9 +444,7 @@ static struct task_struct * futex_find_g
    struct task_struct *p;

    rcu_read_lock();
- p = find_task_by_pid_ns(pid,
-   current->nsproxy->pid_ns);
-
+ p = find_task_by_vpid(pid);
    if (!p || ((current->euid != p->euid) && (current->euid != p->uid)))
        p = ERR_PTR(-ESRCH);

```

```

else
@@ -1856,8 +1854,7 @@ sys_get_robust_list(int pid, struct robu

    ret = -ESRCH;
    rcu_read_lock();
-   p = find_task_by_pid_ns(pid,
-   current->nsproxy->pid_ns);
+   p = find_task_by_vpid(pid);
    if (!p)
        goto err_unlock;
    ret = -EPERM;
diff --git a/kernel/futex_compat.c b/kernel/futex_compat.c
index a21e766..d64f7c3 100644
--- a/kernel/futex_compat.c
+++ b/kernel/futex_compat.c
@@ -118,8 +118,7 @@ compat_sys_get_robust_list(int pid, comp

    ret = -ESRCH;
    read_lock(&tasklist_lock);
-   p = find_task_by_pid_ns(pid,
-   current->nsproxy->pid_ns);
+   p = find_task_by_vpid(pid);
    if (!p)
        goto err_unlock;
    ret = -EPERM;
diff --git a/kernel/pid.c b/kernel/pid.c
index e2e060e..d7388d7 100644
--- a/kernel/pid.c
+++ b/kernel/pid.c
@@ -302,6 +302,18 @@ struct pid *fastcall find_pid_ns(int nr
}
EXPORT_SYMBOL_GPL(find_pid_ns);

+struct pid *find_vpid(int nr)
+{
+   return find_pid_ns(nr, current->nsproxy->pid_ns);
+}
+EXPORT_SYMBOL_GPL(find_vpid);
+
+struct pid *find_pid(int nr)
+{
+   return find_pid_ns(nr, &init_pid_ns);
+}
+EXPORT_SYMBOL_GPL(find_pid);
+
+/*
+ * attach_pid() must be called with the tasklist_lock write-held.
+ */

```

```

@@ -368,6 +380,25 @@ struct task_struct *find_task_by_pid_type

EXPORT_SYMBOL(find_task_by_pid_type_ns);

+struct task_struct *find_task_by_pid(pid_t nr)
+{
+ return find_task_by_pid_type_ns(PIDTYPE_PID, nr, &init_pid_ns);
+}
+EXPORT_SYMBOL(find_task_by_pid);
+
+struct task_struct *find_task_by_vpid(pid_t vnr)
+{
+ return find_task_by_pid_type_ns(PIDTYPE_PID, vnr,
+   current->nsproxy->pid_ns);
+}
+EXPORT_SYMBOL(find_task_by_vpid);
+
+struct task_struct *find_task_by_pid_ns(pid_t nr, struct pid_namespace *ns)
+{
+ return find_task_by_pid_type_ns(PIDTYPE_PID, nr, ns);
+}
+EXPORT_SYMBOL(find_task_by_pid_ns);
+
struct pid *get_task_pid(struct task_struct *task, enum pid_type type)
{
    struct pid *pid;
@@ -412,6 +443,30 @@ pid_t pid_nr_ns(struct pid *pid, struct
    return nr;
}

+pid_t task_pid_nr_ns(struct task_struct *tsk, struct pid_namespace *ns)
+{
+ return pid_nr_ns(task_pid(tsk), ns);
+}
+EXPORT_SYMBOL(task_pid_nr_ns);
+
+pid_t task_tgid_nr_ns(struct task_struct *tsk, struct pid_namespace *ns)
+{
+ return pid_nr_ns(task_tgid(tsk), ns);
+}
+EXPORT_SYMBOL(task_tgid_nr_ns);
+
+pid_t task_pgrp_nr_ns(struct task_struct *tsk, struct pid_namespace *ns)
+{
+ return pid_nr_ns(task_pgrp(tsk), ns);
+}
+EXPORT_SYMBOL(task_pgrp_nr_ns);
+

```

```

+pid_t task_session_nr_ns(struct task_struct *tsk, struct pid_namespace *ns)
+{
+ return pid_nr_ns(task_session(tsk), ns);
+}
+EXPORT_SYMBOL(task_session_nr_ns);
+
+/*
+ * Used by proc to find the first pid that is greater then or equal to nr.
+ */
diff --git a/kernel/ptrace.c b/kernel/ptrace.c
index 812f1f3..593afeb 100644
--- a/kernel/ptrace.c
+++ b/kernel/ptrace.c
@@ -444,8 +444,7 @@ struct task_struct *ptrace_get_task_stru
     return ERR_PTR(-EPERM);

     read_lock(&tasklist_lock);
- child = find_task_by_pid_ns(pid,
- current->nsproxy->pid_ns);
+ child = find_task_by_vpid(pid);
     if (child)
         get_task_struct(child);

diff --git a/kernel/sched.c b/kernel/sched.c
index f22a216..b23c30f 100644
--- a/kernel/sched.c
+++ b/kernel/sched.c
@@ -4186,8 +4186,7 @@ struct task_struct *idle_task(int cpu)
 */
static inline struct task_struct *find_process_by_pid(pid_t pid)
{
- return pid ?
- find_task_by_pid_ns(pid, current->nsproxy->pid_ns) : current;
+ return pid ? find_task_by_vpid(pid) : current;
}

/* Actually do priority change: must hold rq lock. */
diff --git a/kernel/signal.c b/kernel/signal.c
index c5d72be..c308c2d 100644
--- a/kernel/signal.c
+++ b/kernel/signal.c
@@ -2237,7 +2237,7 @@ static int do_tkill(int tgid, int pid, i
    info.si_uid = current->uid;

    read_lock(&tasklist_lock);
- p = find_task_by_pid_ns(pid, current->nsproxy->pid_ns);
+ p = find_task_by_vpid(pid);
    if (p && (tgid <= 0 || task_tgid_vnr(p) == tgid)) {

```

```

    error = check_kill_permission(sig, &info, p);
/*
diff --git a/kernel/sys.c b/kernel/sys.c
index 787b73e..796299c 100644
--- a/kernel/sys.c
+++ b/kernel/sys.c
@@ -151,8 +151,7 @@ asmlinkage long sys_setpriority(int which
    switch (which) {
        case PRIO_PROCESS:
            if (who)
-   p = find_task_by_pid_ns(who,
-   current->nsproxy->pid_ns);
+   p = find_task_by_vpid(who);
            else
                p = current;
            if (p)
@@ -209,8 +208,7 @@ asmlinkage long sys_getpriority(int which
    switch (which) {
        case PRIO_PROCESS:
            if (who)
-   p = find_task_by_pid_ns(who,
-   current->nsproxy->pid_ns);
+   p = find_task_by_vpid(who);
            else
                p = current;
            if (p) {
@@ -1065,7 +1063,8 @@ asmlinkage long sys_setsid(void)
    * session id and so the check will always fail and make it so
    * init cannot successfully call setsid.
    */
-   if (session > 1 && find_task_by_pid_type(PIDTYPE_PGID, session))
+   if (session > 1 && find_task_by_pid_type_ns(PIDTYPE_PGID,
+   session, &init_pid_ns))
        goto out;

    group_leader->signal->leader = 1;
diff --git a/mm/mempolicy.c b/mm/mempolicy.c
index a09ca3b..c1592a9 100644
--- a/mm/mempolicy.c
+++ b/mm/mempolicy.c
@@ -941,8 +941,7 @@ asmlinkage long sys_migrate_pages(pid_t

    /* Find the mm_struct */
    read_lock(&tasklist_lock);
-   task = pid ?
-   find_task_by_pid_ns(pid, current->nsproxy->pid_ns) : current;
+   task = pid ? find_task_by_vpid(pid) : current;
    if (!task) {

```

```
    read_unlock(&tasklist_lock);
    return -ESRCH;
diff --git a/mm/migrate.c b/mm/migrate.c
index 6f7e4f3..7fff95d 100644
--- a/mm/migrate.c
+++ b/mm/migrate.c
@@ -931,8 +931,7 @@ asmlinkage long sys_move_pages(pid_t pid

/* Find the mm_struct */
read_lock(&tasklist_lock);
- task = pid ?
- find_task_by_pid_ns(pid, current->nsproxy->pid_ns) : current;
+ task = pid ? find_task_by_vpid(pid) : current;
if (!task) {
    read_unlock(&tasklist_lock);
    return -ESRCH;
```

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
