

Changes since v.4:

- * make SLAB_NOTIFY caches mark pages as SlabDebug. That makes the interesting paths simpler (thanks to Christoph);
- * the change above caused appropriate changes in "turn notifications on" path - all available pages must become SlabDebug and page's freelists must be flushed;
- * added two more events - "on" and "off" to make kmalloc caches disabling more gracefully;
- * turning notifications "off" is marked as "TODO". Right now it's hard w/o massive rework of slub.c in respect to full slabs handling.

Changes since v.3:

- * moved alloc/free notification into slow path and make "notify-able" caches walk this path always;
- * introduced some optimization for the case, when there's only one listener for SLUB events (saves more that 10% of performance);
- * ported on 2.6.23-rc6-mm1 tree.

Changes since v.2:

- * introduced generic notifiers for slub. right now there are only events, needed by accounting, but this set can be extended in the future;
- * moved the controller core into separate file, so that its extension and/or porting on sLAb will look more logical;
- * fixed this message :).

Changes since v.1:

- * fixed Paul's comment about subsystem registration;
- * return ERR_PTR from ->create callback, not NULL;
- * make container-to-object assignment in rcu-safe section;
- * make turning accounting on and off with "1" and "0".

=====

Long time ago we decided to start memory control with the user memory container. Now this container in -mm tree and I think we can start with the kmem one.

First of all - why do we need this kind of control. The major "pros" is that kernel memory control protects the system from DoS attacks by processes that live in container. As our

experience shows many exploits simply do not work in the container with limited kernel memory.

I can split the kernel memory container into 4 parts:

1. kmalloc-ed objects control
2. vmalloc-ed objects control
3. buddy allocated pages control
4. kmem_cache_alloc-ed objects control

the control of first tree types of objects has one peculiarity: one need to explicitly point out which allocations he wants to account and this becomes not-configurable and is to be discussed.

On the other hands such objects as anon_vma-s, file-s, sighangds, vfsmounts, etc are created by user request always and should always be accounted. Fortunately they are allocated from their own caches and thus the whole kmem cache can be accountable.

This is exactly what this patchset does - it adds the ability to account for the total size of kmem-cache-allocated objects from specified kmem caches.

This is based on the SLUB allocator, Paul's control groups and the resource counters I made for RSS controller and which are in -mm tree already.

To play with it, one need to mount the container file system with -o kmem and then mark some caches as accountable via /sys/slab/<cache_name>/cache_notify.

As I have already told kmalloc caches cannot be accounted easily so turning the accounting on for them will fail with -EINVAL.

Turning the accounting off is possible only if the cache has no objects. This is done so because turning accounting off implies marking of all the slabs in the cache as not-debug, but due to full-pages in slub are not stored in any lists (usually) this is impossible to do so, however this is in todo list.

Thanks,
Pavel
