
Subject: [PATCH] Make initializer for statically declared krefs
Posted by [Pavel Emelianov](#) on Mon, 01 Oct 2007 10:27:24 GMT
[View Forum Message](#) <> [Reply to Message](#)

Since the struct kref already has the _get, _put and _init routines, this seems useful to have an initializer for those statically declared (like for atomic_t or spinlock_t).

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/include/linux/kref.h b/include/linux/kref.h
index 6fee353..a84c582 100644
--- a/include/linux/kref.h
+++ b/include/linux/kref.h
@@ -24,6 +24,8 @@ struct kref {
     atomic_t refcount;
 };

+#define INIT_KREF(count) { .refcount = ATOMIC_INIT(count), }
+
void kref_init(struct kref *kref);
void kref_get(struct kref *kref);
int kref_put(struct kref *kref, void (*release) (struct kref *kref));
diff --git a/init/version.c b/init/version.c
index 9d17d70..53d2ca7 100644
--- a/init/version.c
+++ b/init/version.c
@@ -19,9 +19,7 @@
int version_string(LINUX_VERSION_CODE);

struct uts_namespace init_uts_ns = {
- .kref = {
- .refcount = ATOMIC_INIT(2),
- },
+ .kref = INIT_KREF(2),
 .name = {
 .sysname = UTS_SYSNAME,
 .nodename = UTS_NODENAME,
diff --git a/ipc/util.c b/ipc/util.c
index fd29246..526aa14 100644
--- a/ipc/util.c
+++ b/ipc/util.c
@@ -45,9 +45,7 @@ struct ipc_proc_iface {
};

struct ipc_namespace init_ipc_ns = {
```

```

- .kref = {
- .refcount = ATOMIC_INIT(2),
- },
+ .kref = INIT_KREF(2),
};

static struct ipc_namespace *clone_ipc_ns(struct ipc_namespace *old_ns)
diff --git a/kernel/pid.c b/kernel/pid.c
index d7388d7..e9d3ff1 100644
--- a/kernel/pid.c
+++ b/kernel/pid.c
@@ -69,9 +69,7 @@ static inline int mk_pid(struct pid_name
 * the scheme scales to up to 4 million PIDs, runtime.
 */
struct pid_namespace init_pid_ns = {
- .kref = {
- .refcount = ATOMIC_INIT(2),
- },
+ .kref = INIT_KREF(2),
  .pidmap = {
    [ 0 ... PIDMAP_ENTRIES-1] = { ATOMIC_INIT(BITS_PER_PAGE), NULL }
  },
diff --git a/kernel/user_namespace.c b/kernel/user_namespace.c
index 7af90fc..33d21e0 100644
--- a/kernel/user_namespace.c
+++ b/kernel/user_namespace.c
@@ -11,9 +11,7 @@
#include <linux/user_namespace.h>

struct user_namespace init_user_ns = {
- .kref = {
- .refcount = ATOMIC_INIT(2),
- },
+ .kref = INIT_KREF(2),
  .root_user = &root_user,
};

```
