Subject: Re: [PATCH 1/5] The config option itself Posted by serue on Mon, 01 Oct 2007 15:53:17 GMT View Forum Message <> Reply to Message

```
Quoting Pavel Emelyanov (xemul@openvz.org):
> The option is called NAMESPACES. It can be selectable only
> if EMBEDDED is chosen (this was Eric's requisition). When
> the EMBEDDED is off namespaces will be on automatically.
> One more option (NAMESPACES_EXPERIMENTAL) was added by
> Serge's request to move there all the namespaces that are
> not finished yet. Currently only the user and the network
> namespaces are such. This option is selectable all the
> time NAMESPACES are "y" regardless of EMBEDDED one.
> Signed-off-by: Pavel Emelyanov <xemul@openvz.org>
> Acked-by: Cedric Le Goater <clg@fr.ibm.com>
Looks good. Thanks.
Acked-by: Serge Hallyn <serue@us.ibm.com>
(for the whole set, just to save the list from a few emails)
-serge
>
> diff --git a/init/Kconfig b/init/Kconfig
> index 6bb603a..67b1e41 100644
> --- a/init/Kconfig
> +++ b/init/Kconfig
> @ @ -390,6 +381,23 @ @ config RELAY
>
    If unsure, say N.
>
> +config NAMESPACES
> + bool "Namespaces support" if EMBEDDED
> + default !EMBEDDED
> + help
> + Provides the way to make tasks work with different objects using
> + the same id. For example same IPC id may refer to different objects
> + or same user id or pid may refer to different tasks when used in
   different namespaces.
> +config NAMESPACES_EXPERIMENTAL
> + bool "Add experimental namespaces support"
```

- > + depends on NAMESPACES && EXPERIMENTAL
- > + default n
- > + help
- > + Also include the support for the namespaces that are not fnished
- > + or well developed yet
- > +
- > config BLK_DEV_INITRD
- > bool "Initial RAM filesystem and RAM disk (initramfs/initrd) support"
- > depends on BROKEN || !FRV