

---

Subject: Split a server into security units - what is the best way?

Posted by [bjmg](#) on Wed, 22 Mar 2006 08:30:38 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Hello again,

This time I have a question about the performance of openvz. We want to use openvz to split a quite large server into several "security units".

This is the configuration of that server:

Dual Intel Pentium 4 Xeon HT EM64T with 3.2GHz (2 physical CPUs + 2 virtual CPUs)

4 GB of RAM

SATA-Raid in Mirroring Mode

Centos 4.3 x86\_64 (Host System)

Debian Sarge AMD64 (inside VPSs)

Now we want to run a quite large database server (MySQL) on it. The databases have a file size of about 20 GB (growing rate: 1.2GB/month). So MySQL needs a lot of RAM to be fast enough to handle that. I would say: MySQL should get about 3072 MB of RAM and "most" of the CPU power. That MySQL server should run on its own VPS (using Debian Sarge AMD64 as VPS-OS). In addition to that MySQL-VPS we need a development system, a testing system and a system that runs some network/traffic accounting tools. These servers are low priority servers and we think that they don't need much CPU power and also not that much RAM.

Here is a small table that shows the "promised" CPU power for the VPSs from above:

80% MySQL-System

10% Development-System

10% Network-Accounting-System

00% Testing-System (not needed every day)

If this is not optimal, please give us other values.

Now what is the best way to create a config like that?

I thought vzsplite should do the job. I thought splitting the server into 10 parts  $((80+10+10)/10)$  and then multiplying the values for the MySQL-System with 8 would be perfect. What do you think about that? Is that the right way?

Thank you!

Bernhard

---