
Subject: [PATCH][NET-2.6.24] Remove double dev->flags checking when calling dev_close()

Posted by [Pavel Emelianov](#) on Tue, 09 Oct 2007 10:50:54 GMT

[View Forum Message](#) <> [Reply to Message](#)

The unregister_netdevice() and dev_change_net_namespace() both check for dev->flags to be IFF_UP before calling the dev_close(), but the dev_close() checks for IFF_UP itself, so remove those unneeded checks.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/net/core/dev.c b/net/core/dev.c
```

```
index e7e728a..1e169a5 100644
```

```
--- a/net/core/dev.c
```

```
+++ b/net/core/dev.c
```

```
@@ -3893,8 +3893,7 @@ void unregister_netdevice(struct net_dev
    BUG_ON(dev->reg_state != NETREG_REGISTERED);
```

```
    /* If device is running, close it first. */
```

```
    - if (dev->flags & IFF_UP)
```

```
    - dev_close(dev);
```

```
    + dev_close(dev);
```

```
    /* And unlink it from device chain. */
```

```
    unlist_netdevice(dev);
```

```
@@ -4018,8 +4017,7 @@ int dev_change_net_namespace(struct net_
    */
```

```
    /* If device is running close it first. */
```

```
    - if (dev->flags & IFF_UP)
```

```
    - dev_close(dev);
```

```
    + dev_close(dev);
```

```
    /* And unlink it from device chain */
```

```
    err = -ENODEV;
```
