

---

Subject: [PATCH 5/6][NET-2.6.24] Make the IRDA use the seq\_open\_private()  
Posted by Pavel Emelianov on Tue, 09 Oct 2007 16:01:32 GMT

[View Forum Message](#) <> [Reply to Message](#)

---

Just switch to the consolidated code

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>  
Cc: Samuel Ortiz <samuel@sortiz.org>

---

```
diff --git a/net/irda/irlap.c b/net/irda/irlap.c
index 3d76aaf..f3236ac 100644
--- a/net/irda/irlap.c
+++ b/net/irda/irlap.c
@@ -1219,29 +1219,11 @@ static const struct seq_operations irlap

static int irlap_seq_open(struct inode *inode, struct file *file)
{
- struct seq_file *seq;
- int rc = -ENOMEM;
- struct irlap_iter_state *s = kzalloc(sizeof(*s), GFP_KERNEL);
+ if (irlap == NULL)
+ return -EINVAL;

- if (!s)
- goto out;
-
- if (irlap == NULL) {
- rc = -EINVAL;
- goto out_kfree;
- }
-
- rc = seq_open(file, &irlap_seq_ops);
- if (rc)
- goto out_kfree;
-
- seq     = file->private_data;
- seq->private = s;
-out:
- return rc;
-out_kfree:
- kfree(s);
- goto out;
+ return seq_open_private(file, &irlap_seq_ops,
+ sizeof(struct irlap_iter_state));
}
```

```

const struct file_operations irlap_seq_fops = {
diff --git a/net/irda/irlmp.c b/net/irda/irlmp.c
index 7efa930..7db92ce 100644
--- a/net/irda/irlmp.c
+++ b/net/irda/irlmp.c
@@ @ -2003,27 +2003,10 @@ static const struct seq_operations irlmp

static int irlmp_seq_open(struct inode *inode, struct file *file)
{
- struct seq_file *seq;
- int rc = -ENOMEM;
- struct irlmp_iter_state *s;
-
- IRDA_ASSERT(irlmp != NULL, return -EINVAL;);

- s = kmalloc(sizeof(*s), GFP_KERNEL);
- if (!s)
- goto out;
-
- rc = seq_open(file, &irlmp_seq_ops);
- if (rc)
- goto out_kfree;
-
- seq     = file->private_data;
- seq->private = s;
-out:
- return rc;
-out_kfree:
- kfree(s);
- goto out;
+ return seq_open_private(file, &irlmp_seq_ops,
+ sizeof(struct irlmp_iter_state));
}


```

```

const struct file_operations irlmp_seq_fops = {
diff --git a/net/irda/irtpp.c b/net/irda/irtpp.c
index 3d7ab03..1311976 100644
--- a/net/irda/irtpp.c
+++ b/net/irda/irtpp.c
@@ @ -1884,25 +1884,8 @@ static const struct seq_operations irtpp

static int irtpp_seq_open(struct inode *inode, struct file *file)
{
- struct seq_file *seq;
- int rc = -ENOMEM;
- struct irtpp_iter_state *s;
-
- s = kzalloc(sizeof(*s), GFP_KERNEL);

```

```
- if (!s)
- goto out;
-
- rc = seq_open(file, &irtp_seq_ops);
- if (rc)
- goto out_kfree;
-
- seq    = file->private_data;
- seq->private = s;
-out:
- return rc;
-out_kfree:
- kfree(s);
- goto out;
+ return seq_open_private(file, &irtp_seq_ops,
+ sizeof(struct irtp_iter_state));
}
```

```
const struct file_operations irtp_seq_fops = {
```

---