
Subject: Re: [PATCH 2/3] Lost locking in fl6_sock_lookup
Posted by [Pavel Emelianov](#) on Thu, 18 Oct 2007 12:11:58 GMT
[View Forum Message](#) <> [Reply to Message](#)

YOSHIFUJI Hideaki wrote:

> In article <47174950.6060409@openvz.org> (at Thu, 18 Oct 2007 15:53:52 +0400), Pavel Emelyanov <xemul@openvz.org> says:

>
>> This routine scans the ipv6_fl_list whose update is
>> protected with the socket lock and the ip6_sk_fl_lock.
>
>> struct ip6_flowlabel *fl = sfl->fl;
>> if (fl->label == label) {
>> + read_unlock_bh(&ip6_sk_fl_lock);
>> fl->lastuse = jiffies;
>> atomic_inc(&fl->users);
>> return fl;
>
> We should increment fl->users within the critical section, shouldn't we?

Not necessary. The users is more than zero (because it is linked in the sock's list) so garbage collector won't catch it in any way.

Thanks,
Pavel

> --yoshfji
> -
> To unsubscribe from this list: send the line "unsubscribe netdev" in
> the body of a message to majordomo@vger.kernel.org
> More majordomo info at <http://vger.kernel.org/majordomo-info.html>
>
