
Subject: [RFC][PATCH] memory cgroup enhancements updated [5/10] per cpu accounting

Posted by KAMEZAWA Hiroyuki on Fri, 19 Oct 2007 09:32:03 GMT

[View Forum Message](#) <> [Reply to Message](#)

Add statistics account infrastructure for memory controller.

Changelog v1 -> v2

- Removed Charge/Uncharge counter
- reflected comments.
- changes __move_lists() args.
- changes __mem_cgroup_stat_add() name, comment and added VM_BUGON

Changes from original:

- divided into 2 patch (account and show info)
- changed from u64 to s64
- added mem_cgroup_stat_add() and batched statistics modification logic.
- removed stat init code because mem_cgroup is allocated by kzalloc().

Signed-off-by: KAMEZAWA Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

Signed-off-by: YAMAMOTO Takashi <yamamoto@valinux.co.jp>

mm/memcontrol.c | 120 ++++++-----
1 file changed, 113 insertions(+), 7 deletions(-)

Index: devel-2.6.23-mm1/mm/memcontrol.c

=====

```
--- devel-2.6.23-mm1.orig/mm/memcontrol.c
+++ devel-2.6.23-mm1/mm/memcontrol.c
@@ -35,6 +35,64 @@ struct cgroup_subsys mem_cgroup_subsys;
 static const int MEM_CGROUP_RECLAIM_RETRIES = 5;

/*
+ * Statistics for memory cgroup.
+ */
+enum mem_cgroup_stat_index {
+ /*
+ * For MEM_CONTAINER_TYPE_ALL, usage = pagecache + rss.
+ */
+ MEM_CGROUP_STAT_PAGECACHE, /* # of pages charged as cache */
+ MEM_CGROUP_STAT_RSS, /* # of pages charged as rss */
+
+ /*
+ * usage = charge - uncharge.
+ */
+ MEM_CGROUP_STAT_ACTIVE, /* # of pages in active list */
+ MEM_CGROUP_STAT_INACTIVE, /* # of pages on inactive list */
```

```

+
+ MEM_CGROUP_STAT_NSTATS,
+};
+
+struct mem_cgroup_stat_cpu {
+ s64 count[MEM_CGROUP_STAT_NSTATS];
+} ____cacheline_aligned_in_smp;
+
+struct mem_cgroup_stat {
+ struct mem_cgroup_stat_cpu cpustat[NR_CPUS];
+};
+
+/*
+ * For batching....mem_cgroup_charge_statistics()(see below).
+ * MUST be called under preempt_disable().
+ */
+static inline void __mem_cgroup_stat_add(struct mem_cgroup_stat *stat,
+ enum mem_cgroup_stat_index idx, int val)
+{
+ int cpu = smp_processor_id();
+#ifdef CONFIG_PREEMPT
+ VM_BUG_ON(preempt_count() == 0);
+#endif
+ stat->cpustat[cpu].count[idx] += val;
+}
+
+static inline void mem_cgroup_stat_inc(struct mem_cgroup_stat *stat,
+ enum mem_cgroup_stat_index idx)
+{
+ preempt_disable();
+ __mem_cgroup_stat_add(stat, idx, 1);
+ preempt_enable();
+}
+
+static inline void mem_cgroup_stat_dec(struct mem_cgroup_stat *stat,
+ enum mem_cgroup_stat_index idx)
+{
+ preempt_disable();
+ __mem_cgroup_stat_add(stat, idx, -1);
+ preempt_enable();
+}
+
+/*
* The memory controller data structure. The memory controller controls both
* page cache and RSS per cgroup. We would eventually like to provide
* statistics based on the statistics developed by Rik Van Riel for clock-pro,
@@ -63,6 +121,10 @@ struct mem_cgroup {

```

```

*/
spinlock_t lru_lock;
unsigned long control_type; /* control RSS or RSS+Pagecache */
+ /*
+ * statistics.
+ */
+ struct mem_cgroup_stat stat;
};

/*
@@ -96,6 +158,33 @@ enum {
    MEM_CGROUP_TYPE_MAX,
};

+/*
+ * Batched statistics modification.
+ * We have to modify several values at charge/uncharge..
+ */
+static inline void
+mem_cgroup_charge_statistics(struct mem_cgroup *mem, int flags, int charge)
+{
+ int val = (charge)? 1 : -1;
+ struct mem_cgroup_stat *stat = &mem->stat;
+ preempt_disable();
+
+ if (flags & PCGF_PAGESHARE)
+     __mem_cgroup_stat_add(stat, MEM_CGROUP_STAT_PAGESHARE, val);
+ else
+     __mem_cgroup_stat_add(stat, MEM_CGROUP_STAT_RSS, val);
+
+ if (flags & PCGF_ACTIVE)
+     __mem_cgroup_stat_add(stat, MEM_CGROUP_STAT_ACTIVE, val);
+ else
+     __mem_cgroup_stat_add(stat, MEM_CGROUP_STAT_INACTIVE, val);
+
+ preempt_enable();
+}
+
+
+
+
static struct mem_cgroup init_mem_cgroup;

static inline
@@ -209,12 +298,27 @@ clear_page_cgroup(struct page *page, str

static void __mem_cgroup_move_lists(struct page_cgroup *pc, bool active)
{

```

```

+ int moved = 0;
+ struct mem_cgroup *mem = pc->mem_cgroup;
+
+ if (active && (pc->flags & PCGF_ACTIVE) == 0)
+ moved = 1; /* Move from inactive to active */
+ else if (!active && (pc->flags & PCGF_ACTIVE))
+ moved = -1; /* Move from active to inactive */
+
+ if (moved) {
+ struct mem_cgroup_stat *stat = &mem->stat;
+ preempt_disable();
+ __mem_cgroup_stat_add(stat, MEM_CGROUP_STAT_ACTIVE, moved);
+ __mem_cgroup_stat_add(stat, MEM_CGROUP_STAT_INACTIVE, -moved);
+ preempt_enable();
+ }
if (active) {
pc->flags |= PCGF_ACTIVE;
- list_move(&pc->lru, &pc->mem_cgroup->active_list);
+ list_move(&pc->lru, &mem->active_list);
} else {
pc->flags &= ~PCGF_ACTIVE;
- list_move(&pc->lru, &pc->mem_cgroup->inactive_list);
+ list_move(&pc->lru, &mem->inactive_list);
}
}
}

```

@@ -233,15 +337,12 @@ int task_in_mem_cgroup(struct task_struct *

```

void mem_cgroup_move_lists(struct page_cgroup *pc, bool active)
{
- struct mem_cgroup *mem;
if (!pc)
return;

- mem = pc->mem_cgroup;
-
- spin_lock(&mem->lru_lock);
+ spin_lock(&pc->mem_cgroup->lru_lock);
__mem_cgroup_move_lists(pc, active);
- spin_unlock(&mem->lru_lock);
+ spin_unlock(&pc->mem_cgroup->lru_lock);
}

```

unsigned long mem_cgroup_isolate_pages(unsigned long nr_to_scan,
@@ -440,6 +541,9 @@ noreclaim:

```

goto retry;
}
```

```

+ /* Update statistics vector */
+ mem_cgroup_charge_statistics(mem, pc->flags, true);
+
spin_lock_irqsave(&mem->lru_lock, flags);
list_add(&pc->lru, &mem->active_list);
spin_unlock_irqrestore(&mem->lru_lock, flags);
@@ -505,6 +609,7 @@ void mem_cgroup_uncharge(struct page_cgr
    spin_lock_irqsave(&mem->lru_lock, flags);
    list_del_init(&pc->lru);
    spin_unlock_irqrestore(&mem->lru_lock, flags);
+ mem_cgroup_charge_statistics(mem, pc->flags, false);
    kfree(pc);
}
}
@@ -580,6 +685,7 @@ retry:
css_put(&mem->css);
res_counter_uncharge(&mem->res, PAGE_SIZE);
list_del_init(&pc->lru);
+ mem_cgroup_charge_statistics(mem, pc->flags, false);
    kfree(pc);
} else /* being uncharged ? ...do relax */
    break;

```

Containers mailing list
 Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
