
Subject: [RFC][PATCH] memory cgroup enhancements updated [9/10] implicit force empty at rmdir

Posted by [KAMEZAWA Hiroyuki](#) on Fri, 19 Oct 2007 09:36:27 GMT

[View Forum Message](#) <> [Reply to Message](#)

This patch adds pre_destroy handler for mem_cgroup and try to make mem_cgroup empty at rmdir().

Signed-off-by: KAMEZAWA Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>

mm/memcontrol.c | 8 +++++++
1 file changed, 8 insertions(+)

Index: devel-2.6.23-mm1/mm/memcontrol.c

=====

--- devel-2.6.23-mm1.orig/mm/memcontrol.c

+++ devel-2.6.23-mm1/mm/memcontrol.c

@@ -959,6 +959,13 @@ mem_cgroup_create(struct cgroup_subsys *
 return &mem->css;
}

+static void mem_cgroup_pre_destroy(struct cgroup_subsys *ss,
+ struct cgroup *cont)

+{

+ struct mem_cgroup *mem = mem_cgroup_from_cont(cont);

+ mem_cgroup_force_empty(mem);

+}

+

static void mem_cgroup_destroy(struct cgroup_subsys *ss,
 struct cgroup *cont)

{

@@ -1010,6 +1017,7 @@ struct cgroup_subsys mem_cgroup_subsys =
 .name = "memory",

.subsys_id = mem_cgroup_subsys_id,

.create = mem_cgroup_create,

+ .pre_destroy = mem_cgroup_pre_destroy,

.destroy = mem_cgroup_destroy,

.populate = mem_cgroup_populate,

.attach = mem_cgroup_move_task,

Containers mailing list

Containers@lists.linux-foundation.org

<https://lists.linux-foundation.org/mailman/listinfo/containers>
