
Subject: [PATCH 2/3] Remove in-code externs for some functions from net/core/dev.c

Posted by Pavel Emelianov on Mon, 22 Oct 2007 15:25:35 GMT

[View Forum Message](#) <> [Reply to Message](#)

Inconsistent prototype and real type for functions may have worse consequences, than those for variables, so move them into a header.

Since they are used privately in net/core, make this file reside in the same place.

Signed-off-by: Pavel Emelyanov <xemul@openvz.org>

```
diff --git a/net/core/dev.c b/net/core/dev.c
index 8726589..9ea3665 100644
--- a/net/core/dev.c
+++ b/net/core/dev.c
@@ -120,6 +120,8 @@
#include <linux/ctype.h>
#include <linux/if_arp.h>

+#include "net-sysfs.h"
+
/*
 * The list of packet types we will receive (as opposed to discard)
 * and the routines to invoke.
@@ -249,10 +251,6 @@ static RAW_NOTIFIER_HEAD(netdev_chain);

DEFINE_PER_CPU(struct softnet_data, softnet_data);

-extern int netdev_kobject_init(void);
-extern int netdev_register_kobject(struct net_device *);
-extern void netdev_unregister_kobject(struct net_device *);
-
#endif CONFIG_DEBUG_LOCK_ALLOC
/*
 * register_netdevice() init dev->xmit_lock and sets lockdep class
diff --git a/net/core/net-sysfs.c b/net/core/net-sysfs.c
index 6628e45..61ead1d 100644
--- a/net/core/net-sysfs.c
+++ b/net/core/net-sysfs.c
@@ -18,6 +18,8 @@
#include <linux/wireless.h>
#include <net/iw_handler.h>
```

```
+#include "net-sysfs.h"
+
#endif CONFIG_SYSFS
static const char fmt_hex[] = "%#x\n";
static const char fmt_long_hex[] = "%#lx\n";
diff --git a/net/core/net-sysfs.h b/net/core/net-sysfs.h
new file mode 100644
index 0000000..a41683d
--- /dev/null
+++ b/net/core/net-sysfs.h
@@ -0,0 +1,8 @@
+#ifndef __NET_SYSFS_H__
#define __NET_SYSFS_H__
+
+int netdev_kobject_init(void);
+int netdev_register_kobject(struct net_device *);
+void netdev_unregister_kobject(struct net_device *);
+
#endif
--
```

1.5.3.4
