
Subject: Re: [RFC][PATCH] memory cgroup enhancements updated [3/10]

remember pagecache

Posted by [Balbir Singh](#) on Wed, 24 Oct 2007 13:56:34 GMT

[View Forum Message](#) <> [Reply to Message](#)

KAMEZAWA Hiroyuki wrote:

```
> Add PCGF_PAGECACHE flag to page_cgroup to remember "this page is
> charged as page-cache."
> This is very useful for implementing precise accounting in memory cgroup.
>
> Changelog v1 -> v2
>   - moved #define to out-side of struct definition
>
> Signed-off-by: KAMEZAWA Hiroyuki <kamezawa.hiroyu@jp.fujitsu.com>
> Signed-off-by: YAMAMOTO Takashi <yamamoto@valinux.co.jp>
>
> mm/memcontrol.c | 18 ++++++-----
> 1 file changed, 15 insertions(+), 3 deletions(-)
>
> Index: devel-2.6.23-mm1/mm/memcontrol.c
> =====
> --- devel-2.6.23-mm1.orig/mm/memcontrol.c
> +++ devel-2.6.23-mm1/mm/memcontrol.c
> @@ -83,7 +83,9 @@ struct page_cgroup {
>     struct mem_cgroup *mem_cgroup;
>     atomic_t ref_cnt; /* Helpful when pages move b/w */
>     /* mapped and cached states */
> + int flags;
> };
> +#define PCGF_PAGECACHE (0x1) /* charged as page-cache */
>
> enum {
>     MEM_CGROUP_TYPE_UNSPEC = 0,
> @@ -315,8 +317,8 @@ unsigned long mem_cgroup_isolate_pages(u
>     * 0 if the charge was successful
>     * < 0 if the cgroup is over its limit
>     */
> -int mem_cgroup_charge(struct page *page, struct mm_struct *mm,
> -    gfp_t gfp_mask)
> +static int mem_cgroup_charge_common(struct page *page, struct mm_struct *mm,
> +    gfp_t gfp_mask, int is_cache)
> {
>     struct mem_cgroup *mem;
>     struct page_cgroup *pc;
> @@ -418,6 +420,10 @@ noreclaim:
>     atomic_set(&pc->ref_cnt, 1);
>     pc->mem_cgroup = mem;
>     pc->page = page;
```

```
> + if (is_cache)
> + pc->flags = PCGF_PAGECACHE;
```

I prefer PAGE_CGROUP_CACHE since cache can be page cache/swap cache.

```
> + else
> + pc->flags = 0;
> if (page_cgroup_assign_new_page_cgroup(page, pc)) {
> /*
> * an another charge is added to this page already.
> @@ -442,6 +448,12 @@ err:
> return -ENOMEM;
> }
>
> +int mem_cgroup_charge(struct page *page, struct mm_struct *mm,
> + gfp_t gfp_mask)
> +{
> + return mem_cgroup_charge_common(page, mm, gfp_mask, 0);
```

Could we define

```
enum {
MEM_CGROUP_CHARGE_TYPE_CACHE = 0,
MEM_CGROUP_CHARGE_TYPE_MAPPED = 1,
};
```

and use the enums here and below.

```
> +}
> +
> /*
> * See if the cached pages should be charged at all?
> */
> @@ -454,7 +466,7 @@ int mem_cgroup_cache_charge(struct page
>
> mem = rcu_dereference(mm->mem_cgroup);
> if (mem->control_type == MEM_CGROUP_TYPE_ALL)
> - return mem_cgroup_charge(page, mm, gfp_mask);
> + return mem_cgroup_charge_common(page, mm, gfp_mask, 1);
> else
> return 0;
> }
```

--
Warm Regards,
Balbir Singh

Linux Technology Center
IBM, ISTL

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
