Subject: Re: [PATCH 2/2] CFS CGroup: Report usage Posted by Paul Menage on Fri, 26 Oct 2007 01:24:55 GMT View Forum Message <> Reply to Message

On 10/23/07, Srivatsa Vaddagiri <vatsa@linux.vnet.ibm.com> wrote: > > agreed, we need to be reporting idle time in (milli)seconds, although > the requirement we had was to report it back in percentage. I guess the > percentage figure can be derived from the raw idle time number. > > How about: > idle time = t4-t3 (effectively sleep time) > > > in the above example? > >> It doesn't seem guite right to me that a cgroup's idle time metric be > > affected by the activity of other cgroups on the machine, > > I don't see how the idle time metric defined above (t4-t3) can be

> affected by other cgroup activity, unless the execution pattern of one

> cgroup is dependent on the others.

If the other cgroups are busier, and t1-t2 is longer, then the cgroup will get to the point where it's ready to sleep later in wallclock time, and t4-t3 will be shorter in absolute terms. If there were no other cgroups running, then presumably the sleep time would actually be the sum of those three periods.

Even so, I guess you're right that t4-t3 is the most appropriate thing to report, as long as people realise that it's a bit of a fuzzy value.

> I think primarily for systems management tools to report back various

> statistics about a OpenVZ/VServer-like container (just like top reports stats

> for a OS currently). Let me check if there are other uses envisoned for
> it.

Sorry, I didn't mean "how will you report it to users?", I meant "what kinds of useful information will the users be able to get from it?"

Paul

Containers mailing list Containers@lists.linux-foundation.org https://lists.linux-foundation.org/mailman/listinfo/containers