
Subject: Re: [PATCH] pidns: Place under CONFIG_EXPERIMENTAL (take 2)
Posted by [akpm](#) on Sat, 27 Oct 2007 04:40:46 GMT
[View Forum Message](#) <> [Reply to Message](#)

On Fri, 26 Oct 2007 21:46:59 -0600 ebiederm@xmission.com (Eric W. Biederman) wrote:

> Andrew Morton <akpm@linux-foundation.org> writes:
>
> >> On Sat, 27 Oct 2007 04:04:08 +0200 Adrian Bunk <bunk@kernel.org> wrote:
> >> > be happy to hear if someone has a better idea.
> >>
> >> There is a difference between "complete the feature" and "early adopters
> >> to start playing with the feature" on the one side, and making something
> >> available in a released kernel on the other side.
> >>
> >> For development and playing with it it can depend on BROKEN (perhaps
> >> with the dependency removed through the first -rc kernels), but as soon
> >> as it's available in a -final kernel the ABI is fixed.
> >>
> >
> > Yes, if we're not 100% certain that the interfaces are correnct and unchanging
> > and that the implementation is solid, we should disable the feature at Kconfig
> > time.
>
> Reasonable. So far things look good for a single pid namespace. Multiple
> pid namespaces look iffy.
>
> > The best option would be to fix things asap. But assuming that option isn't
> > reasonable and/or safe, we can slip a `depends on BROKEN' into -rc6 then
> > resume development for 2.6.25.
>
> I think we can make a lot of progress but there is enough development
> yet to do to reach the target of correct and unchanging interfaces,
> with a solid interface. That unless we achieve a breakthrough I
> don't see us achieving that target for 2.6.24.
>
> The outstanding issues I can think of off the top of my head:
> - signal handling for init on secondary pid namespaces.
> - Properly setting si_pid on signals that cross namespaces.
> - The kthread API conversion so we don't get kernel threads
> trapped in pid namespaces and make them unfreeable.
> - At fork time I think we are doing a little bit too much work
> in setting the session and the pgrp, and removing the controlling
> tty.
> - AF_unix domain credential passing.
> - misc pid vs vpid sorting out (autofs autofs4, coda, arch specific
> syscalls, others?)
> - Removal of task->pid, task->tgid, task->signal->__pgrp,

- > tsk->signal->__session or some other way to ensure that we have
- > touched and converted all of the kernel pid handling.
- > - flock pid handling.

Given that a lot of this development will hopefully happen over the next two months, ...

- > It hurts me to even ponder what thinking makes it that
- > CONFIG_EXPERIMENTAL isn't enough to keep a stable distro
- > from shipping the code in their stable kernel, and locking us into
- > trouble.
- >
- > With that said. I think I should just respin the patchset now and add
- > the "depends on BROKEN".

it doesn't make sense to make it all dependent upon BROKEN now. Better would be to make it dependant upon CONFIG_SOMETHING_ELSE now, which depends upon EXPERIMENTAL and which will, around -rc6, be changed to depend upon BROKEN.

If that makes sense.

It's all a bit unusual and complex, but this is an exceptional set of features - let's hang in there.

Containers mailing list
Containers@lists.linux-foundation.org
<https://lists.linux-foundation.org/mailman/listinfo/containers>
